

QUICK SEAM SPLICE PRIMER SP-1924/A1

MSDS Number

BSCNR

National Stock Number

8030-00N045196

Product Name

QUICK SEAM SPLICE PRIMER SP-1924/A1

Manufacturer

FIRESTONE BUILDING PRODUCTS CO

Product Identification

Product ID:QUICK SEAM SPLICE PRIMER SP-1924/A1

MSDS Date:05/13/1991

FSC:8030

NIIN:00N045196

MSDS Number: BSCNR

Responsible Party

FIRESTONE BUILDING PRODUCTS CO

525 CONGRESSIONAL BLVD

CARMEL , IN 46032

US

Emergency Phone: 800-424-9300(CHEMTREC)

Info Phone: 216-379-6409

Cage: FIRES

Contractor

FIRESTONE BUILDING PRODUCTS CO

CARMEL, IN 46032-5000

US

615-231-3911

Cage: FIRES

Ingredients

SHOVEL OR SCOOP INTO A SEALABLE CONTAINER FOR

RTECS: 9999999ZZ

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC; (SOLVENT,

CAS: 64742-89-8

OSHA PELN/K

ACGIH TLV: N/K

(ORAL,RAT) 5 G/KG

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight:

OSHA PEL100 PPM;150 STEL

ACGIH TLV: 50 PPM, S

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

BUTENE, POLYMERS; (POLYBUTENE) (MFR CAS # 9003-28-5).

CAS: 9003-29-6

RTECS: EM9032000

Fraction By Weight:

OSHA PELN/K

ACGIH TLV: N/K

Hazards

LD50 LC50 Mixture:SEE INGREDIENTS

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: EYES: MAY CAUSE REDNESS, TEARING OR BLURRED VISION. EYE IRRIT INDEX - HIGHLY IRRIT. SKIN: PROLONGED OR REPEATED CONTACT MAY CAUSE SKIN IRRITATION AND DERMATITIS. MAY REMOVE NATURAL SKIN OILS (D EFATTING ACTION). SKIN IRRIT INDEX - MODERATELY IRRIT. INHAL: MAY CAUSE CNS DEPRESSION (NARCOSIS) (EFTS OF OVEREXP)

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:HLTH HAZ: CHARAC BY HDCH, DIZZ, MUSCULAR WEAKNESS & FATIGUE. MAY CAUSE UNCONSCIOUSNESS IF EXPOSURE IS EXCESSIVE. INGEST: CAUSES CHEM PNEUMONITIS IF ASPIRATED INTO THE LUNGS. MAY CAUSE UNCON. CHRONIC: MAY CAUSE LIVER & KIDNEY DAMAGE. MAY CAUSE BRAIN CELL DAMAGE. NOTE: TOLUENE APPEARS ON NAVY LIST OF OCCUP (SUPP DATA)

Medical Cond Aggravated by Exposure:ONE SPECIFIED BY MANUFACTURER.

First Aid

First Aid:EYE:HOLD EYELIDS OPEN & FLUSH THORO W/GENTLE STREAM OF WATER FOR @ LST 15 MIN, PREFERABLY AT EYEWASH FOUNTAIN. GET MED ATTN IF IRRIT PERSISTS. SKIN: WASH AFFECTED AREA THORO W/SOAP & WATER WHEN TIME PE RMITS. WASH HANDS & FACE THORO W/SOAP AND WATER BEFORE EATING, DRINKING OR SMOKING. INHAL: REMOVE TO FRESH UNCONTAM AIR. ADMIN O*2 IF BTHG IS LABORED. GIVE ARTF RESP IF BRTHG HAS STOPPED.(SUPP DATA)

Fire Fighting

Flash Point:10F,-12C

Lower Limits:1.2%

Extinguishing Media:ALCOHOL FOAM, CARBON DIOXIDE OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT . TOXIC FUMES AND VAPORS MAY BE EVOLVED.

Unusual Fire/Explosion Hazard:HEAT BUILDS UP PRESSURE IN CLOSED CONTAINERS. COOL WITH WATER STREAM.

Accidental Release

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. CONTROL THE SOURCE OF THE SPILL IF IT IS SAFE TO DO SO. VENTILATE ENCLOSED AREAS TO PVNT VAP ACCUM. RESTRICT ACCESS BY UNAUTHORIZED PERSONNEL. ABSORB SPILLED PRODUCT W/ VERMICULITE OR OTHER ABSORBENT MATL. (ING 4)

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAMES. KEEP CNTNR CLOSED. STORE AT ROOM TEMPERATURE WITH GOOD VENTILATION.

Other Precautions:VAPORS OF THIS MATL ARE HEAVIER THAN AIR AND WILL

COLLECT IN LOW OR CONFINED AREAS. GROUND DISPENSING EQUIPMENT TO AVOID STATIC DISCHARGE. EMPTIED CONTAINERS MAY RETAIN HAZARDOUS PROPERTIES. DO NOT CUT OR WELD ON OR NEAR CONTAINER.

Exposure Controls

Respiratory Protection:USE NIOSH/MSHA APPROVED CHEMICAL CARTRIDGE RESPIRATOR FOR ORGANIC VAPORS IF EXPOSURE MIGHT EXCEED THE TLV.
Ventilation:USE IN A WELL-VENTILATED LOCATION.
Protective Gloves:WEAR BUTYL GLOVES.
Eye Protection:WEAR SAFETY GLASSES WITH SIDE SHIELDS.
Other Protective Equipment:NONE REQUIRED.
Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.
Supplemental Safety and Health
EFFECTS OF OVEREXPOSURE: CHEM REPROD HAZ. SEEK CONSULTATION FROM APPROPRIATE HEALTH PROFESSIONALS CONCERNING LATEST HAZ LIST INFO & SAFE HANDLING INFO.
FIRST AID PROC: GET MED ATTENTION IMMEDIATELY IF OXYGEN OR ARTIFICIAL RESPIRATION ARE ADMINISTERED. INGESTION: CONTINUE PETROLEUM DISTILLATES. DO NOT INDUCE VOMIT. GET MED ATTENTION & ADVICE REGARDING THE NATURE OF MATERIAL.

Chemical Properties

HCC:F3
Boiling Pt:Boiling Point:185F,85C
Vapor Pressure:38 @ 68F
Vapor Density:3.6
Specific Gravity:0.73 (H₂O=1)
Evaporation Rate & Reference:3.5 (ETHER=1)
Solubility in Water:NEGLECTIBLE
Appearance and Odor:AMBER TO GRAY/CHARACTERISTIC ALIPHATIC SOLVENT ODOR.
Percent Volatiles by Volume:92

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:HEAT, SPARKS, AND OPEN FLAMES.
Hazardous Decomposition Products:CARBON DIOXIDE AND CARBON MONOXIDE, ALDEHYDES, PARTIALLY BURNED CARBON.

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL ENVIRONMENTAL AND WASTE REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.