

ASBESTOS FILLED SPIRAL WOUND GASKET

MSDS Number

BSCYS

National Stock Number

5330-01-083-5516

Product Name

ASBESTOS FILLED SPIRAL WOUND GASKET

Manufacturer

FLEXITALLIC GASKET CO INC

Product Identification

Product ID:ASBESTOS FILLED SPIRAL WOUND GASKET

MSDS Date:07/09/1989

FSC:5330

NIIN:01-083-5516

MSDS Number: BSCYS

Responsible Party

FLEXITALLIC GASKET CO INC.

6915 LAPORTE RD

DEER PARK , TX 77536

US

Emergency Phone: 713-479-3491

Info Phone: 713-479-3491

Cage: 58156

Contractor

FLEXITALLIC GASKET CO INC.

760

DEER PARK, TX 77536

US

713-479-3491

Cage: 58156

Ingredients

ASBESTOS, CHRYSOTILE

CAS: 12001-29-5

RTECS: CI6478500

OSHA PEL0.2 FIBERS/CC

ACGIH TLV: 2 FIBERS/CC; A1;9293

LATEX RUBBER

Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:BREATHING OF ASBESTOS FIBERS IN SIGNIFIGANT AMOUNTS MAY PRODUCE IRREVERSIBLE LUNG DISEASE AND CANCER.

Explanation of Carcinogenicity:CONTAINS ASBESTOS [12001-21-9] WHICH IS

LISTED BY NTP AND IARC AND REGULATED BY OSHA AS A CARCINOGEN.
Effects of Overexposure:LOSS OF BREATHING CAPACITY, SHORTNESS OF BREATH.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.
HMIS:PULMONARY DISEASES

First Aid

First Aid:NONE SPECIFIED BY MANUFACTURER.

Fire Fighting

Flash Point:NONE
Extinguishing Media:MEDIA APPROPRIATE FOR SURROUNDING FIRE.
Fire Fighting Procedures:NONE SPECIFIED BY MANUFACTURER. HMIS: WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING.
Unusual Fire/Explosion Hazard:NONE

Accidental Release

Spill Release Procedures:VACUUM FINES AND DUST, CAREFULLY AVOIDING DUSTING. IF SWEEPING BY HAND, CONTROL DUST BY WETTING AREA AND WEAR APPROPRIATE RESPIRATORY PROTECTION.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Other Precautions:SEE OTHER REGULATIONS FOR ASBESTOS HANDLING IN 29 CFR 1910 SUBPART 2 PARAGRAPH 1910.1001.

Exposure Controls

Respiratory Protection:IF ENGINEERING CONTROLS FAIL OR EMERGENCY OCCURS, USE NIOSH/MSHA APPROVED RESPIRATOR. USE IAW 29 CFR 1910.134.
Ventilation:USE ADEQUATE MECHANICAL VENTILATION WITH HEPA FILTERS.
Protective Gloves:NONE NORMALLY REQUIRED.
Eye Protection:SAFETY GLASSES
Other Protective Equipment:NONE NORMALLY REQUIRED.
Work Hygienic Practices:WASH HANDS AFTER USE AND BEFORE EATING, DRINKING, OR SMOKING. KEEP WORK AREA CLEAN OF ASBESTOS DUST.
Supplemental Safety and Health

Chemical Properties

HCC:T6
Spec Gravity:2.50 (WATER=1)
Solubility in Water:NEGLIGIBLE
Appearance and Odor:LIGHT BLUE GASKET WITH NO ODOR

Stability

Stability Indicator/Materials to Avoid:YES
NONE SPECIFIED BY MANUFACTURER.
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.
Hazardous Decomposition Products:NONE SPECIFIED BY MANUFACTURER.

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.