

## **713 WHITE AND RED LAGGING ADHESIVE AND COATING**

### **MSDS Number**

BSCYZ

### **National Stock Number**

2590-01-114-7396

### **Product Name**

713 WHITE AND RED LAGGING ADHESIVE AND COATING

### **Manufacturer**

VIMASCO CORP

### **Product Identification**

Product ID: 713 WHITE AND RED LAGGING ADHESIVE AND COATING

MSDS Date: 02/09/1990

FSC: 2590

NIIN: 01-114-7396

MSDS Number: BSCYZ

### **Responsible Party**

VIMASCO CORP

NITRO , WV 25143-0516

US

Emergency Phone: 304-755-3328

Info Phone: 304-755-3328

Preparer: JOHN TIDQUIST

Cage: 14947

### **Contractor**

VIMASCO CORP

516

NITRO, WV 25143

US

304-755-3328

Cage: 14947

### **Ingredients**

ETHYLENE GLYCOL (SARA III)

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight:

OSHA PELC 50 PPM

ACGIH TLV: C 50 PPM,VAPOR; 9293

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

PARAFFIN WAX AND HYDROCARBON WAX CHLORINATED

CAS: 63449-39-8

Fraction By Weight:

VINYL ACETATE (SARA III)

CAS: 108-05-4

RTECS: AK0875000

Fraction By Weight:

OSHA PEL10 PPM/20 STEL

ACGIH TLV: 10 PPM/20 STEL; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

HEXYLENE GLYCOL

CAS: 107-41-5

RTECS: SA0810000

Fraction By Weight:

OSHA PELC 25 PPM

ACGIH TLV: C 25 PPM; 9293

## Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: INHALATION MAY CAUSE NASAL AND RESPIRATORY IRRITATION. CONTACT MAY IRRITATE SKIN AND EYES.

INGESTION MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS, KIDNEY INJURY, DEATH. CHRONIC: PROLONGED OR REPEAT ED EXPOSURE MAY CAUSE LIVER DAMAGE.

Explanation of Carcinogenicity:VINYL ACETATE HAS BEEN REPORTED TO CAUSE CANCER IN LABORATORY ANIMALS.

Effects of Overexposure:INHALED: COUGHING, SHORTNESS OF BREATH, SNEEZING. EYES: REDNESS, TEARING, DISCOMFORT. SKIN: REDNESS, ITCHING, DISCOMFORT. INGESTED: DRUNKENNESS, COMA, NAUSEA, VOMITING.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

## First Aid

First Aid:SKIN: WASH WITH SOAPAND WATER. EYES: FLUSH WITH LOTS OF WATER FOR 15 MINUTES. CONSULT WITH DOCTOR IF IRRITATION PERSISTS.

INHALED: REMOVE TO FRESH AIR. ADMINISTER OXYGEN IF BREATHING DIFFICULT. SEE DO CTOR IF SYMPTOMS PERSIST. INGESTED: IF CONSCIOUS, GIVE 2 GLASSES OF WATER; THEN INDUCE VOMITING. CALL DOCTOR OR POISON CONTROL CENTER.

## Fire Fighting

Flash Point Method:TCC

Flash Point:NONE

Extinguishing Media:FOAM, ALCOHOL FOAM, CARBON DIOXIDE, DRY CHEMICAL, WATER FOG

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR. PRODUCT WILL NOT BURN UNLESS HAS DRIED TO SOLID FILM.

Unusual Fire/Explosion Hazard:NONE KNOWN

## Accidental Release

Spill Release Procedures:COLLECT FOR DISPOSAL. SMALL SPILLS MAY BE FLUSHED TO SEWER IF LOCAL REGULATIONS PERMIT.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

## Handling

Handling and Storage Precautions:STORE INDOORS AT TEMPERATURES OF 45-90F. KEEP CONTAINER CLOSED. AVOID BREATHING VAPORS AND APPLICATION TO HOT SURFACES.

Other Precautions:FOR INDUSTRIAL/PROFESSIONAL USE ONLY. NOT INTENDED FOR RETAIL SALE OR USE BY INDIVIDUAL CUSTOMERS. DO NOT REUSE CONTAINER FOR POTABLES OR EDIBLES.

## Exposure Controls

Respiratory Protection:IF ENGINEERING CONTROLS FAIL, NON-ROUTINE USE OR EMERGENCY OCCURS; USE NIOSH/MSHA APPROVED RESPIRATOR OR SUPPLIED AIR RESPIRATOR OR SCBA, AS REQUIRED. USE IAW 29 CFR 1910.134.

Ventilation:USE ADEQUATE MECHANICAL VENTILATION.

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY GLASSES/FACESHIELD

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:WASH HANDS AFTER USE AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDRY CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

## Chemical Properties

HCC:N1

Boiling Pt:B.P. Text:212F,100C

Decomp Temp:Decomp Text:340F,171C

Vapor Density:Spec Gravity:1.29 (WATER=1)

pH:>8.0

Viscosity:75000CENTIPOI

Evaporation Rate & Reference:Solubility in Water:APPRECIABLE

Appearance and Odor:VISCOUS, WHITE OR RED PASTE WITH MILD LATEX ODOR

Percent Volatiles by Volume:60

## Stability

Stability Indicator/Materials to Avoid:YES

MATERIALS INCOMPATIBLE WITH WATER.

Stability Condition to Avoid:NONE KNOWN

Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE, HYDROGEN CHLORIDE, ANTIMONY-OXYCHLORIDE AND FRAGMENTED SHORT-CHAIN HYDROCARBONS,

## Disposal

Waste Disposal Methods:CHECK WITH LOCAL, STATE AUTHORITIES PRIOR TO ALLOWING TO ENTER SEWER. DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.