

EP-E CARTRIDGE, R74-1001, R74-1002, R74-1003, R74-1004

MSDS Number

BSDDD

National Stock Number

6850-01-376-1766

Product Name

EP-E CARTRIDGE, R74-1001, R74-1002, R74-1003, R74-1004

Manufacturer

CANON USA INC

Product Identification

Product ID:EP-E CARTRIDGE, R74-1001, R74-1002, R74-1003, R74-1004 MSDS Date: 08/01/1993

FSC:6850 NIIN:01-376-1766 MSDS Number: BSDDD

Responsible Party

CANON USA INC

ONE CANON PLAZA

LAKE SUCCESS, NY 11042-1113

US

Emergency Phone: 516-488-6700

Info Phone: 516-488-6700 Preparer: JOSEPH PALMERI

Cage: 1BA63 **Contractor**

UNITED LASER (808-941-1220)

LAKE SUCCESS, NY 11042

US

516-328-5600 Cage: ULASO

Ingredients

STYRENE ACRYLATE COPOLYMER

Fraction By Weight: 45-55%

IRON OXIDE

CAS: 1317-61-9

Fraction By Weight: 45-55%

Hazards

LD50 LC50 Mixture:TLV: 10 MG/M3 (TOTAL DUST) Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: INHALATION-GASPING, DO NOT BREATHE DUST. EYE-NO SPECIFIC HAZARD KNOWN TO CANON. HOWEVER, ANY MATERIAL

CONTACTING THE EYE MAY BE IRRITATING. SKIN-LOW HAZARD FOR

RECOMMENDED HANDLING. INGESTION-NOT TYPI CAL ROUTE OF ENTRY DURING



ORDINARY USE.

Effects of Overexposure: TONER POWDER IS NOT ACCESSIBLE, UNLESS THE CARTRIDGE IS FORCED, OR BROKEN INTO.

Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid

First Aid:INHALATION: REMOVE FROM EXPOSURE. EYES-IN CASE OF EYE CONTACT, FLUSH EYE WITH PLENTY OF WATER. IF IRRITATION PERSISTS CONTACT A PHYSICIAN. SKIN: WASH WITH SOAP AND WATER.

Fire Fighting

Extinguishing Media: WATER, DRY CHEMICAL, CARBON DIOXIDE.

Fire Fighting Procedures: NONE.

Unusual Fire/Explosion Hazard:THIS MATERIAL, LIKE MOST ORGANIC MATERIAL IN POWDERED FORM, IS CAPABLE OF CREATING A DUST EXPLOSION.

Accidental Release

Spill Release Procedures: NO TONER SPILLAGE OCCURS IN NORMAL OPERATION OR HANDLING. IF IT SHOULD OCCUR, AVOID INHALATION. SWEEP MATERIAL ONTO PAPER AND PLACE IN A FIBER CARTON.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions: KEEP OUT OF REACH OF CHILDREN. KEEP FROM CONTACT WITH OXIDIZING MATERIALS.

Other Precautions: NONE

Exposure Controls

Respiratory Protection: NONE SPECIFIED BY MANUFACTURER. Ventilation: GOOD GENERAL VENTILATION SHOULD BE SUFFICIENT.

Protective Gloves: NONE REQUIRED. Eye Protection: NONE REQUIRED. Other Protective Equipment: NONE.

Work Hygienic Practices: WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health

PROPER SHIPPING NAME: MAGNETIZED MATERIAL. HAZARD CLASS: 9.

Chemical Properties

HCC:M1

Melt/Freeze Pt:M.P/F.P Text:100C-150C

Vapor Pres: NEGLIGIBLE Spec Gravity: 1.4-1.6

Evaporation Rate & Reference: NEGLIGIBLE

Solubility in Water: NEGLIGIBLE

Appearance and Odor: BLACK FINE POWDER, SLIGHT PLASTIC ODOR.

Percent Volatiles by Volume: NEGL.

Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS.

Stability Condition to Avoid: NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products: AS WITH ANY OTHER ORGANIC MATERIAL, COMBUSTION WILL PRODUCE CARBON DIOXIDE AND PROBABLY CARBON MONOXIDE.

Disposal

Waste Disposal Methods: NO SPECIAL DISPOSAL TECHNIQUES REQUIRED. ENSURE COMPLIANCE WITH FEDERAL, STATE AND OR LOCAL REGULATIONS. CARTRIDGE MAY BE CONSIDERED PLASTIC WASTE. THIS CARTRIDGE IS COMPOSED OF PLASTIC AND METAL.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and





assume responsibility for the suitability of this information to their particular situation.