

## **1750 EXT LATEX-HIGH GLOSS W/P**

### **MSDS Number**

BSDHG

### **National Stock Number**

8010-00N044504

### **Product Name**

1750 EXT LATEX-HIGH GLOSS W/P

### **Manufacturer**

DYCO PAINTS

### **Product Identification**

Product ID:1750 EXT LATEX-HIGH GLOSS W/P

MSDS Date:04/01/1993

FSC:8010

NIIN:00N044504

MSDS Number: BSDHG

### **Responsible Party**

DYCO PAINTS

3850 ULMERTON RD

CLEARWATER , FL 64620

US

Emergency Phone: 813-461-7358

Info Phone: 813-536-6560

Cage: DYCPA

### **Contractor**

DYCO PAINTS

CLEARWATER, FL 64620

US

813-536-6560

Cage: DYCPA

### **Ingredients**

2 @ 68F

CAS: 8032-32-4

RTECS: OI6180000

Fraction By Weight:

OSHA PELN/K

ACGIH TLV: N/K

ETHANOL, 2-(2-METHOXYETHOXY)-; (GLYCOL BUTYL ETHER)

CAS: 111-77-3

RTECS: KL6125000

Fraction By Weight:

OSHA PEL200 PPM (MFR)

ACGIH TLV: 5 PPM, S (MFR)

570 @ 68F

CAS: 7664-41-7

RTECS: BO0875000

Fraction By Weight:

OSHA PEL35 PPM STEL

ACGIH TLV: 25 PPM; 35 STEL

EPA Report Quantity: 100 LBS

DOT Report Quantity: 100 LBS

0.5

CAS: 110-80-5

RTECS: KK8050000

Fraction By Weight:

OSHA PEL200 PPM, S

ACGIH TLV: 5 PPM, S

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

0.1 @ 68F

CAS: 57-55-6

RTECS: TY2000000

Fraction By Weight:

OSHA PELN/K

ACGIH TLV: N/K

0.1 @ 68F

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight:

OSHA PEL50 PPM, C

ACGIH TLV: 50 PPM, C

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

5.1 @ 68F

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight:

OSHA PEL100 PPM; 150 STEL

ACGIH TLV: 100 PPM; 150 STEL

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

## Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE/CHRONIC: NO ADVERSE EFFECTS FROM AVAILABLE INFORMATION. INHAL:HIGH CONCENTRATIONS OF VAPOR OR SPRAY MIST IN CONFINED AREAS MAY EXCLUDE OXYGEN FROM THE ATMOSPHERE & CAUSE SIGNS OF ASPHIXIA. EYE C ONTACT:MAY CAUSE IRRITATION, REDNESS & CONJUNCTIVITIS. SKIN:MAY CAUSE IRRITATION. PROLONGED CONTACT (EFTS OF OVEREXP)  
Explanation of Carcinogenicity:NOT RELEVANT.  
Effects of Overexposure:HLTH HAZ:IN THE WET STATE MAY CAUSE WATER ABSORPTION INTO THE SKIN. INGEST:MAY CAUSE NAUSEA IN SOME PERSONS.  
Medical Cond Aggravated by Exposure:NO EVIDENCE OF ADVERSE EFFECTS FROM AVAILABLE INFORMATION.

## First Aid

First Aid:EYES:FLUSH W/LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINS. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. SKIN:WASH W/SOAP & WATER. REMOVE SOILED CLOTHES & LAUNDER BEFORE REUSE. INGEST:GIVE TWO GLASSES OF WATER. INDUCE VOMITING IMMEDIATELY BY STICKING FINGER DOWN THROAT. CALL MD. INHAL:REMOVE TO FRESH AIR. SUPPORT BREATHING (GIVE OXYGEN/ARTIFICIAL RESPIRATION). CALL MD .

## Fire Fighting

Flash Point Method:TCC  
Flash Point:81.0F,27.2C  
Lower Limits:1%  
Upper Limits:25%  
Extinguishing Media:FOR RESIDUAL SOLIDS, USE WATER SPRAY, CARBON DIOXIDE, DRY CHEMICAL OR ALL PURPOSE-TYPE FOAMS.  
Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT .  
Unusual Fire/Explosion Hazard:THE LATEX WILL NOT BURN UNTIL WATER HAS EVAPORATED.

## Accidental Release

Spill Release Procedures:MAJOR SPILLS:WALK AREAS & FLOORS WILL BE SLIPPERY; TAKE PRECAUTIONS. COLLECT MATERIAL W/ABSORBANT SUCH AS SAND AND DRY FOR PROPER DISPOSAL. MINOR SPILLS:ABSORB W/RAGS OR OTHER ABSORBANT. CLEAN UP W/WA TER.  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

## Handling

Handling and Storage Precautions:AVOID BREATHING VAPORS. KEEP CONTAINER CLOSED. USE WITH ADEQUATE VENTILATION.  
Other Precautions:KEEP OUT OF REACH OF CHILDREN.

## Exposure Controls

Respiratory Protection:NONE REQUIRED. AN ORDINARY NIOSH/MSHA DUST (MIST) RESPIRATOR IS RECOMMENDED IF THE PRODUCT IS TO BE SPRAYED.  
Ventilation:GENERAL (MECHANICAL) ROOM VENTILATION IS EXPECTED TO BE SATISFACTORY.  
Protective Gloves:IMPERVIOUS GLOVES .  
Eye Protection:ANSI APPROVED SAFETY GLASSES .  
Other Protective Equipment:NONE REQUIRED.  
Work Hygienic Practices:WASH HANDS BEFORE EATING, SMOKING OR USING THE WASHROOM.  
Supplemental Safety and Health  
SOL IN H\*2O:DILUTES & THINS IN WATER IN ALL PROPORTIONS.

## Chemical Properties

HCC:F4  
Boiling Pt:B.P. Text:>83F,>28C

Vapor Pres:SEE INGRED  
Vapor Density:HVR/AIR  
Spec Gravity:1.2 (H\*2O=1)  
Evaporation Rate & Reference:SLOWER THAN ETHER  
Solubility in Water:SUPP DATA  
Appearance and Odor:LIQUID W/SLIGHT ODOR.

## Stability

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING COMPOUNDS & LIQUID BLEACH WITH LIQUID PRODUCT.  
Stability Condition to Avoid:NONE.  
Hazardous Decomposition Products:CHLORINE GAS IS FORMED WHEN BLEACH IS  
MIXED W/PRODUCT. PRODUCTS OF COMBUSTION ARE CARBON MONOXIDE &  
CARBON DIOXIDE.

## Disposal

Waste Disposal Methods:LIQUID MATERIAL IS CONSIDERED A HAZARDOUS  
MATERIAL & MUST BE DISPOSED OF W/AN AUTHORIZED DISPOSAL COMPANY.  
DRY MATERIAL IS NOT CONSIDERED HAZARDOUS & MAY BE DISPOSED OF  
ACCORDING TO LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.