

DECRATRIM PEARL WHITE, 012-0216

MSDS Number

BSDJW

National Stock Number

8010-00N044927

Product Name

DECRATRIM PEARL WHITE, 012-0216

Manufacturer

DECRATREND PAINT CORP

Product Identification

Product ID:DECRATRIM PEARL WHITE, 012-0216

MSDS Date:04/29/1987

FSC:8010

NIIN:00N044927

MSDS Number: BSDJW

Responsible Party

DECRATREND PAINT CORP

251 MASON WAY

CITY OF INDUSTRY , CA 91746

US

Emergency Phone: 818-333-4592

Info Phone: 818-333-4592

Cage: 42590

Contractor

DECRATREND PAINT CORP

CITY OF INDUSTRY, CA 91746

US

818-333-4592

Cage: 42590

Ingredients

SOLVENT NAPHTHA PETROLEUM MEDIUM ALIPHATIC; (ALIPHATIC

CAS: 64742-88-7

Fraction By Weight: 30%

OSHA PELN/K

ACGIH TLV: N/K

NEPHELINE SYENITE

Fraction By Weight: 10%

OSHA PELN/K

ACGIH TLV: N/K

2.98 LB/GL (357 G/L)

RTECS: 9999999VO

OSHA PELN/K

ACGIH TLV: N/K

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: EYES: CAN CAUSE SEV IRRIT, RED, TEAR, BLURRED VISION. SKIN: CAN CAUSE MOD IRRIT, DEFAT, & DERM.

INHAL: CAN CAUSE NASAL & RESP IRRIT. ASPIR INTO LUNGS CAN CAUSE CHEM PNEUM WHICH CAN BE FATAL. CH RONIC:PRLNGD/RPTD EXPOS ABOVE TLV MAY RESULT IN PERM BRAIN & NERV SYS DAM. CHRONIC OVEREXP TO TIO*2 (EFTS OF OVEREXP)

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:HLTH HAZ: DUST MAY CAUSE SLIGHT LUNG FIBROSIS.

INHAL: EXCESS INHAL OF VAPS CAN CAUSE NASAL & RESP IRRIT, WEAK, DIZZ, FATG, NAUS, HDCH & POSS UNCON & EVEN ASPHY. SKIN: PRLNGD/RPTD CONT CAN CAUSE MOD IR RIT, DEFAT, DERM. EYE: CAN CAUSE SEV IRRIT, RED, TEAR & BLURRED VISION. SKIN ABSORP: ORG SOLV ARE EASILY (SUPP DATA)

Medical Cond Aggravated by Exposure:NONE KNOWN.

First Aid

First Aid:EYES: FLUSH IMMED W/LG AMTS OF WATER FOR @ LST 15 MIN. TAKE TO A PHYS FOR MED TRTMT. SKIN: WASH AFFECTED AREAS W/SOAP & WATER. REMOVE CONTAMD CLTHG. CONSULT A PHYS IF IRRIT PERSISTS. INHAL: REMOVE TO FRESH AIR. RESTORE BRTHG. TREAT SYMPTOMATICALLY. CONSULT A PHYS. INGEST: DRINK 1-2 GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMIT. CONSULT A PHYS/POIS CTL CTR IMMED. TREAT SYMPTOMATICALLY.

Fire Fighting

Flash Point Method:TCC

Flash Point:109F,43C

Lower Limits:1%

Upper Limits:6%

Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL.

Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT . DURING EMER CNDTNS OVEREXP TO DECOMP PROD MAY CAUSE IMMED/DELAYED HLTH HAZS.

Unusual Fire/Explosion Hazard:VAPS ARE HVR/AIR & MAY TRAVEL ALONG GROUND & BE IGNITED BY HEAT, OPEN FLAME/OTHER IGNIT SOURCES. KEEP CONTRS TIGHTLY CLSD. ISOLATE FROM HEAT, SPARKS,(SUPP DATA)

Accidental Release

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. DIKE, CONTAIN, OR ABSORB WITH INERT MATERIALS (SAND, VERMICULITE, ETC). TRANSFER TO CONTAINERS FOR RECOVERY OR DISPOSAL. PREVENT RUNOFF INTO SEWERS, STREAMS, OR OTHER B ODIES OF WATER.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:DO NOT STORE OR USE NEAR SOURCES OF HIGH TEMPERATURES, NEAR FIRE/OPEN FLAME, OR OTHER IGNITION SOURCES. Other Precautions:DO NOT TAKE INTERNALLY. AVOID PROLONGED OR REPEATED EXPOSURE TO LEVELS ABOVE TLV.

Exposure Controls

Respiratory Protection:IF TLV IS EXCEEDED USE NIOSH/MSHA APROVED ORGANIC VAPOR AND MIST, SUPPLIED AIR/SCBA.

Ventilation:USE ADEQUATE MECHANICAL (GENERAL &/OR LOCAL) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV.

Protective Gloves:RESISTANT GLOVES SUCH A NITRILE RUBBER.

Eye Protection:CHEM SPLASH GOGG/OTHER OSHA (SUPP DATA)

Other Protective Equipment:WEAR IMPERVIOUS CLOTHING. EYEWASH STATIONS.

Work Hygienic Practices:WASH HANDS BEFORE EATING OR USING RESTROOM. REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

EXPLO HAZ: ELEC EQUIP, & OPEN FLAMES. CLSD CONTRS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. EFTS OF OVEREXP: ABSORBED, DRYING OF SKIN, RED/DERM ARE SIGNS OF RPTD/OVEREXP TO THEIR DEFAT ACTION. INGEST: CAN CAUSE GI IRRIT, NAUS, VOMIT & DIARR. EYE PROT: PERMITTED SAFETY GLASSES.

Chemical Properties

HCC:F4

Boiling Pt:B.P. Text:310F,154C

Vapor Pres:SEE INGRED

Vapor Density:HVR/AIR

Spec Gravity:1.2(H*20=1)

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:NONE

Appearance and Odor:TYPICAL FOR SOLVENT BASED COATING.

Stability

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:DO NOT EXPOSE TO HIGH TEMPERATURES OR OPEN IGNITION SOURCES.

Hazardous Decomposition Products:MAY FORM TOXIC MATERIALS, CARBON DIOXIDE, CARBON MONOXIDE, VARIOUS HYDROCARBONS, ETC ON THERMAL DECOMPOSITION.

Disposal

Waste Disposal Methods:DISPOSE OF I/A/W LOCAL, STATE, OR FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.