

# **TOLUENE (TOLUOL), 153-7851**

# **MSDS Number**

**BSDMF** 

# **National Stock Number**

6810-00N045063

# **Product Name**

TOLUENE (TOLUOL), 153-7851

#### Manufacturer

SHERWIN WILLIAMS

# **Product Identification**

Product ID:TOLUENE (TOLUOL), 153-7851 MSDS Date:01/01/1991 FSC:6810 NIIN:00N045063 MSDS Number: BSDMF

# **Responsible Party**

SHERWIN WILLIAMS

101 PROSPECT AVE NW

CLEVELAND, OH 44115

US

Emergency Phone: 216-566-2917

Info Phone: 216-566-2902

Cage: 54626

# **Contractor** SHERWIN-WILLIAMS CO THE

CLEVELAND, OH 44115-1042

US

800-251-2486/216-566-2242

Cage: 54636

# **Ingredients**

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 100% OSHA PEL100 PPM; 150 STEL

ACGIH TLV: 50 PPM

EPA Report Quantity: 1000 LBS DOT Report Quantity: 1000 LBS

VOLATILE ORGANIC COMPOUNDS 7.18 LB, 860 GM

RTECS: 9999999VO OSHA PELN/K

ACGIH TLV: N/K



NO

RTECS: 9999999ZZ

PRLNGD OVEREXPOS TO SOLV INGREDS IN ING SECTION MAY

RTECS: 9999999ZZ

CARDIO-VASCULAR SYS. RPTS HAVE ASSOC RPTD & PRLNGD

RTECS: 9999999ZZ

FLAMES, PILOT LIGHTS, & HEATERS-TURN OFF

RTECS: 9999999ZZ

OF IGNIT. CONSULT NFPA CODE. USE APPRVD BONDING &

RTECS: 9999999ZZ

ONLY TO APPRVD CNTNRS W/COMPLETE AND APPROP LABELING.

RTECS: 9999999ZZ

LIMITS. REFER TO OSHA STANDARDS 1910.94, 1910.107,

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation: YES Skin: YES Ingestion: NO

RTECS: 9999999ZZ

#### **Hazards**

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:TOLUENE APPEARS ON NAVY LISTING OF
OCCUPATIONAL CHEM REPRODUCTIVE HAZ. SEEK CONSULTATION FROM APPROP
HLTH PROFESSIONALS CONCERNING LATEST HAZ LIST INFO & SAFE HNDLG &
EXPOS INFO . EXPOS MAY BE B Y INHAL &/OR SKIN OR EYE CNTCT,
DEPENDING ON CNDTNS OF USE TO MINIMIZE EXPOS, FOLLOW
RECOMMENDATIONS (EFTS OF OVEREXP)
Explanation of Carcinogenicity:NOT RELEVANT
Effects of Overexposure:HLTH HAZ:FOR PROPER USE, VENT, & PERS PROT
EQUIP. ACUTE:IRRIT OF EYES, SKIN & RESP SYS. MAY CAUSE NERVOUS SYS
DEPRESS. EXTREME OVEREXP MAY RESULT IN UNCONSCIOUSNESS, & POSS
DEATH. HDCH, DIZZ, NAUS, & LOSS OF COORD ARE INDICATIONS OF
EXCESSEXPOS TO VAPS/SPRAY MISTS. REDNESS & ITCHING/BURNING
SENSATION MAY (ING 3)
Medical Cond Aggravated by Exposure:NONE GENERALLY RECOGNIZED.

# First Aid

First Aid:INHAL:REMOVE FROM EXPOS. RESTORE BRTHG. KEEP WARM & QUIET. SKIN:WASH AFFECTED AREA THORO W/SOAP & WATER. REMOVE CONTAM CLTHG & LAUNDER BEFORE RE-USE. EYES:FLUSH EYES W/LG AMTS OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION. INGEST:NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. DO NOT INDUCE VOMITING. GIVE SEVERAL GLASSES OF WATER. SEEK MEDICAL ATTENTION.

# **Fire Fighting**

Flash Point Method:TCC Flash Point:40.0F,4.4C Lower Limits:1.0



Upper Limits: 7.0

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM Fire Fighting Procedures: FULL PROT EQUIP INCL SCBA SHOULD BE USED. WATER SPRAY MAY BE INEFFECTIVE. IF WATER IS USED, FOG NOZZ ARE PREF. WATER MAY BE USED TO COOL CLSD CNTNRS (SUPP DATA) Unusual Fire/Explosion Hazard: KEEP CNTNRS TIGHTLY CLSD. ISOLATE FROM HEAT, ELEC EQUIP, SPARKS, & OPEN FLAME. CLSD CNTNRS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT, APPLIC TO HOT (SUPP DATA)

### **Accidental Release**

Spill Release Procedures: REMOVE OF SOURCES OF IGNITION. VENTILATE AND REMOVE WITH INERT ABSORBENT.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

# Handling

Handling and Storage Precautions: CONTENTS ARE FLAMM. KEEP AWAY FROM HEAT, SPARKS, & OPEN FLAME. DURING USE & UNTIL ALL VAPS ARE GONE: KEEP AREA VENT-DO NOT SMOKE-EXTING ALL (ING 6) Other Precautions: INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS CAN BE HARMFUL OR FATAL. USE ONLY WITH ADEQUATE VENT. AVOID BREATHING VAPOR AND SPRAY MIST. AVOID CONTACT WITH SKIN AND EYES.

### **Exposure Controls**

Respiratory Protection: NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN .

Ventilation:LOCAL EXHAUST PREF. GEN EXHAUST ACCEPTABLE IF EXPOS TO MATLS IN ING SECTION IS MAINTAINED BELOW APPLIC EXPOS (ING 9) Protective Gloves:IMPERVIOUS GLOVES .

Eye Protection: ANSI APPROVED CHEMICAL WORKERS GOGGLES. Other Protective Equipment: NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices: WASH HANDS AFTER USING.

Supplemental Safety and Health

FIRE FIGHT PROC:TO PRVNT PRESS BUILD-UP & POSS AUTOIGNIT/EXPLO WHEN EXPOSED TO EXTREME HEAT. EXPLO HAZ:SURF REQ SPECIAL PREC. DURING EMERGENCY CNDTNS OVEREXPOS TO DECOMP PRODS MAY CAUSE HLTH HAZ. SYMP S MAY NOT BE IMMED APPARENT. OBTAIN MEDATTN.

# **Chemical Properties**

HCC:F3

Boiling Pt:B.P. Text:222F,106C Vapor Density:HVR/AIR Spec Gravity:0.86

Evaporation Rate & Reference:SLOWER THAN ETHER Appearance and Odor:NONE SPECIFIED BY MANUFACTURER.

Percent Volatiles by Volume:100%

# **Stability**

Stability Indicator/Materials to Avoid:YES NONE KNOWN Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products:BY FIRE:CARBON DIOXIDE, CARBON MONOXIDE.

# **Disposal**

Waste Disposal Methods: WASTE FROM THIS PROD MAY BE HAZ AS DEFINED UNDER RESOURCE CONSERVATION & APPLIC EPA HAZ WASTE NUMBERS. INCIN IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINER. DISPOSE OF IN ACCORDANCE WITH FED ERAL, STATE, AND LOCAL REGS REGARDING POLLUTION.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and





assume responsibility for the suitability of this information to their particular situation.