

B-FLEX EPOXY NON-SAGGING PART B

MSDS Number

BSDNF

National Stock Number

8010-00N045186

Product Name

B-FLEX EPOXY NON-SAGGING PART B

Manufacturer

SOUNDCOAT CO INC

Product Identification

Product ID:B-FLEX EPOXY NON-SAGGING PART B MSDS Date: 04/21/1990 FSC:8010 NIIN:00N045186

MSDS Number: BSDNF

Responsible Party

SOUNDCOAT CO INC

1 BURT DR

DEER PARK, NY 11729

US

Emergency Phone: 516-242-2200

Info Phone: 516-242-2200

Preparer: D. RAO Cage: 28818

Contractor

SOUNDCOAT CO INC DEER PARK, NY 11729

US

516-242-2200

Cage: 28818

Ingredients

POLYAMIDE RESIN

Fraction By Weight: 95%

OSHA PELN/K ACGIH TLV: N/K

SILICA (NON-DUSTING FORM)

Fraction By Weight: 5%

OSHA PELN/K

ACGIH TLV: N/K

Hazards

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO



Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: ACUTE: VAPOR IRRITATING TO EYES, NOSE

AND THROAT. CHRONIC: NOT KNOWN.

Explanation of Carcinogenicity: NOT RELEVANT

Effects of Overexposure: EYE IRRITATION, EXCESS EXPOSURE MAY CAUSE

DERMATITIS, HEADACHE, DIZZINESS, ETC.

Medical Cond Aggravated by Exposure: NOT KNOWN.

First Aid

First Aid:SEEK MEDICAL ASSISTANCE FOR FURTHER TREATMENT, OBSERVATION AND SUPPORT IF NECESSARY. EYE: IMMED FLUSH WITH WATER FOR AT LEAST 15 MINUTES, GET MEDICAL ASSISTANCE. SKIN: PROMPTLY WASH THOROUGHLY WITH SO AP AND WATER. INHAL: REMOVE TO FRESH AIR. GIVE OXYGEN IF BREATHING IS DIFFICULT. INGEST: DO NOT INDUCE VOMITING. DRINK 1-2 GLASSES OF TO DILUTE. SEE A PHYSICIAN.

Fire Fighting

Flash Point Method:CC Flash Point:340F,171C

Extinguishing Media: CARBON DIOXIDE, FOAM, WATER.

Fire Fighting Procedures: WEAR NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT . CONTAINERS EXPOSED TO FIRE SHOULD BE KEPT

COOL W/WATER SPRAY.

Unusual Fire/Explosion Hazard: NONE.

Accidental Release

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. ABSORB ON COMBUSTIBLE MATERIAL FOR PROPER DISPOSAL. AVOID DIRECT CONTACT. FLUSH CONTAMINTED AREAS WITH WATER.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions: STORE IN COOL PLACE AWAY FROM SPARKS AND OPEN FLAME.

Other Precautions: AVOID CONTACT WITH EYES, SKIN AND CLOTHING. HARMFUL IF INHALED. USE W/ADEQUATE VENTILATION.

Exposure Controls

Respiratory Protection: NIOSH/MSHA APPROVED ORGANIC VAPOR RESPIRATOR.

Ventilation:LOCAL EXHAUST/MECHANICAL(GENERAL): RECOMMENDED.

Protective Gloves: NEOPRENE RUBBER.

Eye Protection: CHEMICAL GOGGLES.

Other Protective Equipment: AS REQUIRED TO PREVENT SKIN CONTACT.

Work Hygienic Practices: NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

Chemical Properties

HCC:N1

Spec Gravity: 0.99(H*20=1)

Evaporation Rate & Reference: VERY LOW

Solubility in Water:SLIGHT

Appearance and Odor: NONE SPECIFIED BY MANUFACTURER.

Stability

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS, NATURAL RUBBER. Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products:CARBON MONOXIDE, NITROGEN OXIDES, CARBON DIOXIDE.

Disposal

Waste Disposal Methods: INCINERATION I/A/W LOCAL POLLUTION REGULATION AND ORDINANCE. DISPOSE OF I/A/W FEDERAL, STATE AND LOCAL REGULATIONS .

Disclaimer (provided with this information by the compiling agencies):



https://msdsreport.com/msds/BSDNF

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.