

## **TT-P-1952B WHITE, P/C 184602**

### **MSDS Number**

BSGGC

### **National Stock Number**

8010-01-017-1512

### **Product Name**

TT-P-1952B WHITE, P/C 184602

### **Manufacturer**

WELLBORN PAINT MFG CO

### **Product Identification**

Product ID:TT-P-1952B WHITE, P/C 184602

MSDS Date:12/11/1985

FSC:8010

NIIN:01-017-1512

MSDS Number: BSGGC

### **Responsible Party**

WELLBORN PAINT MFG CO

215 ROSSMOOR RD

ALBUQUERQUE , NM 87012

US

Emergency Phone: 505-877-5050/505-843-2551

Info Phone: 505-877-5050

Cage: WELLB

### **Contractor**

WELLBORN PAINT MFG CO

ALBUQUERQUE, NM 87012

US

505-877-5050

Cage: WELLB

### **Ingredients**

TEXANOL (VAPOR PRESSURE 1.00 MM HG @ 68F) (LEL 0.6)

CAS: 25265-77-4

RTECS: UF6000000

Fraction By Weight: 1.4%

ETHYLENE GLYCOL (SARA III) (VAPOR PRESSURE 0.10 MM HG @

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight: 2.4%

ACGIH TLV: 100 PPM

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

TITANIUM DIOXIDE (NUISANCE DUST)

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: 16.9%

ACGIH TLV: 10 MG/M3

ALUMINUM OXIDE (SARA III) (NUISANCE DUST)

CAS: 1344-28-1

RTECS: BD1200000

Fraction By Weight: 1.8%

ACGIH TLV: 10 MG/M3

SILICA AMORPHOUS

CAS: 112945-52-5

RTECS: VV7310000

Fraction By Weight: 2.4%

ACGIH TLV: 6 MG/M3

CALCIUM CARBONATE (NUISANCE DUST)

CAS: 1317-65-3

RTECS: EV9580000

Fraction By Weight: 13.2%

ACGIH TLV: 10 MG/M3

AMMONIA

CAS: 1336-21-6

RTECS: BQ9625000

Fraction By Weight: TRACE

ACGIH TLV: 25 PPM

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

## Hazards

Health Hazards Acute and Chronic: INHALATION: VAPOR OR MIST MAY IRRITATE EYES, NOSE, THROAT & MUCOUS MEMBRANES PRODUCING DIZZINESS, HEADACHES, NAUSEA IN POORLY VENTILATED AREAS. SKIN: PROLONGED/REPEATED CONTACT WITH LATEX PAINT MAY CAUSE SKIN IRRITATION. EYE: DIRECT CONTACT WITH LATEX PAINT MAY RESULT IN EYE IRRITATION.

Effects of Overexposure: CHRONIC: INHALATION MAY HAVE AN EFFECT ON CENTRAL NERVOUS SYSTEM. MAY CAUSE DIZZINESS OR NARCOSIS.

## First Aid

First Aid: INHALATION: REMOVE TO FRESH AIR. CONSULT PHYSICIAN. SPLASH (EYES): FLUSH WITH WATER FOR 15 MIN. SPLASH (SKIN): WASH WITH SOAP AND WATER. REMOVE & WASH CLOTHING. INGESTION: IF VICTIM IS CONSCIOUS, GIVE TWO GLASSES OF WATER TO DRINK. DO NOT INDUCE VOMITING. CALL A PHYSICIAN.

---

## Fire Fighting

Extinguishing Media:NON COMBUSTIBLE

Fire Fighting Procedures:LATEX COATINGS WILL NOT BURN. THEY MAY SPATTER IF TEMP EXCEEDS BOILING POINT. DRY FILMS ARE CAPABLE OF BURNING.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY RUPTURE WHEN EXPOSED TO EXTREME HEAT. KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT AND OPEN FLAME.

## Accidental Release

Spill Release Procedures:DIKE AND CONTAIN SPILL WITH INERT MATERIAL & TRANSFER THE LIQUID TO CONTAINERS FOR RECOVERY AND DISPOSAL. KEEP SPILL OUT OF SEWERS AND OPEN BODIES OF WATER.

## Handling

Handling and Storage Precautions:KEEP FROM FREEZING. DO NOT TAKE INTERNALLY. AVOID PROLONGED CONTACT OR INHALATION.

Other Precautions:WHEN TINTED, THIS BASE MAY CONSIST OF UP TO 2 FL OZ OF UNIVERSAL MACHINE COLORANTS WHICH CONTAIN ETHYLENE GLYCOL. ON AVERAGE THIS TINTED BASE WOULD CONTAIN AN ADDITIONAL AMOUNT OF 0.6% BY WEIGHT OF EH TYLENE GLYCOL (TLV/TWA = 100 PPM).

## Exposure Controls

Respiratory Protection:WEAR APPROVED ORGANIC VAPOR RESPIRATOR UNLESS VENTILATION EQUIPMENT IS ADEQUATE TO KEEP AIRBORNE CONCENTRATIONS BELOW THE EXPOSURE STANDARDS.

Ventilation:GENERAL MECHANICAL VENT MAY BE SUFFICIENT TO KEEP PRODUCT VAPOR CONCENTRATIONS BELOW TLV RANGES, USE LOCAL EXHAUST.

Protective Gloves:IMPERMEABLE SOLVENT RESISTANT GLOVES

Eye Protection:SFTY GOGGLES,CHEM SFTY GLASSES,FACE SHLD

Other Protective Equipment:IMPEREABLE APRONS & PROTECTIVE CLOTHING ARE ADVISED WHEN WORKING WITH THIS PRODUCT. USE HEAD CAPS WHENEVER POSSIBLE.

Work Hygienic Practices:EYE WASHES AND SAFETY SHOWERS IN THE WORKPLACE ARE RECOMMENDED.

Supplemental Safety and Health

## Chemical Properties

Boiling Pt:B.P. Text:212F,100C

Vapor Density:> AIR

Evaporation Rate & Reference:SLOWER TAN N-BU/AC

Percent Volatiles by Volume:63.0

## Stability

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:HIGH TEMPERATURES OR HIGH HUMIDITIES

Conditions to Avoid Polymerization:HIGH TEMPERATURES OR HIGH HUMIDITIES

## Disposal

Waste Disposal Methods:INCINERATE OR LANDFILL LIQUID AND CONTAMINATED DIKING MATERIAL, ACCORDING TO LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.