

## **TT-P-1952B YELLOW P/C 184601**

### **MSDS Number**

BSGGF

### **National Stock Number**

8010-01-019-1776

### **Product Name**

TT-P-1952B YELLOW P/C 184601

### **Manufacturer**

WELLBORN PAINT MFG CO

### **Product Identification**

Product ID:TT-P-1952B YELLOW P/C 184601

MSDS Date:04/28/1988

FSC:8010

NIIN:01-019-1776

MSDS Number: BSGGF

### **Responsible Party**

WELLBORN PAINT MFG CO

215 ROSSMOOR RD

ALBUQUERQUE , NM 87012

US

Emergency Phone: 505-877-5050/505-843-2551

Info Phone: 505-877-5050

Cage: WELLB

### **Contractor**

WELLBORN PAINT MFG CO

ALBUQUERQUE, NM 87012

US

505-877-5050

Cage: WELLB

### **Ingredients**

FORMALDEHYDE (SARA III) (VAPOR PRESSURE 17.00 MM HG @ 68F)

CAS: 50-00-0

RTECS: LP8925000

Fraction By Weight: TRACE

ACGIH TLV: 2 PPM

EPA Report Quantity: 100 LBS

DOT Report Quantity: 100 LBS

LEAD (AS PB) (SARA III)

CAS: 7439-92-1

RTECS: OF7525000

Fraction By Weight: 10.3%

ACGIH TLV: 0.15 MG/M3

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

CHROMIUM (AS CR) (SARA III)

CAS: 7440-47-3

RTECS: GB4200000

Fraction By Weight: 2.4%

ACGIH TLV: 0.05 MG/M3

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

SILICA-CRYSTALLINE

CAS: 112945-52-5

RTECS: VV7310000

Fraction By Weight: 8.6%

ACGIH TLV: 0.1 MG/M3

CALCIUM CARBONATE (NUISANCE DUST)

CAS: 1317-65-3

RTECS: EV9580000

Fraction By Weight: 34.5%

ACGIH TLV: 10 MG/M3

AMMONIUM

CAS: 1336-21-6

RTECS: BQ9625000

Fraction By Weight: TRACE

ACGIH TLV: 25 PPM

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

ETHYLENE GLYCOL (SARA III) (VAPOR PRESSURE .10 MM HG @

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight: 2.2%

ACGIH TLV: 100 PPM

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

TEXANOL (VAPOR PRESSURE 1.00 MM HG @ 68F) (LEL 0.6)

CAS: 25265-77-4

RTECS: UF6000000

Fraction By Weight: 0.7%

## Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Health Hazards Acute and Chronic:INHALATION: VAPOR OR MIST MAY IRRITATE EYES, NOSE, THROAT, MUCOUS MEMBRANES PRODUCING DIZZINESS, HEADACHES, NAUSEA IN POORLY VENTILATED AREAS. SKIN: PROLONGED/REPEATED: SKIN IRRITATION. EYE: IRRITATIO N.  
Explanation of Carcinogenicity:FORMALDEHYDE AND CHROMIUM ARE SUSPECTED CARCINOGENS.  
Effects of Overexposure:CHRONIC: INHALATION MAY HAVE AN EFFECT ON CENTRAL NERVOUS SYSTEM. MAY CAUSE DIZZINESS OR NARCOSIS. EXCESSIVE CHRONIC, LONG TERM EXPOSURE TO LEAD MAY CAUSE METALLIC TASTE IN MOUTH, LOSS OF APPETITE, IN DIGESTION, NAUSEA, SLEEPLESSNESS, WEAKNESS, STUPOR, COMA, ENCEPHALOPATHY.

## First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. CONSULT PHYSICIAN. SPLASH (EYES): FLUSH WITH WATER FOR 15 MIN. SPLASH (SKIN): WASH WITH SOAP AND WATER. REMOVE & WASH CLOTHING. INGESTION: IF VICTIM IS CONSCIOUS, GIVE 529 GLASSES OF WATER TO DRINK. DO NOT INDUCE VOMITING. CALL A PHYSICIAN.

## Fire Fighting

Flash Point:NOT REGULATED  
Extinguishing Media:NON COMBUSTIBLE  
Fire Fighting Procedures:LATEX COATINGS WILL NOT BURN. THEY MAY SPATTER IF TEMP EXCEEDS BOILING POINT. DRY FILMS ARE CAPABLE OF BURNING.  
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY RUPTURE WHEN EXPOSED TO EXTREME HEAT. KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT AND OPEN FLAME.

## Accidental Release

Spill Release Procedures:DIKE AND CONTAIN SPILL WITH INERT MATERIAL & TRANSFER THE LIQUID TO CONTAINERS FOR RECOVERY AND DISPOSAL. KEEP SPILL OUT OF SEWERS AND OPEN BODIES OF WATER.

## Handling

Handling and Storage Precautions:KEEP FROM FREEZING. DO NOT TAKE INTERNALLY. AVOID PROLONGED CONTACT OR INHALATION.

## Exposure Controls

Respiratory Protection:WEAR APPROVED ORGANIC VAPOR RESPIRATOR UNLESS VENTILATION EQUIPMENT IS ADEQUATE TO KEEP AIRBORNE CONCENTRATIONS BELOW THE EXPOSURE STANDARDS.  
Ventilation:GENERAL MECHANICAL VENT MAY BE SUFFICIENT TO KEEP PRODUCE CONCENTRATIONS BELOW TLV, IF INADEQUATE USE LOCAL EXHAUST.  
Protective Gloves:USE IMPERMEABLE SOLVENT RESISTANT GLOVES  
Eye Protection:SFTY GOGGLES,CHEM SFTY GLASSES,FACESHLD  
Other Protective Equipment:IMPERMEABLE APRONS AND PROTECTIVE CLOTHING WHEN WORKING W/PRODUCT. USE OF HEADCAPS RECOMMENDED WHENEVER POSSIBLE.  
Work Hygienic Practices:EYE WASHING AND SAFETY SHOWERS IN WORKPLACE ARE RECOMMENDED.  
Supplemental Safety and Health

## Chemical Properties

HCC:T6  
Boiling Pt:B.P. Text:212F,100C  
Vapor Density:> AIR  
Evaporation Rate & Reference:SLOWER THAN N-BU/AC  
Percent Volatiles by Volume:65.5

## Stability

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:HIGH TEMPERATURES OR HIGH HUMIDITIES.  
Hazardous Decomposition Products:IF HEATED TO DECOMPOSITION, THIS  
PRODUCT WILL EMIT TOXIC FUMES OF LEAD  
Conditions to Avoid Polymerization:HIGH TEMPERATURES OR HIGH HUMIDITIES

## **Disposal**

Waste Disposal Methods:INCINERATE OR LANDFILL AND CONTAMINATED DIKING  
MATERIAL, ACORDING TO LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.