

OMEGALAQ TEMPERATURE RATING (SEE SUPP)

MSDS Number

BSMGV

National Stock Number

8010-00F030957

Product Name

OMEGALAQ TEMPERATURE RATING (SEE SUPP)

Manufacturer

OMEGA ENGINEERING INC

Product Identification

Product ID:OMEGALAQ TEMPERATURE RATING (SEE SUPP)

MSDS Date:07/20/1989

FSC:8010

NIIN:00F030957

MSDS Number: BSMGV

Responsible Party

OMEGA ENGINEERING INC

ONE OMEGA DRIVE

STAMFORD , CT 06907-0047

US

Emergency Phone: 203-359-1660

Info Phone: 203-359-1660

Cage: 29907

Contractor

OMEGA ENGINEERING INC.

4047

STAMFORD, CT 06907-0047

US

203-359-1660

Cage: 29907

Ingredients

ACRYLIC RESIN *93-3*

CAS: 29354-73-2

Fraction By Weight:

METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (CHLOROTHENE NU),

CAS: 71-55-6

RTECS: KJ2975000

Fraction By Weight: 62-69%

OSHA PEL350 PPM

ACGIH TLV: 1910 MG/CUM

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

TOLUENE

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight:

ACGIH TLV: 100 PPM

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

ADDITIVES

Fraction By Weight:

PIGMENT

Fraction By Weight: 0.1-0.6%

THICKENERS & INHIBITORS

Fraction By Weight:

GUANIDINE

CAS: 97-39-2

RTECS: MF1400000

Fraction By Weight:

Hazards

LD50 LC50 Mixture:ORAL LD50 (LAB ANIMAL): 0.1-0.5 G/KG SUP

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: SOLVENT VAPOR MAY CAUSE ANESTHESIA. COATING SOLIDS MAY EMIT FUMES OR VAPORS WHICH MAY BE HARMFUL. 1,3-DIOTOLYLGUANIDINE: NEUROLOGICAL DISTURBANCES.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:INGESTION: NAUSEA. 1,3-DIOTOLYLGUANIDINE: NAUSEA, DIARRHEA.

First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. INGESTION: DON'T INDUCE VOMITING. EYES: FLUSH W/PLENTY OF WATER. SKIN: WASH W/SOAP & WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point:NONE

Fire Fighting Procedures:USE SCBA OR AIR-SUPPLIED BREATHING APPARATUS FOR PROTECTION AGAINST POSSIBLE TOXIC COMBUSTION OR DECOMPOSITION PRODUCTS.

Accidental Release

Spill Release Procedures:ABSORB IN RAGS & DISCARD BY APPROVED PROCEDURES.

Handling

Handling and Storage Precautions:AVOID CONTACT W/EYES, SKIN, & CLOTHING. USE W/ADEQUATE VENTILATION. DON'T REPACKAGE INTO METAL CONTAINERS.

Exposure Controls

Ventilation:LOCAL EXHAUST

Protective Gloves:IMPERMEABLE

Eye Protection:SAFETY GLASSES

Work Hygienic Practices:OBSERVE GOOD HYGIENIC PRACTICES.
Supplemental Safety and Health
SUSPENSION OF FUSIBLE SOLIDS IN VOLATILE ORGANIC SOLVENTS. TEMP
RATINGS: 344F. LD50 INFORMATION IS FOR 1,3-DITOLYLGUANIDINE.

Chemical Properties

Boiling Pt:B.P. Text:160-190F
Vapor Pres:100
Vapor Density:4.6
Spec Gravity:1.3
Evaporation Rate & Reference:(ETHYL ETHER = 1): 0.4
Solubility in Water:MODERATE
Appearance and Odor:SOLVENT SUSPENSION, CHARACTERISTIC ODOR.
Percent Volatiles by Volume: 60

Stability

Stability Indicator/Materials to Avoid:YES
LIQUID OMEGALAQ: WATER, ALUMINUM MAY CAUSE SLOW DECOMPOSITION
Hazardous Decomposition Products:DRY COATING: CO2, CO. LIQUID OMEGALAQ:
SAME AS DRY COATING PLUS HYDROGEN CHLORIDE, PHOSGENE, CHLORINE

Disposal

Waste Disposal Methods:STANDARD, OBSERVING ALL FEDERAL, STATE, & LOCAL
REGULATIONS CONCERNING HEALTH & ENVIRONMENT. UN2831.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.