

## **CANON TONER FOR CLC 200/300 (YELLOW)**

### **MSDS Number**

BSRGD

### **National Stock Number**

6859-00D005339

### **Product Name**

CANON TONER FOR CLC 200/300 (YELLOW)

### **Manufacturer**

CANON U S A INC

### **Product Identification**

Product ID: CANON TONER FOR CLC 200/300 (YELLOW)

MSDS Date: 12/01/1991

FSC: 6859

NIIN: 00D005339

MSDS Number: BSRGD

### **Responsible Party**

CANON U.S.A., INC.

ONE CANON PLAZA

LAKE SUCCESS, NY 11042

US

Emergency Phone: 516-488-6700

Info Phone: 516-488-6700

Cage: 08YZ7

### **Contractor**

CANON USA INC

LAKE SUCCESS, NY 11042

US

516-328-5600

Cage: 1BA63

### **Ingredients**

SALICYLIC ACID CHELATE CHROMIUM (III)

CAS: 72869-85-3

Fraction By Weight: 1-5%

PIGMENT

Fraction By Weight: 3-10%

POLYESTER RESIN

Fraction By Weight: 85-95%

### **Hazards**

LD50 LC50 Mixture: LD50(ORAL,RAT)=GREATER THAN 5.0G.KG

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES

Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO

Health Hazards Acute and Chronic: EYE: IRRITANT. NO SPECIFIC HAZARD IS

KNOWN TO CANON. INHAL:TONER IS FINELY DIVIDED SOLID. DO NOT BREATHE DUST. SKIN:LOW HAZARD FOR INDUSTRIAL HANDLING. PER MFG'S MSDS NO DATA AVAILABLE FOR CHRONIC EFFECTS OF OVEREXPOSURE. Effects of Overexposure:EYE:REDNESS, TEARING, BLURRED VISION, DISCOMFORT. PER MFG'S MSDS NO DATA AVAILABLE FOR CHRONIC EFFECTS OF OVEREXPOSURE.

Medical Condition Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

## First Aid

First Aid:INHAL:REMOVE TO FRESH AIR. EYE:FLUSH WITH PLENTY OF WATER OPENING EYELIDS. IF IRRITATION PERSISTS GET MEDICAL ATTENTION. SKIN:WASH WITH SOAP & WATER. INGEST:DRINK SEVERAL GLASSES OF WATER. CALL A PHYSICIAN.

## Fire Fighting

Flash Point:NONE SPECIFIED .  
Autoignition Temp:Autoignition Temp Text:NONE .  
Lower Limits:NONE SPECIFIED.  
Upper Limits:NONE SPECIFIED.  
Extinguishing Media:CARBON DIOXIDE, WATER, DRY CHEMICALS.  
Fire Fighting Procedures:NONE.  
Unusual Fire/Explosion Hazard:THIS MATERIAL IS CAPABLE OF CREATING A DUST EXPLOSION.

## Accidental Release

Spill Release Procedures:SWEEP ONTO PAPER & PLACE IN FIBER CARTON.

## Handling

Handling and Storage Precautions:KEEP AWAY FROM CONTACT WITH OXIDIZING MATERIALS. STORE IN THE ROOM BELOW 40C.  
Other Precautions:NONE SPECIFIED BY MANUFACTURER.

## Exposure Controls

Respiratory Protection:NONE REQUIRED.  
Ventilation:GOOD GENERAL VENTILATION SHOULD BE SUFFICIENT.  
Protective Gloves:NONE NORMALLY REQUIRED.  
Eye Protection:NONE NORMALLY REQUIRED.  
Other Protective Equipment:NONE NORMALLY REQUIRED.  
Work Hygienic Practices:WASH HANDS THOROUGHLY AFTER USAGE AND BEFORE EATING/DRINKING/SMOKING.  
Supplemental Safety and Health  
CHROMIUM (II) AND COMPOUND(S): 4.0 WT%(MAX) (AS CHROMIUM METAL: 0.5 WT%(MAX). ALL COMPONENTS ARE REGISTERED IN ACCORDANCE WITH TSCA.

## Chemical Properties

HCC:N1  
Boiling Pt:B.P. Text:NONE SPECIFIED.  
Melt/Freeze Pt:M.P/F.P Text:212F,100C  
Vapor Pressure:NEGLIGIBLE  
Specific Gravity:1.0-1.2  
Evaporation Rate & Reference:NEGLIGIBLE  
Solubility in Water:NEGLIGIBLE  
Appearance and Odor:A FINE POWDER WITH SLIGHT ODOR.  
Percent Volatiles by Volume:NEGLIGIBLE

## Stability

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZERS.  
Stability Condition to Avoid:N/A.  
Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE.

## Disposal

Waste Disposal Methods:THE WASTE TONER COULD BE CONSIDERED AS PLASTIC WASTE. FOR INCINERATION, PACKAGE IT ADEQUATELY. DO NOT DISPERSE THE TONER INTO FIRE. DISPOSE IN ACCORDANCE WITH FEDERAL/STATE/LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.