

GW-2 TILE ADHESIVE, 467

MSDS Number

BSTQV

National Stock Number

8040-00N047945

Product Name

GW-2 TILE ADHESIVE, 467

Manufacturer

CHEMSECO

Product Identification

Product ID:GW-2 TILE ADHESIVE, 467

MSDS Date:04/10/1989

FSC:8040

NIIN:00N047945

MSDS Number: BSTQV

Responsible Party

CHEMSECO

4800 BLUE PARKWAY

KANSAS CITY , MO 64130

US

Emergency Phone: 816-923-2000

Info Phone: 816-923-2000

Cage: 60778

Contractor

CHEMSECO

17337

KANSAS CITY, MO 64130-2818

US

816-923-8200

Cage: 60778

Ingredients

XYLENES (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 1.3%

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150 STEL

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

MINERAL SPIRITS

CAS: 64741-41-9

Fraction By Weight: 1.3%

OSHA PEL100 PPM

ACGIH TLV: 100 PPM

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE/SKIN CONTACT:MAY CAUSE IRRIT. FOR XYLENE:ACUTE:OVEREXPOSURE CAN LEAD TO CENTRAL NERVOUS SYSTEM DEPRESSION PRODUCING SUCH EFFECTS AS HEADACHE, DIZZINESS, NAUSEA AND LOSS OF CONSCIOUSNESS. MAY CAUSE RESPIRATORY TRACT IRRITATION. SYSTEMIC:EXPOSURE MAY CAUSE LIVER OR KIDNEY DAMAGE. NOTE:NORMAL XYLENE (EFTS OF OVEREXP)

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:HLTH HAZ:TLV DOES NOT APPLY AS XYLENE MOLECULE IS ENCAPSULATED IN LATEX POLYMER.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid

First Aid:EYE:FLUSH WITH WATER FOR AT LEAST 15 MINUTES WHILE HOLDING EYELIDS OPEN. SKIN:WASH WITH SOAP AND WATER. INHAL:REMOVE TO FRESH AIR. INGEST:CONSULT PHYSICIAN IMMEDIATELY.

Fire Fighting

Flash Point:NONE

Extinguishing Media:MEDIA SUITABLE FOR SURROUNDING FIRE .

Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT .

Unusual Fire/Explosion Hazard:NONE

Accidental Release

Spill Release Procedures:SCRAPE INTO SUITABLE CONTAINER FOR DISPOSAL OR RECOVERY.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:KEEP FROM FREEZING-PRODUCT MAY COAGULATE. DO NOT WELD, HEAT AND/OR DRILL ON OR NEAR CONTAINERS. MINIMIZE SKIN CONTACT.

Other Precautions:STORE AT TEMPERATURES BETWEEN 32-140F.

Exposure Controls

Respiratory Protection:NONE REQD IF GOOD VENT IS MAINTAINED. USE NIOSH/MSHA SCBA (PRESSURE-DEMAND) APPROVED RESPIRATOR.

Ventilation:GENERAL MECHANICAL AT POINT OF RELEASE.

Protective Gloves:IMPERMEABLE GLOVES.

Eye Protection:SAFETY GLASSES OR CHEMICAL GOGGLES.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

Chemical Properties

Boiling Pt:B.P. Text:212F,100C

Vapor Pres:17 @68F

Vapor Density:1; WATER

Spec Gravity:1.51 (H*20=1)

Evaporation Rate & Reference:1.0 (H*20=1)

Solubility in Water:MISCIBLE

Appearance and Odor:OFF-WHITE COLORED PASTE; MILD ODOR

Percent Volatiles by Volume:53

Stability

Stability Indicator/Materials to Avoid:YES

NONE SPECIFIED BY MANUFACTURER.

Stability Condition to Avoid:EXCESSIVE TEMPERATURE EXTREMES.

Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CO AND/OR CO*2; TRACES OF THE MONOMER.

Disposal

Waste Disposal Methods:IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.