

Q D DECRATRIM UD BASE, 612-0003

MSDS Number

BSVCG

National Stock Number

8010-00N042007

Product Name

Q D DECRATRIM UD BASE, 612-0003

Manufacturer

DECRATREND PAINT CORP

Product Identification

Product ID: Q D DECRATRIM UD BASE, 612-0003

MSDS Date: 01/01/1992

FSC: 8010

NIIN: 00N042007

MSDS Number: BSVCG

Responsible Party

DECRATREND PAINT CORP

251 MASON WAY

CITY OF INDUSTRY , CA 91746

US

Emergency Phone: 818-333-4592

Info Phone: 818-333-4592

Cage: 42590

Contractor

DECRATREND PAINT CORP

CITY OF INDUSTRY, CA 91746

US

818-333-4592

Cage: 42590

Ingredients

2 @ 68F

CAS: 63148-69-6

Fraction By Weight: 60%

SOLVENT NAPHTHA PETROLEUM, MED ALIPHATIC; (NAPHTHA, MEDIUM

CAS: 64742-88-7

Fraction By Weight: 10%

OSHA PEL500 PPM (MFR)

ACGIH TLV: 100 PPM (MFR)

SOLVENT NAPHTHA (PETROLEUM); LIGHT AROMATIC NAPHTHA, LIGHT

CAS: 64742-95-6

RTECS: WF3400000

Fraction By Weight: < 5%

OSHA PEL100 PPM (MFR)

ACGIH TLV: 50 PPM (MFR)

3.31 LB/GL (0.397 G/L)

RTECS: 9999999VO

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHAL: EXCESS INHAL OF VAPS CAN CAUSE NASAL & RESP IRRIT, WEAKNESS, DIZZINESS, FATIGUE, NAUS, HEADACHE & POSSIBLE UNCONSCIOUSNESS AND EVEN ASPHYX. SKIN: PROLONGED OR REPEATED CONTACT CAN CAUSE MODERATE IRRITATION, DEFATTING, DERMATITIS. CAN CAUSE SEVERE EYE IRRITATION, REDNESS, TEARING AND BLURRED (EFTS OF OVEREXP)

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:HLTH HAZ: VISION. SKIN ABSORP: ORGANIC SOLVS ARE EASILY ABSORBED, DRYING OF SKIN, REDNESS, OR DERMATITIS ARE SIGNS OF RPTD OVEREXP TO THEIR DEFATTING ACTION. INGEST: CAN CAUSE GI IRRIT, NAUSEA, VOMIT & DIARR. ACUTE & CHRONIC: CAN CAUSE SEVERE IRRIT, REDNESS, TEARING, AND BLURRED VISION. SKIN: CAN CAUSE (SUPP DATA)

Medical Cond Aggravated by Exposure:NONE KNOWN.

First Aid

First Aid:EYE:FLUSH IMMED W/LRG AMTS OF WATER FOR AT LEAST 15 MIN. TAKE TO MD FOR MED TREATMENT. SKIN: WASH AFFECTED AREAS W/SOAP & WATER. REMOVE CONTAMINATED CLTHG. CONSULT MD IF IRRIT PERSISTS. INHAL: REMOVE TO FRESH AIR. RESTORE BREATHING. TREAT SYMPTOMATICALLY. CONSULT MD. INGEST: DRINK 1 OR 2 GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMIT. CONSULT MD OR POIS CONTROL CTR IMMED. TREAT SYMPTOMATICALLY.

Fire Fighting

Flash Point Method:TCC

Flash Point:102F,39C

Lower Limits:0.8%

Upper Limits:7%

Extinguishing Media:FOAM, CO*2, DRY CHEMICAL.

Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT .

Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND AND BE IGNITED BY HEAT, OPEN FLAME OR OTHER IGNITION SOURCES.

Accidental Release

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. DIKE, CONTAIN, OR ABSORB WITH INERT MATERIALS (SAND, VERMICULITE, ETC.) TRANSFER TO CONTAINERS FOR RECOVERY OR DISPOSAL. PREVENT RUNOFF INTO SEWERS, STREAMS, OR OTHER BODIES OF WATER.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:DO NOT STORE OR USE NEAR SOURCES OF HIGH TEMPERATURES, NEAR FIRE OR OPEN FLAME, OR OTHER IGNITION SOURCES.

Other Precautions:DO NOT TAKE INTERNALLY. AVOID PROLONGED OR REPEATED EXPOSURE TO LEVELS ABOVE TLV.

Exposure Controls

Respiratory Protection:TLV IS EXCEEDED USE NIOSH/MSHA APPROVED ORGANIC

VAPOR AND MIST, SUPPLIED AIR OR SCBA.
Ventilation:USE ADEQUATE VENTILATION TO MAINTAIN EXPOSURE BELOW TLV.
Protective Gloves:NITRILE RUBBER GLOVES.
Eye Protection:ANSI APRV CHEM WORK GOGG .
Other Protective Equipment:WEAR IMPERVIOUS CLOTHING. EYE WASH STATIONS WHICH MEET ANSI DESIGN CRITERIA .
Work Hygienic Practices:WASH HANDS BEFORE EATING OR USING RESTROOMS. REMOVE AND CONTAMINATED CLOTHING BEFORE REUSE.
Supplemental Safety and Health
EFTS OF OVEREXP: MODERATE IRRITATION, DEFATTING, AND DERMATITIS. INHAL: CAN CAUSE NASAL AND RESPIRATORY IRRITATION. ASPIRATION INTO LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. CHRONIC: PROLONGED OR REPEATED EXPOSURE ABOVE TLV MAY RESULT IN PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.

Chemical Properties

HCC:F4
Boiling Pt:B.P. Text:>310F,>154C
Vapor Pres:SEE INGS
Vapor Density:HVR/AIR
Spec Gravity:1.1 (H*2O=1)
Evaporation Rate & Reference:SLOWER THAN ETHER
Solubility in Water:NONE
Appearance and Odor:TYPICAL FOR SOLVENT BASED COATING.

Stability

Stability Indicator/Materials to Avoid:YES
CONTACT WITH STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:EXPOSURE TO HIGH TEMPERATURES OR OPEN IGNITION SOURCES.
Hazardous Decomposition Products:FORM TOXIC MATERIALS, CARBON DIOXIDE, CARBON MONOXIDE, VARIOUS HYDROCARBONS, ETC. ON THERMAL DECOMPOSITION.

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE OR FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.