

TOUCHDOWN 606 LATEX ADDITIVE

MSDS Number

BSWGS

National Stock Number

8010-00N041725

Product Name

TOUCHDOWN 606 LATEX ADDITIVE

Manufacturer

W F TAYLOR CO INC

Product Identification

Product ID:TOUCHDOWN 606 LATEX ADDITIVE

MSDS Date:10/07/1988

FSC:8010

NIIN:00N041725

MSDS Number: BSWGS

Responsible Party

W F TAYLOR CO INC

13660 EXCELIOR DR

SANTA FE SPRINGS , CA 90670

US

Emergency Phone: 213-802-1896

Info Phone: 213-802-1896

Cage: HO551

Contractor

W F TAYLOR CO INC

SANTA FE SPRINGS, CA 90670

US

213-802-1896

Cage: HO551

Ingredients

METHANOL; (METHYL ALCOHOL)

CAS: 67-56-1

RTECS: PC1400000

Fraction By Weight: 35%

OSHA PEL200PPM;250PPM STEL,S

ACGIH TLV: 200PPM;250PPM STEL,S

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

VOLATILE ORGANIC COMPOUNDS (VOC). 144 GRAMS/LITER -

RTECS: 9999999VO

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHAL: MAY CAUSE HEADACHE. EYES/SKIN:
MAY CAUSE MILD IRRITATION. INGEST: MAY CAUSE DIARRHEA.
Explanation of Carcinogenicity:NOT RELEVANT.
Effects of Overexposure:SEE HEALTH HAZARDS.
Medical Cond Aggravated by Exposure:NOT DETERMINED.

First Aid

First Aid:EYES:FLUSH W/WATER FOR AT LEAST 15 MINS. SEEK MEDICAL
ATTENTION IF IRRITATION PERSISTS. SKIN: WASH W/SOAP & WATER. APPLY
SKIN CREAM. SEEK MEDICAL ATTENTION IF IRRITATION PERSISTS. INHAL:
REMOVE TO FRE SH AIR. INGEST: DRINK TWO GLASSES OF WATER. DO NOT
INDUCE VOMITING. SEEK MEDICAL ATTENTION. VOMITING MAY CAUSE
CHEMICAL PNEUMONITUS.

Fire Fighting

Flash Point:WATERBASED
Extinguishing Media:WATER SPRAY, FOAM, CARBON DIOXIDE OR DRY CHEMICAL.
Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL
PROTECTIVE EQUIPMENT .
Unusual Fire/Explosion Hazard:NONE KNOWN.

Accidental Release

Spill Release Procedures:CONTAIN SPILL & SOAK UP W/SAND OR SAWDUST.
PLACE IN CLOSED CONTAINER.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:STORE IN A COOL PLACE. PROTECT AGAINST
PHYSICAL DAMAGE. USE IN WELL VENTILATED AREA. AVOID BREATHING
BUILDUP OF VAPOR.
Other Precautions:KEEP OUT OF REACH OF CHILDREN. FOLLOW ALL LABEL
DIRECTIONS.

Exposure Controls

Respiratory Protection:IF TLV IS EXCEEDED, USE NIOSH/MSHA APPROVED
SCBA.
Ventilation:IF TLV IS EXCEEDED, USE MECHANICAL EXHAUST.
Protective Gloves:NEOPRENE GLOVES.
Eye Protection:CHEMICAL WORKERS GOGGLES .
Other Protective Equipment:NONE.
Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.
Supplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

Chemical Properties

Boiling Pt:B.P. Text:212F,100C
Vapor Density:>1
Spec Gravity:0.9-1.1
Evaporation Rate & Reference:1 (WATER=1)
Solubility in Water:DILUTABLE
Appearance and Odor:THIN MILKY COLORED SOLUTION; MILD ODOR.

Stability

Stability Indicator/Materials to Avoid:YES
NONE.
Stability Condition to Avoid:NONE.
Hazardous Decomposition Products:OXIDES OF CARBON.

Disposal

Waste Disposal Methods:DISPOSE OF ALL WASTES IN ACCORDANCE W/FEDERAL,
STATE, AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.