

## **TRIBOLUBE-F167 OIL**

### **MSDS Number**

BSYLB

### **National Stock Number**

9150-01-036-9604

### **Product Name**

TRIBOLUBE-F167 OIL

### **Manufacturer**

AEROSPACE LUBRICANTS INC

### **Product Identification**

Product ID:TRIBOLUBE-F167 OIL

MSDS Date:10/11/1993

FSC:9150

NIIN:01-036-9604

MSDS Number: BSYLB

### **Responsible Party**

AEROSPACE LUBRICANTS INC.

1505 DELASHMUT AVE

COLUMBUS , OH 43212-2641

US

Emergency Phone: 614-291-3045

Info Phone: 614-291-3045

Cage: 66164

### **Contractor**

AEROSPACE LUBRICANTS INC.

COLUMBUS, OH 43228

US

614-878-3600

Cage: 66164

### **Ingredients**

NON HAZARDOUS INGREDIENTS

Fraction By Weight: 100%

PERFLUORINATED POLYETHER

### **Hazards**

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SKIN:PROLONGED CONTACT MAY CAUSE MILD IRRITATION.INHAL:DECOMPOSITION PRODUCTS FORMED AT HIGH TEMPERATURES MAY CAUSE "POLYMER FEVER".

Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1% OR GREATER IS LISTED AS A CARCINOGEN BY NTP, IARC, OR OSHA.

Effects of Overexposure:INHAL:POLYMER FEVER. SKIN:IRRITATION.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

### **First Aid**

First Aid:SKIN:REMOVE CONTAMINATED CLOTHING;WASH WITH SOAP AND

WATER.EYES:FLUSH WITH WATER FOR 15 MINUTES.INHAL:REMOVE TO FRESH AIR.GIVE OXYGEN OR ARTIFICIAL RESPIRATION IF NEEDED.INGEST:IF CONSCIOUS,GIVE LARGE AMOUNTS OF WATER.DO NOT INDUCE VOMITING.GET PROMPT QUALIFIED MEDICAL ATTENTION.

## Fire Fighting

Flash Point:NONE

Extinguishing Media:MEDIA APPROPRIATE FOR SURROUNDING FIRE.

Fire Fighting Procedures:USE A SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE EQUIPMENT.COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:FIRE CONDITIONS AND TEMPERATURES ABOVE 554F(290C) MAY EVOLVE TOXIC FUMES.

## Accidental Release

Spill Release Procedures:SOAK UP WITH A NON-COMBUSTIBLE INERT ABSORBANT(CLAY,SAND);PLACE IN PROPER CONTAINER FOR DISPOSAL.WASH SPILL AREA TO REMOVE SLIPPINESS.

Neutralizing Agent:NONE

## Handling

Handling and Storage Precautions:STORE AWAY FROM FLAMMABLE OR EXPLOSIVE MATERIALS.

Other Precautions:TOXIC VAPORS MAY FORM ABOVE 554F (290C).DO NOT CONTAMINATE SMOKING PRODUCTS WITH THIS MATERIAL.

## Exposure Controls

Respiratory Protection:NONE NORMALLY REQUIRED.

Ventilation:MAINTAIN ADEQUATE MECHANICAL VENTILATION.

Protective Gloves:PLASTIC DISPOSABLE

Eye Protection:SAFETY GLASSES

Other Protective Equipment:APRON, LAB COAT OR COVERALLS.HAVE EYE WASH AVAILABLE.

Work Hygienic Practices:WASH HANDS.SEPERATE WORK CLOTHES FROM STREET CLOTHES.LAUNDER WORK CLOTHES BEFORE REUSE.KEEP FOOD OUT OF THE WORK AREA.

Supplemental Safety and Health

INGREDIENT #2 COMES FROM INFORMATION ON THE TIR.

## Chemical Properties

HCC:V6

Boiling Pt:B.P. Text:>392F,>200C

Decomp Temp:Decomp Text:554F,290C

Vapor Pres:2.9E-12

Spec Gravity:1.851

Solubility in Water:NEGLIGIBLE

Appearance and Odor:LIQUID;CLEAR;NO ODOR

## Stability

Stability Indicator/Materials to Avoid:YES

MOLTEN ALKALI METALS, INTERHALOGEN COMPOUNDS, STRONG OR NON AQUEOUS ALKALI,LEWIS ACIDS ABOVE 100C.

Stability Condition to Avoid:FIRE,TEMPERATURES ABOVE 554F(290C).

Hazardous Decomposition Products:TOXIC FLUORINE COMPOUNDS

## Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL,STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.

