

A P GREEN INSULATING CEMENT

MSDS Number

BSZHX

National Stock Number

8040-00F032344

Product Name

A P GREEN INSULATING CEMENT

Manufacturer

P K INSULATION MFG CO INC

Product Identification

Product ID:A P GREEN INSULATING CEMENT

MSDS Date:09/17/1992

FSC:8040

NIIN:00F032344

MSDS Number: BSZHX

Responsible Party

P K INSULATION MFG CO INC

2417 DAVIS BLVD

JOPLIN , MO 64804

US

Emergency Phone: 417-781-6380

Info Phone: 417-781-6380

Cage: 3N726

Contractor

P K INSULATION MFG CO INC

JOPLIN, MO 64804

US

417-781-6380

Cage: 3N726

Ingredients

CALCIUM CARBONATE, DOMOLITE, LIMESTONE, WHITING

CAS: 1317-65-3

RTECS: EV9580000

ACGIH TLV: 10 MG/CUM (DUST)

SODIUM NITRITE

CAS: 7632-00-0

RTECS: RA1225000

ACGIH TLV: 10 MG/CUM

EPA Report Quantity: 100 LBS

DOT Report Quantity: 100 LBS

MINERAL WOOL FIBER

ACGIH TLV: 10 MG/CUM

ALUMINUM SILICATE, BENTONITE, MONTMORILLONITE, CLAY

CAS: 1302-78-9

RTECS: CT9450000

ACGIH TLV: 10 MG/CUM (DUST)

Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES & SKIN: IRRITATION. INHALATION:
UPPER RESPIRATORY TRACT IRRITATION. PROLONGED INHALATION OF DUST
MAY CAUSE LUNG FUNCTION.
Explanation of Carcinogenicity:NONE
Medical Cond Aggravated by Exposure:UPPER RESPIRATORY & LUNG DISEASES

First Aid

First Aid:EYES: RINSE W/WATER. SKIN: WASH W/SOAP & WATER. INHALATION:
REMOVE TO FRESH AIR. REMOVE FIBERS & DUST FROM NOSE & DRINK WATER
TO CLEAR THROAT. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point:NON-COMBUSTIBLE
Extinguishing Media:CO2, WATER, DRY CHEMICAL

Accidental Release

Spill Release Procedures:AVOID CREATING DUST. USE WET VACUUM.

Handling

Handling and Storage Precautions:STORE ON PALLETS IN DRY AREA TO
MINIMIZE DUST WHILE HANDLING.

Exposure Controls

Respiratory Protection:WEAR NIOSH/MSHA APPROVED RESPIRATOR
Ventilation:USE NATURAL OR MECHANICAL WHILE MATERIAL IS IN DRY STATE.
Protective Gloves:WATERPROOF OR RUBBER
Eye Protection:SAFETY GLASSES, GOGGLES
Other Protective Equipment:WEAR LONG SLEEVED, LOOSE FITTING CLOTHING
W/CAP.
Work Hygienic Practices:WASH WORK CLOTHES SEPARATE FROM OTHER CLOTHING
TO PREVENT POSSIBLE MIGRATION OF MINERAL WOOL/DUST TO OTHER
CLOTHING.
Supplemental Safety and Health
ALWAYS RINSE WASHER W/WATER AFTER EACH USE.

Chemical Properties

Appearance and Odor:DRY, GRAY, GRANULAR MIXITURE, NO ODOR

Stability

Stability Indicator/Materials to Avoid:YES
STRONG ACIDS

Disposal

Waste Disposal Methods:DISPOSE IN LANDFILL I/A/W LOCAL, STATE & FEDERAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.