

Y430 WONDER-TONES INTERIOR LATEX FLAT WALL PAINT

MSDS Number

BTBCG

National Stock Number

8010-00F032714

Product Name

Y430 WONDER-TONES INTERIOR LATEX FLAT WALL PAINT

Manufacturer

AMERITONE PAINT CORP

Product Identification

Product ID:Y430 WONDER-TONES INTERIOR LATEX FLAT WALL PAINT

MSDS Date:11/20/1987

FSC:8010

NIIN:00F032714

MSDS Number: BTBCG

Responsible Party

AMERITONE PAINT CORP

18414 S SANTA FE AVE

COMPTON , CA 90221

US

Emergency Phone: 213-639-6791

Info Phone: 213-639-6791

Cage: FO133

Contractor

AMERITONE PAINT CORP/COMPTON, CA 90221

190

LONG BEACH, CA 90801

US

310-639-6791

Cage: FO133

Ingredients

DIATOMACEOUS EARTH, FLUX-CALCINED, NATURAL, SILICA,

CAS: 68855-54-9

Fraction By Weight:

CLAY (KAOLIN), ALUMINUM SILICATE

CAS: 1332-58-7

RTECS: GF1670500

Fraction By Weight:

ACGIH TLV: 10 MG/CUM TOTAL DUST

TITANIUM DIOXIDE, TIO2

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight:

OSHA PEL15 MG/CUM

ACGIH TLV: 10 MG/CUM (DUST)

PROPANOIC ACID, 2-METHYL, MONOESTER

CAS: 25265-77-4

RTECS: UF6000000

Fraction By Weight:

AMMONIUM HYDROXIDE, AQUA AMMONIA

CAS: 1336-21-6

RTECS: BQ9625000

Fraction By Weight:

ACGIH TLV: 25 PPM

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

ATTAPULGITE CLAY, HYDROUS MAGNESIUM ALUMINUM SILICATE

CAS: 12174-11-7

RTECS: RT6400000

Fraction By Weight:

SILICA DIOXIDE, CRYSTALLINE QUARTZ, SAND (SUSPECTED HUMAN

CAS: 14808-60-7

RTECS: VV7330000

Fraction By Weight:

ACGIH TLV: 0.1 MG/CUM RESP DUST

10.6-11.20

RTECS: 9999999WG

188-233 G/L

RTECS: 9999999VO

NAPHTHA PETROLEUM, HEAVY ALKYLATE C9-C12 BOILING PT

CAS: 64741-65-7

Fraction By Weight:

OSHA PEL500 PPM

ACGIH TLV: 100 PPM

ETHYLENE GLYCOL, GLYCOL

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight:

ACGIH TLV: C 127 MG/CUM

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

CHLOROTHALONIL; TETRACHLOROISOPHTHALONITRILE; DACONIL;

CAS: 1897-45-6

RTECS: NT2600000

Fraction By Weight:

Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:INHALATION: RESPIRATORY TRACT IRRITATION. SKIN/EYES: IRRITATION. PROLONGED & REPEATED INHALATION OF SPRAY MIST &/OR SANDING DUST OVER A PERIOD OF YEARS MAY CAUSE DUST DISEASE OF THE LUNGS.
Explanation of Carcinogenicity:SEE INGREDIENTS
Effects of Overexposure:INHALATION: HEADACHE, NAUSEA, DIZZINESS. SKIN/EYES: IRRITATION.

First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. EYES: FLUSH IMMEDIATELY W/PLENTY OF WATER FOR AT LEAST 15 MINS. SKIN: REMOVE W/SOAP & WATER. REMOVE SOILED CLOTHING. INGESTION: DRINK 1 OR 2 GLASSES OF WATER TO DILUTE . DON'T INDUCE VOMITING. TREAT SYMPTOMATICALLY. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point:NONE
Extinguishing Media:CO2, DRY CHEMICAL, FOAM OR OTHER NFPA APPROVED METHOD FOR TREATING A CLASS B FIRE.
Fire Fighting Procedures:USE FULL PROTECTIVE EQUIPMENT & SCBA. WATER SPRAY MAY BE INEFFECTIVE. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE. USE WATER TO COOL FIRE EXPOSED CONTAINERS.
Unusual Fire/Explosion Hazard:DUE TO PRESSURE BUILD UP, CLOSED CONTAINERS EXPOSED TO EXTREME HEAT MAY EXPLODE.

Accidental Release

Spill Release Procedures:WASH W/WATER. CONTAIN SPILLED MATERIAL & REMOVE WITH INERT ABSORBENT. STORE IN CLOSED CONTAINER UNTIL PROPERLY DISPOSED OF.

Handling

Handling and Storage Precautions:STORE CONTAINER CLOSED WHEN NOT IN USE. DON'T REUSE EMPTY CONINERS. DON'T TRANSFER TO BOTTLES OR UNMARKED CONTAINERS.
Other Precautions:KEEP OUT OF REACH OF CHILDREN. DON'T GET IN EYES OR BREATHE VAPORS, SPRAY MIST OR SANDING DUST.

Exposure Controls

Respiratory Protection:WHEN SPRAY APPLIED IN OUTDOOR OR OPEN AREAS W/UNRESTRICTED VENTILATION & DURING SANDING/GRINDING OPERATIONS, USE A NIOSH/MSHA MECHANICAL FILTER RESPIRATOR. IN RESTRICTED VENTILATIONS AREAS, USE A NIOS H/MSHA CHEMICAL/MECHANICAL FILTERS. SUPP
Ventilation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION IN VOLUME & PATTERN TO KEEP CONCENTRATIONS BELOW TLV.
Eye Protection:SAFETY GLASSES W/SPLASH GUARD/SIDESHIELD
Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. WASH HANDS BEFORE EATING, SMOKING OR USING THE WASHROOM.
Supplemental Safety and Health
CON'T: WHEN USED IN CONFINED AREAS, USE A NIOSH/MSHA APPROVED AIR

SUPPLY RESPIRATOR OR HOOD. USE A NIOSH/MSHA APPROVED RESPIRATOR WHEN FLAME CUTTING, WELDING, BRAZING & SANDING MATERIAL COATED W/THIS PRODUCT.

Chemical Properties

Boiling Pt:B.P. Text:212-369F
Vapor Density:>1
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:70-72

Stability

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:EXTREME HEAT, TEMPS >110F, FREEZING OR OTHER SOURCES OF IGNITION.
Hazardous Decomposition Products:FUMES MAY CONTAIN CO, CO2, OXIDES OF NITROGEN.

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE & FEDERAL REGULATIONS. INCINERATE ONLY IN APPROVED FACILITY. DON'T INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.