

PHTHALO GREEN PAINT, TY6468

MSDS Number

BTFYQ

National Stock Number

8010-00N043183

Product Name

PHTHALO GREEN PAINT, TY6468

Manufacturer

DEERE AND CO

Product Identification

Product ID: PHTHALO GREEN PAINT, TY6468 MSDS Date: 02/15/1989 FSC:8010 NIIN:00N043183 MSDS Number: BTFYQ

Responsible Party

DEERE & CO

JOHN DEERE RD

MOLINE, IL 61265

US

Emergency Phone: 309-765-2767; 309-765-4292

Info Phone: 309-765-2767

Cage: 4X159 **Contractor**

DEERE AND CO

MOLINE, IL 61265

US

309-765-8000

Cage: 75160

Ingredients

0.7%

CAS: 8052-41-3 RTECS: WJ8925000 Fraction By Weight: OSHA PEL100 PPM ACGIH TLV: 100 PPM

KEROSENE (PETROLEUM), HYDROTREATED; (HYDROTREATED LIGHT

RTECS: 0A5504000 Fraction By Weight: OSHA PEL100 PPM (MFR) ACGIH TLV: 100 PPM (MFR)

CAS: 64742-47-8



0.9%

CAS: 8032-32-4 RTECS: OI6180000 Fraction By Weight:

OSHA PEL300 PPM; 400 STEL

ACGIH TLV: 300 PPM

1.3%

CAS: 108-88-3
RTECS: XS5250000
Fraction By Weight:

OSHA PEL100 PPM; 150 STEL, S

ACGIH TLV: 50 PPM, S

EPA Report Quantity: 1000 LBS DOT Report Quantity: 1000 LBS

2.

CAS: 111-15-9 RTECS: KK8225000 Fraction By Weight: OSHA PEL100 PPM, S

ACGIH TLV: 5 PPM, S

1.1

CAS: 1330-20-7 RTECS: ZE2100000 Fraction By Weight:

OSHA PEL100 PPM; 150 STEL ACGIH TLV: 100 PPM; 150 STEL EPA Report Quantity: 1000 LBS DOT Report Quantity: 1000 LBS

0.9%

CAS: 64742-89-8
Fraction By Weight:
OSHA PEL300 PPM (MFR)
ACGIH TLV: 300 PPM (MFR)

ANTIMONY OXIDE; (ANTIMONY TRIOXIDE) (SARA III)

CAS: 1309-64-4



RTECS: CC5650000

Fraction By Weight:

OSHA PEL0.5 MG/M3 (SB) ACGIH TLV: 0.5 MG/M3 (SB)

EPA Report Quantity: 1000 LBS DOT Report Quantity: 1000 LBS

ALUMINUM SILICATE

CAS: 14504-95-1 Fraction By Weight:

OSHA PEL5 MG/M3 (AL) (MFR) ACGIH TLV: 5 MG/M3 (AL) (MFR)

0.05 MG/M3

CAS: 1344-37-2

Fraction By Weight:

OSHA PELSEE INGREDIENT NAME ACGIH TLV: SEE INGREDIENT NAME

1); (LEAD CHROMATE)

CAS: 7758-97-6

RTECS: GB2975000

Fraction By Weight:

OSHA PEL0.05 MG/M3 (MFR) ACGIH TLV: 0.05 MG/M3 (MFR)

1) (SARA III)

CAS: 7446-14-2

RTECS: OG4375000 Fraction By Weight:

OSHA PEL0.05 MG/M3 (MFR) ACGIH TLV: 0.05 MG/M3 (MFR)

EPA Report Quantity: 100 LBS
DOT Report Quantity: 100 LBS

Hazards

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation: YES Skin: YES Ingestion: NO Reports of Carcinogenicity: NTP: YES IARC: YES OSHA: NO

Health Hazards Acute and Chronic:NOTE: TOLUENE (108-88-3) & LEAD APPEAR ON NAVY LISTING OF OCCUP CHEM REPROD HAZARDS. SEEK CONSULTATION FROM APPROP HLTH PROFESSIONALS CONCERNING LATEST HAZ LIST INFO & SAFE HNDLG & EXPOS INFO . INHAL:ANESTH. IRRIT OF RESP TRACT OR ACUTE NERVISOR DEPRESS CHARACT BY HDCH, DIZZ, STAG GAIT, CONFUSN,

(EFTS OF OVEREXP)

Explanation of Carcinogenicity:LEAD CHROMATE:IARC MONOGRAPHS ON THE EVALUATION OF CARCINOGENIC RISK OF CHEMS TO MAN, VOL 49, PG 49,



1990: (SUPP DATA)

Effects of Overexposure:HLTH HAZ:UNCON OR COMA. PRLNGD/RPTD OVEREXPOS TO SOLVS HAS BEEN ASSOC W/CNS, KIDNEY & LIVER DAM. LEAD POISONING CHARACT BY METALLIC TASTE, LOSS OF APPETITE, INDIGESTION, NAUS, VOM, CONSTIP, ABDOM CRAM PS, SLEEP DISTURB & WEAK. SKIN/EYE CONT:IRRIT. MAY CAUSE DERM. RED, PIMPLY ERUPTIONS WHICH CAN RSLT FROM ANTIMONY.

Medical Cond Aggravated by Exposure: PRE-EXISTING SKIN, EYE, RESPIRATORY CONDITIONS & CNS DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

First Aid

First Aid:INHAL:REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM & QUIET. EYE:IMMEDIATELY FLUSH W/WATER FOR AT LEAST 15 MINS. SKIN:WASH W/SOAP & WATER ONLY. INGEST:DO NOT INDUCE VOMITING. NOTIFY MD IN ALL CAS ES.

Fire Fighting

Flash Point: 45.0F, 7.2C Lower Limits: SEE INGREDS

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL OR FOAM. Fire Fighting Procedures: WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT. WATER MAY BE INEFFECTIVE. WATER MAY BE USED TO KEEP FIRE EXPOSED CHEMICALS COOL. Unusual Fire/Explosion Hazard: KEEP CONTRS TIGHTLY CLSD. ISOLATE FROM

Unusual Fire/Explosion Hazard: KEEP CONTRS TIGHTLY CLSD. ISOLATE FROM HEAT, ELEC EQUIP, SPARKS & OPEN FLAME. CLSD CONTRS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. DO NOT APPLY TO HOT SURF.

Accidental Release

Spill Release Procedures: REMOVE ALL IGNITION SOURCES. AVOID BREATHING VAPORS. VENTILATE AREA. CLEAN UP W/INERT ABSORBENT & NON-SPARKING TOOLS.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. DO NOT EXPOSE TO DIRECT SUNLIGHT OR OTHER HEAT SOURCE. DO NOT PUNCTURE OR INCINERATE. CONTRS SHOULD BE GROUNDED WHEN POURING.

Other Precautions:DO NOT FLAME CUT, BRAZE OR WELD PARTS COATED W/PAINT. DO NOT TAKE INTERNALLY. KEEP AWAY FROM CHILDREN.

Exposure Controls

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATOR. Ventilation:LOCAL EXHAUST TO KEEP TLV, PEL & LEL BELOW ACCEPTABLE LEVELS.

Protective Gloves: IMPERVIOUS GLOVES .

Eye Protection: ANSI APPR CHEMICAL SAFETY GOGGLES

Other Protective Equipment: NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices: NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

EXPLAN OF CARCIN:GROUP 1. NTP 6TH ANNUAL REPORT ON CARCINOGENS, 1991:KNOWN TO BE CARCINOGENIC; ANTIMONY TRIOXIDE, IARC GROUP 2B

Chemical Properties

HCC:F3

Vapor Pres:SEE INGRED Vapor Density:HVR/AIR

Evaporation Rate & Reference: Solubility in Water: NOT APPICABLE

Appearance and Odor: GREEN; SOLVENT ODOR.

Percent Volatiles by Volume: 70

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.
Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE,
OXIDES OF ANTIMONY, ALUMINUM, LEAD AND CHROME.



Disposal

Waste Disposal Methods: IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.