

205-00 P F INTERIOR LATEX FLAT WHITE

MSDS Number

BTNRW

National Stock Number

8010-00F034490

Product Name

205-00 P F INTERIOR LATEX FLAT WHITE

Manufacturer

O'BRIEN CORP

Product Identification

Product ID:205-00 P F INTERIOR LATEX FLAT WHITE

MSDS Date:05/26/1992

FSC:8010

NIIN:00F034490

MSDS Number: BTNRW

Responsible Party

O'BRIEN CORPORATION

450 E. GRAND AVENUE

SOUTH SAN FRANCISCO , CA 94080-6207

US

Emergency Phone: 415-761-2300

Info Phone: 800-338-8084/415-761-2300

Cage: 85207

Contractor

O'BRIEN CORPORATION, FULLER O'BRIEN PAINTS

SOUTH SAN FRANCISCO, CA 94080-6207

US

Cage: 85207

Ingredients

CALCIUM CARBONATE, DOMOLITE, LIMESTONE, WHITING

CAS: 1317-65-3

RTECS: EV9580000

Fraction By Weight: 40-50%

ACGIH TLV: 10 MG/CUM (DUST)

TITANIUM DIOXIDE, TIO2

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: 10-15%

OSHA PEL15 MG/CUM

ACGIH TLV: 10 MG/CUM (DUST)

ETHYLENE GLYCOL, GLYCOL

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight:

ACGIH TLV: C 127 MG/CUM

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

ETHYLENE OXIDE (SUSPECTED HUMAN CARCINOGEN BY

CAS: 75-21-8

RTECS: KX2450000

Fraction By Weight:

ACGIH TLV: 1.8 MG/CUM (A2)

EPA Report Quantity: 10 LBS

DOT Report Quantity: 10 LBS

SODIUM ALUMINOSILICATE *94-2*

CAS: 1344-00-9

Fraction By Weight:

SILICA DIOXIDE, CRYSTALLINE QUARTZ, SAND (SUSPECTED HUMAN

CAS: 14808-60-7

RTECS: VV7330000

Fraction By Weight:

ACGIH TLV: 0.1 MG/CUM RESP DUST

113.55 G/L

RTECS: 9999999VO

Hazards

LD50 LC50 Mixture:ORAL LD50 (RAT): 6450MG/KG (SEE SUPP)

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:EYES/SKIN: PRIMARY IRRITATION.

INHALATION: HEADACHE & NAUSEA.

Explanation of Carcinogenicity:SEE INGREDIENTS.

Effects of Overexposure:EYES/SKIN: PRIMARY IRRITATION. INHALATION:
HEADACHE & NAUSEA

First Aid

First Aid:INGESTION: DRINK 1-2 GLASSES OF WATER. INDUCE VOMITING BY
PLACING FINGER IN BACK OF THROAT. NEVER GIVE ANYTHING BY MOUTH TO
AN UNCONSCIOUS PERSON. INHALATION: REMOVE TO FRESH AIR. RESTORE
BREATHING. EYES: IMMEDIATELY FLUSH W/COOL WATER. SKIN: WASH
THOROUGHLY W/SOAP & WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point:>200F

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN
EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures:SOAK UP & REMOVE W/INERT ABSORBENT MATERIAL.

PROVIDE ADEQUATE VENTILATION.

Handling

Handling and Storage Precautions:KEEP FROM FREEZING. AVOID PROLONGED CONTACT W/SKIN.

Other Precautions:DON'T INGEST. KEEP OUT OF REACH OF CHILDREN.

Exposure Controls

Respiratory Protection:APPROVED MECHANICAL RESPIRATOR/MASK TO AVOID BREATHING SPRAY MIST.

Ventilation:SUFFICIENT IN VOLUME & PATTERN TO KEEP AIR CONTAMINATION CONCENTRATION BELOW OSHA PEL/ACGIH TLV LIMIT.

Eye Protection:GOGGLES/SAFETY GLASSES W/SIDE SHIELDS

Other Protective Equipment:OVERALLS

Work Hygienic Practices:REMOVE & WASH CONTAMINATED CLOTHING. DISCARD CONTAMINATED SHOES.

Supplemental Safety and Health

LD50 INFORMATION IS FOR CALCIUM CARBONATE.

Chemical Properties

Boiling Pt:B.P. Text:212F

Vapor Density:Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:74.73

Stability

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:EXTREME HEAT, FREEZING

Hazardous Decomposition Products:CO, CO2, NITROGEN DIOXIDE

Disposal

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/FEDERAL, STATE & LOCAL REGULATIONS. DON'T INCINERATE IN CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.