

A-1104 PRIMER FOR PLASTISOL COATINGS

MSDS Number

BTWCQ

National Stock Number

8030-01-041-1598

Product Name

A-1104 PRIMER FOR PLASTISOL COATINGS

Manufacturer

QCM COMPANY

Product Identification

Product ID:A-1104 PRIMER FOR PLASTISOL COATINGS

MSDS Date:05/20/1994

FSC:8030

NIIN:01-041-1598

Kit Part:Y

MSDS Number: BTWCQ

Responsible Party

QCM COMPANY

930 SOUTH CENTRAL AVENUE

KENT , WA 98032

US

Emergency Phone: 206-859-0933/800-424-9300 CHEMTREC

Info Phone: 206-859-0933

Preparer: ROY WHEELDON

Cage: 8L872

Contractor

Q C M CO

KENT, WA 98032-6105

US

253-859-0933, FAX 253-859-0935

Cage: 8L872

Ingredients

FINAL RQ 5000 LBS)

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight: 61.8%

OSHA PEL200 PPM

ACGIH TLV: 200 PPM

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

FINAL RQ 100 LBS)

CAS: 64-17-5

RTECS: KQ6300000

Fraction By Weight: 20%

OSHA PEL1000 PPM

ACGIH TLV: 1000 PPM

5.78 LBS/GAL (692 GRAMS/LITER); VOC PER

RTECS: 9999999VO

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SKIN, EYE, RESPIRATORY AND
GASTROINTESTINAL IRRITATION, POSSIBLY SEVERE. EXCESSIVE INHALATION
MAY PRODUCE CENTRAL NERVOUS SYSTEM DEPRESSION.
Explanation of Carcinogenicity:NONE KNOWN

First Aid

First Aid:EYE CONTACT: IMMEDIATELY FLUSH WITH LARGE AMOUNTS OF WATER
FOR AT LEAST 15 MINUTES. SEEK MEDICAL ATTENTION. SKIN CONTACT:
REMOVE CONTAMINATED CLOTHING. WASH THOROUGHLY WITH SOAP AND WATER.
INHALATION: SEEK IMMEDIATE MEDICAL ATTENTION. DO NOT INDUCE
VOMITING.

Fire Fighting

Flash Point Method:TCC
Flash Point:16.0F,-8.9C
Lower Limits:1.8
Upper Limits:19.0
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL
Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS WITH
FULL FACEPIECE. COOL CONTAINERS IN VICINITY WITH WATER SPRAY.
Unusual Fire/Explosion Hazard:KEEP ALL IGNITION SOURCES AWAY. GROUND
ALL CONTAINERS. VAPORS MAY TRAVEL TO SOURCE OF IGNITION AND CAUSE
FLASHBACK. FIRE CAUSES ACID SMOKE AND/OR FUMES.

Accidental Release

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. SMALL SPILLS:
TAKE UP WITH ABSORBENT MATERIAL. LARGE SPILLS: DAM AND RECOVER.

Handling

Handling and Storage Precautions:AVOID HIGH TEMPERATURE AREA AND
IGNITION SOURCES. ALL HANDLING EQUIPMENT SHOULD BE GROUNDED AND
EXPLOSION PROOF. AVOID ALL PERSONAL CONTACT.
Other Precautions:WASH THOROUGHLY AFTER HANDLING.

Exposure Controls

Respiratory Protection:USE APPROVED SELF-CONTAINED BREATHING APPARATUS
IF NECESSARY.
Ventilation:LOCAL EXHAUST: NECESSARY. MECHANICAL (GENERAL): NECESSARY.
Protective Gloves:RUBBER OR NEOPRENE
Eye Protection:CHEMICAL SPALSH GOGGLES
Other Protective Equipment:SAFETY SHOWER. EYE WASH STATION.
Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:165F,74C
Vapor Pres:85 @ 20C
Vapor Density:2.4
Spec Gravity:0.86 (WATER=1)
Evaporation Rate & Reference:4.6 (BU AC=1)
Solubility in Water:APPRECIABLE
Appearance and Odor:CLEAR TO AMBER LIQUID, KETONE ODOR
Percent Volatiles by Volume:86

Stability

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid: STRONG ACIDS OR OXIDIZERS, HIGH TEMPERATURES

Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE, MISCELLANEOUS HYDROCARBON

Conditions to Avoid Polymerization: STRONG OXIDIZERS, ALL IGNITION SOURCES.

Disposal

Waste Disposal Methods: ACCORDING TO STATE, FEDERAL, AND LOCAL REGULATIONS. HAZARDOUS WASTE CODE: F005, D001, U159, FLAMMABLE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.