

X STAMPER INK (X200) VIOLET

MSDS Number

BVDWT

National Stock Number

7510-00N050638

Product Name

X STAMPER INK (X200) VIOLET

Manufacturer

SHACHIHATA INDUSTRIAL CO LTD

Product Identification

Product ID:X STAMPER INK (X200) VIOLET

MSDS Date:12/05/1987

FSC:7510

NIIN:00N050638

MSDS Number: BVDWT

Responsible Party

SHACHIHATA INDUSTRIAL CO LTD

NO 69 AMATSUKA-CHO 4-CHOME

NISHI-KU NAGOYA-SHI AICHI-KEN, JAPAN

Emergency Phone: 310-530-4445

Info Phone: 310-530-4445

Cage: B0964

Contractor

SHACHIHATA INDUSTRIAL CO LTD

NISHI-KU NAGOYA-SHI AICHI-KEN, JAPAN

310-530-4445

Cage: B0964

Ingredients

CASTOR OIL DERIVATIVE

CAS: 123-94-4

Fraction By Weight: 42-48%

OSHA PELN/K

ACGIH TLV: N/K

ETHANOL, 2-(2-BUTOXYETHOXY)-; (2-(2-BUTOXYETHOXY)-ETHANOL)

CAS: 112-34-5

RTECS: KJ9100000

Fraction By Weight: 10-12%

OSHA PEL50 PPM

ACGIH TLV: 50 PPM

1,2-PROPANEDIOL; (PROPYLENE GLYCOL)

CAS: 57-55-6

RTECS: TY2000000

Fraction By Weight: 11-13%

OSHA PELN/K

ACGIH TLV: N/K

ISOPROPYL ALCOHOL

CAS: 67-63-0

RTECS: NT8050000

Fraction By Weight: 8-10%

OSHA PEL400 PPM;500 STEL

ACGIH TLV: 400 PPM;500 STEL

9-OCTADECENOIC ACID, (Z)-; (FATTY ACID GROUP)

CAS: 112-80-1

RTECS: RG2275000

Fraction By Weight: 5-8%

OSHA PELN/K

ACGIH TLV: N/K

RESIN

CAS: 68441-83-8

Fraction By Weight: 1-9%

OSHA PELN/K

ACGIH TLV: N/K

DYESTUFF

CAS: 52080-58-7

Fraction By Weight: 8-12%

OSHA PELN/K

ACGIH TLV: N/K

DYESTUFF

CAS: 509-34-2

OSHA PELN/K

ACGIH TLV: N/K

DYESTUFF

CAS: 1325-86-6

OSHA PELN/K

ACGIH TLV: N/K

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: SKIN: NO SIGNIFICANT EFFECT.
EYES: MAY CAUSE SLIGHT IRRITATION.
Explanation of Carcinogenicity:NOT RELEVANT
Effects of Overexposure:NONE.
Medical Cond Aggravated by Exposure:NONE.

First Aid

First Aid:SKIN: REMOVE LIQUID FROM SKIN W/DRY CLOTH OR TOWEL AND WASH EXPOSED AREA WITH SOAP. EYES: IMMEDIATELY FLUSH COPIOUSLY WITH WATER FOR AT LEAST 15 MINUTES AND OBTAIN MED ASSIST. INHAL: REMOVE TO FRESH AIR. SU PPORT BRTHG (GIVE O*2/ARTF RESP) . INGEST: CALL MD IMMEDIATELY .

Fire Fighting

Flash Point Method:CC
Flash Point:99.7F,37.6C
Lower Limits:2%
Upper Limits:12%
Extinguishing Media:FOAM, DRY CHEMICAL.
Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT .
Unusual Fire/Explosion Hazard:NONE.

Accidental Release

Spill Release Procedures:SCRAPE UP WITH CARDBOARD OR RAG AND WASH AREA WITH DETERGENT.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:STORE IN A COOL PLACE AND KEEP AWAY FROM SUNLIGHT, HEAT, FLAME.
Other Precautions:NOT REQUIRED.

Exposure Controls

Respiratory Protection:NOT REQUIRED. USE NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN .
Ventilation:NOT REQUIRED.
Protective Gloves:PLASTIC FILM/RUBBER GLOVES.
Eye Protection:ANSI APPROVED CHEM WORKS GOGGLES .
Other Protective Equipment:NOT REQUIRED.
Work Hygienic Practices:MUST BE KEPT OUT OF REACH OF CHILDREN.
Supplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

Chemical Properties

Melt/Freeze Pt:M.P/F.P Text:5F,-15C
Spec Gravity:1.04(H*20=1)
Solubility in Water:A LITTLE
Appearance and Odor:PERFUME ODOR.

Stability

Stability Indicator/Materials to Avoid:YES
NONE.
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.
Hazardous Decomposition Products:NONE.

Disposal

Waste Disposal Methods:CAN BE BURNED IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.