

207, FULLER-O'BRIEN AND CROWN SOLVENT- (SUPP DATA)

MSDS Number

BVDXT

National Stock Number

8010-00N050805

Product Name

207, FULLER-O'BRIEN AND CROWN SOLVENT- (SUPP DATA)

Manufacturer

O'BRIEN CORP

Product Identification

Product ID: 207, FULLER-O'BRIEN AND CROWN SOLVENT- (SUPP DATA)

MSDS Date: 03/01/1990

FSC: 8010

NIIN: 00N050805

MSDS Number: BVDXT

Responsible Party

O'BRIEN CORP

450 EAST GRAND AVENUE

SOUTH SAN FRANCISCO , CA 94080

US

Emergency Phone: 800-424-9300(CHEMTREC)

Info Phone: 800-338-8040

Cage: FO983

Contractor

O'BRIEN CORP

SOUTH SAN FRANCISCO, CA 94080

US

(415) 761-2300

Cage: FO983

Ingredients

LIMIT. FOR BAKING FINISHES, VENT VAPORS EMITTED ON

RTECS: 9999999ZZ

WITH A RAG AND WASH THOROUGHLY WITH SOAP

RTECS: 9999999ZZ

CALCIUM CARBONATE

CAS: 1317-65-3

RTECS: EV9580000

Fraction By Weight: 5-10%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST

CARBON BLACK

CAS: 1333-86-4

RTECS: FF5800000

Fraction By Weight: 5%

OSHA PEL3.5 MG/M3

ACGIH TLV: 3.5 MG/M3

CHROMIUM (SARA III)

CAS: 7440-47-3

RTECS: GB4200000

Fraction By Weight: < 5%

OSHA PEL1 MG/M3

ACGIH TLV: 0.5 MG/M3

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

SILICA, CRYSTALLINE - QUARTZ

CAS: 14808-60-7

RTECS: VV7330000

Fraction By Weight: < 5%

OSHA PEL10 MG/M3 RDUST

ACGIH TLV: 0.1 MG/M3 RDUST

SILICA, CRYSTALLINE - CRISTOBALITE

CAS: 14464-46-1

RTECS: VV7325000

Fraction By Weight: < 5%

OSHA PELSEE TABLE

ACGIH TLV: 0.05 MG/M3 RDUST

SILICIC ACID, TETRAETHYL ESTER; (ETHYL SILICATE)

CAS: 78-10-4

RTECS: VV9450000

Fraction By Weight: < 5%

OSHA PEL100 PPM

ACGIH TLV: 10 PPM

SILICATE, MICA; (MICA (MINERAL))

CAS: 12001-26-2

RTECS: VV8760000

Fraction By Weight: < 5%

OSHA PEL20 MPPCF; Z-3

ACGIH TLV: 3 MG/M3 RDUST

MINERAL SPIRITS (F)

CAS: 64742-88-7

Fraction By Weight: 40%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM

MINERAL SPIRITS (G)

CAS: 64742-88-7

Fraction By Weight: 5%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM

MINERAL SPIRITS; (ODORLESS MINERAL SPIRITS)

CAS: 64742-88-7

Fraction By Weight: 10%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM

MINERAL SPIRITS; (PETROLEUM NAPHTHA (H))

CAS: 64742-88-7

Fraction By Weight: 5%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM

SILICON DIOXIDE, AMORPHOUS

CAS: 112945-52-5

RTECS: VV7310000

Fraction By Weight: < 5%

OSHA PELN/K

ACGIH TLV: N/K

TALC (POWDER), CONTAINING NO ASBESTOS FIBERS; (TALC)

CAS: 14807-96-6

RTECS: WW2710000

Fraction By Weight: 5%

OSHA PEL2 MG/M3 RDUST

ACGIH TLV: 2 MG/M2 RDUST

TITANIUM OXIDE; (TITANIUM DIOXIDE)

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: 15%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST

XYLENE (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: < 5%

OSHA PEL100 PPM

ACGIH TLV: 100 PPM;150 STEL

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

ZINC OXIDE

CAS: 1314-13-2

RTECS: ZH4810000

Fraction By Weight: < 5%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10MG/M3 TDUST

250-440 G/L

RTECS: 9999999VO

OSHA PELN/K

ACGIH TLV: N/K

BENZENE (SARA III)

CAS: 71-43-2

RTECS: CY1400000

Fraction By Weight:

OSHA PELN/K

ACGIH TLV: 10 PPM

EPA Report Quantity: 10 LBS

DOT Report Quantity: 10 LBS

GRP2.

RTECS: 9999999ZZ

CAUSE DMG TO KID/LIV/LUNGS/BLOOD CELLS,

RTECS: 9999999ZZ

ALUMINUM (SARA III)

CAS: 7429-90-5

RTECS: BD0330000

Fraction By Weight: 5%

OSHA PEL15MG/M3 DUST;5 FUME

ACGIH TLV: 10MG/M3 DUST

SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC; (AROMATIC

CAS: 64742-95-6

RTECS: WF3400000

Fraction By Weight: < 5%

OSHA PELN/K

ACGIH TLV: 100 PPM

BARIUM SULFATE (DUST)

CAS: 7727-43-7

RTECS: CR0600000

Fraction By Weight:

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO

Health Hazards Acute and Chronic:ACUTE:INGEST:CAUSES IRRIT TO MOUTH, THROAT & GI TRACT W/ACUTE CNS DEPRESS. SYMPS MAY INCL HDCH, DIZZ, CONFUSION, NAUS, VOMIT, ABDOM PAIN, DIARR, UNCON/COMA.INHAL:ANESTHETIC. IRRIT OF RESP TRACT & ACUT E NERV SYS DEPRESS CHARAC BY THE FOLLOWING PROGRESSIVE STEPS:HDCH, DIZZ, STAG GAIT, CONFUSION, UNCON OR(EFTS OF OVEREXP)

Explanation of Carcinogenicity:CHROMIUM: IARC MONOGRAPHS, VOL 49,PG 49, 1990: GRP 1. NTP: ANNUAL REPORT ON CARCIN, 1991: KNOWN TO BE CARCIN.(SUPP DATA)

Effects of Overexposure:HLTH HAZ:COMA. EYE:CAN CAUSE SEV IRRIT & BLURRED VISION. SKIN:CAUSES IRRIT. PRLNG/RPTD CNTCT MAY RSLT IN DERM. CHRONIC:REPORTS HAVE ASSOC PRLNGD & RPTD OCCUP OVEREXP TO SOLVS W/PERM BRAIN & CNS DMG. I NTENTIONAL MISUSE BY DELIB CONC & INHALCONTENTS MAY BE HARMFUL/FATAL. CHRONIC EXPOS TO SOLVS HAS BEEN SHOWN TO (ING 23)

Medical Cond Aggravated by Exposure:ING 4:BIO EXPOS INDICES INCL PHENOL IN URINE & BENZENE IN EXHALER AIR. ING 8:EXISTING LUNG DISEASES; A LUNG TOXIN. ING 19: BIO EXPOS INDICES INCL METHYLHIPURIC ACIDS IN URINE.

First Aid

First Aid:INGEST:DRINK 1-2 GLASSES OF H*2O TO DILUTE. KEEP PERSON WARM, QUIET & GET MED ATTN IMMED. DECISION TO INDUCE VOMIT MUST BE BASED ON ADVICE OF A MD/POIS CTL CTR. NEVER GIVE ANYTHING BY MOUTH TO AN UNCO N PERSON. INHAL:REMOVE TO FRESH AIR. RESTORE BRTHG. CONSULT MD. EYE:IMMED FLUSH W/COOL H*2O FOR @ LST 15 MIN, OCCSNLY LIFTING LIDS TO ENSURE THORO RINSING. SEND FOR ASSISTANCE. SKIN: WIPE OFF(ING 24)

Fire Fighting

Flash Point:105F,41C
Lower Limits:1.0%
Extinguishing Media:FOAM, CO*2, DRY CHEMICAL, WATER FOG.
Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA & FULL PROT EQUIP
. WATER MAY BE USED TO COOL CLSD CNTNRS TO PVNT PRESS BUILD-UP &
POSS AUTOIGNIT/EXPLO WHEN (SUPP DATA)
Unusual Fire/Explosion Hazard:KEEP CNTNRS TIGHTLY CLSD. ISOLATE FROM
HEAT/SPARKS/FLAME/ELEC EQUIP. CLSD CNTNRS MAY EXPLODE WHEN EXPOSED
TO EXTREME HEAT. APPLIC TO HOT SUFS (SUPP DATA)

Accidental Release

Spill Release Procedures:REMOVE SOURCES OF IGNITION. SOAK UP AND REMOVE
WITH INERT ABSORBENT MATERIAL WITH NON-SPARKING TOOLS. PROVIDE
ADEQUATE VENTILATION. USE APPROVED VAPOR RESPIRATOR.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:STORE UPRIGHT IN SEALED CONTAINERS AND
USE AWAY FROM HIGH TEMPS, SPARKS AND FLAME. AVOID PROLONGED CONTACT
WITH SKIN.
Other Precautions:DO NOT INGEST. KEEP CONTAINER TIGHTLY SEALED WHEN NOT
IN USE. KEEP OUT OF REACH OF CHILDREN.

Exposure Controls

Respiratory Protection:NIOSH/MSHA APPRVD PROPERLY FITTED MECH RESP OR
MASK TO AVOID BRTHG VAP/SPRAY MIST DURING MIXING, SPRAYING,
APPLICATION OR CURING. NIOSH/MSHA APPRVD PROPERLY FITTED POSITIVE
AIR SUPPLIED RESP IN CONFIN ED AREAS OR WHEN OVERSPRAY IS PRESENT.
Ventilation:SUFFICIENT VENT IN VOL & PATTERN TO KEEP AIR CONTAM CONC
BELOW APPLIC OSHA PERMISSIBLE EXPOS LEVEL/ACGIH'S TLV (ING 25)
Protective Gloves:IMPERVIOUS GLOVES .
Eye Protection:ANSI APPROVD CHEM WORKER GOGGLES .
Other Protective Equipment:PROTECTIVE OVERALLS RECOMMENDED. REMOVE AND
WASH CONTAM CLTHG. DISCARD CONTAM SHOES.
Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.
Supplemental Safety and Health
MFR TRADE NAME/PART NO: BASED ARCHITECTURAL COATING. FIRE FIGHT
PROC:EXPSD TO EXTREME HEAT. EXPLO HAZ:REQUIRES SPECIAL PRECS.
DURING EMER CNDTNS, OVEREXP TO DECOMP PRODS MAY CAUSE HLTH HAZ.
OBTAIN MED ATTN. EXPLAN OF CARCIN: HUMAN/ANIMAL: LUNG CANCER,
SKIN. SILICA, CRYSTALLINE-(QUARTZ,CRISTOBALITE): IARC (ING 22)

Chemical Properties

Boiling Pt:B.P. Text:>241F,>116C
Vapor Density:HVR/AIR
Spec Gravity:1.3
Evaporation Rate & Reference:SLOWER THAN ETHER
Appearance and Odor:NONE SPECIFIED BY MANUFACTURER.
Percent Volatiles by Volume:60

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS, ACIDS, BASES
Stability Condition to Avoid:HIGH TEMPERATURE.
Hazardous Decomposition Products:MAY PRODUCE FUMES WHEN HEATED TO
DECOMPOSITION. FUMES MAY CONTAIN CO, CO*2, AND NO*2.

Disposal

Waste Disposal Methods:DISPOSE IN SEALED METAL CONTAINER AWAY FROM HEAT
AND FLAME IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.
DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.