

TOUCHDOWN #720 CARPET PAD ADHESIVE

MSDS Number

BVGDD

National Stock Number

8040-00N050348

Product Name

TOUCHDOWN #720 CARPET PAD ADHESIVE

Manufacturer

W F TAYLOR CO INC

Product Identification

Product ID:TOUCHDOWN #720 CARPET PAD ADHESIVE MSDS Date:10/07/1988 FSC:8040 NIIN:00N050348

MSDS Number: BVGDD **Responsible Party**

W F TAYLOR CO INC

13660 EXCELSIOR DR

SANTA FE SPRINGS, CA 90670

US

Emergency Phone: 213-802-1896

Info Phone: 213-802-1896

Cage: HO551

Contractor

W F TAYLOR CO INC

SANTA FE SPRINGS, CA 90670

213-802-1896

US

Cage: HO551

Ingredients

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC; (PETROLEUM

CAS: 64742-89-8

Fraction By Weight: 50%

OSHA PEL500 PPM ACGIH TLV: 500 PPM

403 G/L

RTECS: 9999999VO

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: MAY LEAD TO HEADACHE, SKIN RASH
AND CENTRAL NERVOUS SYSTEM DEPRESSION. CHRONIC: MAY CAUSE NARCOSIS,
UNCONSCIOUSNESS FROM INHALATION. MAY CAUSE DERMATITIS FROM CHRONIC



SKIN CONTACT.

Explanation of Carcinogenicity: NOT RELEVANT

Effects of Overexposure: INHAL: MAY CAUSE NAUSEA, DROWSINESS OR

IRRITATION OF MUCOUS MEMBRANE. EYE: VAPOR MAY CAUSE EYE IRRITATION.

SKIN: MAY CAUSE SKIN IRRITATION AND RASH. INGEST: MAY CAUSE

VOMITING. SYMPTOMS MAY BE SAME AS INHALATION. Medical Cond Aggravated by Exposure: NONE KNOWN.

First Aid

First Aid: EYE: WASH WITH WATER FOR AT LEAST 15 MIN. IF IRRIT PERSISTS, SEEK MED ATTN. SKIN: REMOVE FROM SKIN AND APPLY SKIN CREAM. IF IRRIT PERSIST, SEEK MEDICAL ATTENTION. INHAL: REMOVE TO FRESH AIR, ADMIN OXY GEN AND IF NECESSARY, SEEK MED ATTN. INGEST: SEEK MED ATTN. DO NOT INDUCE VOMITING, THIS COULD CAUSE CHEMICAL PNEUMONITIS. NOTE TO MD: DETERMINE IF EMESIS SHOULD BE INDUCED.

Fire Fighting

Flash Point Method:TCC Flash Point:0F,-18C Lower Limits:1% Upper Limits:7%

Extinguishing Media:WATER SPRAY, FOAM, CARBON DIOXIDE, DRY CHEMICAL. Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT. WATER MAY SPREAD BURNING LIQUID. AVOID

DIRECT STREAM OF WATER.

Unusual Fire/Explosion Hazard: DO NOT EXPOSE TO EXCESSIVE HEAT.

Accidental Release

Spill Release Procedures: MATL IS FLAMM, ELIM SOURCES OF IGNITION. FOR LRG SPILLS, EVAC AREA. DIKE & CONTAIN MATL. STOP LEAK, IF POSSIBLE. USE WATER FOG TO SUPPRESS VAPOR CLOUD. USE CLAY OR SAND TO SOAK UP MATL. PLACE MATL IN NON-LEAKING CNTNR. CAP TIGHTLY. Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions: PROTECT AGAINST PHYSICAL DAMAGE. STORE IN A COOL PLACE. KEEP AWAY FROM HEAT AND SPARKS.

Other Precautions: NO SMOKING, AVOID SPARKS & FLAME. USE NIOSH/MSHA APPROVED RESPIRATOR, UNLESS EXPOSURE IS KNOWN TO BE BELOW TLV. KEEP OUT OF REACH OF CHILDREN. AVOID BREATHING BUILDUP OF VAPORS.

Exposure Controls

Respiratory Protection: NONE REQUIRED, LESS EXPOSURE IS OVER TLV. USE NIOSH/MSHA APPROVED RESPIRATOR.

Ventilation: USE LOCAL EXHAUST. DO NOT USE CLOSED AIR CIRCULATING SYSTEM. OPEN WINDOWS AND DOORS, IF NECESSARY.

Protective Gloves: ACRYLONITRILE GLOVES.

Eye Protection: ANSI APPRVD CHEM WORKER GOGGLES .

Other Protective Equipment:IF CLOTHING BECOMES CONTAMINATED, REMOVE AND CLEAN BEFORE REWEARING.

Work Hygienic Practices: FOLLOW ALL LABEL INSTRUCTIONS.

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

Chemical Properties

Boiling Pt:B.P. Text:142F,61C

Vapor Density:> 1 Spec Gravity:0.8-1.0

Evaporation Rate & Reference:9 (N. B. ACETATE=1)

Solubility in Water:NIL

Appearance and Odor: THIN SYRUP, AMBER COLOR, MILD ODOR.

Stability

Stability Indicator/Materials to Avoid:YES NONE KNOWN.

Stability Condition to Avoid: EXCESSIVE HEAT, OPEN FLAME OR SPRAKS. Hazardous Decomposition Products: CO, CO*2 AND OTHER UNIDENTIFIED



ORGANIC COMPOUNDS.

Disposal

Waste Disposal Methods: DISPOSE OF ALL WASTES IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.