

TOUCHDOWN 1 CONTACT CEMENT LOW FLASH

MSDS Number

BVLHJ

National Stock Number

8040-00N051798

Product Name

TOUCHDOWN 1 CONTACT CEMENT LOW FLASH

Manufacturer

W F TAYLOR CO INC

Product Identification

Product ID:TOUCHDOWN 1 CONTACT CEMENT LOW FLASH

MSDS Date:09/29/1988

FSC:8040

NIIN:00N051798

MSDS Number: BVLHJ

Responsible Party

W F TAYLOR CO INC

13660 EXCELSIOR DR

SANTA FE SPRINGS , CA 90670

US

Emergency Phone: 213-802-1896

Info Phone: 213-802-1896

Cage: HO551

Contractor

W F TAYLOR CO INC

SANTA FE SPRINGS, CA 90670

US

213-802-1896

Cage: HO551

Ingredients

NO INGREDIENT FOR THIS FORMULATION_INGREDIENT

Fire Fighting

Flash Point Method:TCC

Flash Point:0F,-18C

Lower Limits:1%

Upper Limits:7%

Extinguishing Media:WATER SPRAY, FOAM, CARBON DIOXIDE, DRY CHEMICAL.

Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT . WATER MAY SPREAD BURNING LIQUID. AVOID STREAM OF WATER.

Unusual Fire/Explosion Hazard:DO NOT EXPOSE TO EXCESSIVE HEAT, OPEN FLAME OR SPARKS. TURN OFF ALL PILOT LIGHTS.

Exposure Controls

Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:142F,61C

Vapor Density:>1

Spec Gravity:0.8-1

Evaporation Rate & Reference:>1 (N-BUTYL ACETATE=1)
Solubility in Water:NIL
Appearance and Odor:GREEN OR CLEAR COLOR, THIN SYRUP CONSISTENCY; MILD ODOR.

Stability

Stability Indicator/Materials to Avoid:YES
NONE KNOWN.
Stability Condition to Avoid:EXCESSIVE HEAT, OPEN FLAMES OR SPARKS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.