

## **U-1083 NON-GLAR BLACK**

### **MSDS Number**

BVTKL

### **National Stock Number**

8010-00F037237

### **Product Name**

U-1083 NON-GLAR BLACK

### **Manufacturer**

STERLING LACQUER MFG CO

### **Product Identification**

Product ID:U-1083 NON-GLAR BLACK

MSDS Date:06/01/1993

FSC:8010

NIIN:00F037237

MSDS Number: BVTKL

### **Responsible Party**

STERLING LACQUER MFG CO

3150 BRANNON AVE

ST. LOUIS , MO 63139-1422

US

Emergency Phone: 314-776-4450

Info Phone: 314-776-4450

Preparer: P D MOORE

Cage: 60003

### **Contractor**

STERLING LACQUER MFG CO

ST. LOUIS, MO 63139-1422

US

314-776-4450

Cage: 60003

### **Ingredients**

PROPYLENEGLYCOL MONOMETHYL ETHER ACETATE,

CAS: 108-65-6

RTECS: AI8925000

Fraction By Weight: 20%

2-BUTANONE (METHYL ETHYL KETONE) (MEK)

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight: 15%

OSHA PEL200 PPM

ACGIH TLV: 200 PPM

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

TOLUENE (IARC - GROUP 3) \*94-3\*

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 4%

OSHA PEL200 PPM

ACGIH TLV: 100 PPM

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

ETHYL ACETATE

CAS: 141-78-6

RTECS: AH5425000

Fraction By Weight: 10%

OSHA PEL1400 MG/CUM

ACGIH TLV: 400 PPM

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

XYLENE, DIMETHYLBENZENE, XYLOL

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 2%

OSHA PEL100 PPM

ACGIH TLV: 100 PPM, SKIN

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

COLUMBIA CARBON, CARBON BLACK, LAMPBLACK, BLACK PEARLS

CAS: 1333-86-4

RTECS: FF5800000

Fraction By Weight:

OSHA PEL3.5 MG/CUM

ACGIH TLV: 3.5 MG/CUM

590 G/L

RTECS: 9999999VO

## Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: IRRITATION TO RESPIRATORY TRACT, NOSE, THROAT, LUNGS & SILICOSIS. EYES: IRRITATING & MAY

INJURE TISSUE. SKIN: SLIGHT IRRITATION. INGESTION: MODERATLY TOXIC.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:IRRITATION, NARCOSIS, NAUSEA, VOMITING, DIARRHEA.

Medical Cond Aggravated by Exposure:RESPIRATORY PROBLEMS

## First Aid

First Aid:EYES: FLUSH W/WATER FOR 15 MINS. SKIN: WASH AFFECTED AREA W/SOAP & WATER. INHALATION: MOVE TO FRESH AIR. INGESTION: DON'T INDUCE VOMITING. OBTAIN MEDICAL ATTENTION IN ALL CASES.

## Fire Fighting

Flash Point Method:TCC

Flash Point:21F

Lower Limits:1.1

Upper Limits:13.1

Extinguishing Media:FOAM, CO2, DRY CHEMICAL

Fire Fighting Procedures:WEAR SCBA W/A FULL FACEPIECE OPERATED IN PRESSURE-DEMAND. USE WATER FOG NOZZLES TO COOL CLOSED CONTAINER. DON'T USE WATER.

Unusual Fire/Explosion Hazard:FLAMMABLE LIQUID CAN RELEASE VAPORS THAT FORM FLAMMABLE MIXTURES AT/ABOVE 21F.

## Accidental Release

Spill Release Procedures:WEAR RESPIRATOR, ABSORB W/VERMICULITE/OTHER ABSORBENT MATERIAL. ELIMINATE ALL IGNITION SOURCES. STOP SPILL AT SOURCE & PREVENT SPREADING.

## Handling

Handling and Storage Precautions:STORE IN DRY AREA. KEEP CONTAINERS TIGHTLY CLOSED. PROTECT FROM PHYSICAL DAMAGE. STORE BELOW 120F. FOR INDUSTRIAL USE ONLY.

Other Precautions:KEEP CONTAINERS TIGHTLY CLOSED/UPRIGHT TO PREVENT LEAKAGE. DON'T STORE NEAR HEAT, SPARKS/FLAME. DON'T GET INTO EYES. KEEP AWAY FROM CHILDREN. AVOID CONTACT. DON'T TAKE INTERNALLY.

## Exposure Controls

Respiratory Protection:WEAR A NIOSH/MSHA JOINTLY APPROVED AIR SUPPLY RESPIRATOR IF TLV OF THE PRODUCT/ANY COMPONENT IS EXCEEDED.

Ventilation:SUFFICIENT MECHANICAL (GENERAL &/LOCAL EXHAUST) TO MAINTAIN EXPOSURE BELOW TLV.

Protective Gloves:SOLVENT RESISTANT

Eye Protection:CHEMICAL SPLASH GOGGLES

Other Protective Equipment:SOLVENT IMPERVIOUS CLOTHING & BOOTS.

Work Hygienic Practices:WASH W/SOAP & WATER AFTER USE, BEFORE EATING/SMOKING. REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

## Chemical Properties

Boiling Pt:B.P. Text:167-302F

Vapor Density:>1

Spec Gravity:1.2

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:NEGLIGIBLE

Appearance and Odor:BLACK LIQUID W/SOLVENT ODOR

## Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:EXCESSIVE HEAT, SPARKS, FLAME, OTHER IGNITION SOURCES.

Hazardous Decomposition Products:CO2, CO, TOXIC GASES

## Disposal

Waste Disposal Methods:DESTROY BY LIQUID INCINERATION. CONTAMINATED ABSORBENT MAY BE DEPOSITED IN A LANDFILL IAW/FEDERAL, STATE & LOCAL REGULATIONS. EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.