

# H-100

# **MSDS Number**

**BVWLV** 

### **National Stock Number**

4130-00N054272

### **Product Name**

H-100

#### Manufacturer

ALCO CONTROLS

### **Product Identification**

Product ID:H-100 MSDS Date:11/12/1993 FSC:4130 NIIN:00N054272 MSDS Number: BVWLV

# **Responsible Party**

ALCO CONTROLS

SAINT LOUIS , MO 63141-1400

US

Emergency Phone: 314-569-4500

Info Phone: 314-569-4500

Cage: IO896

Contractor

ALCO CONTROLS DIV, EMERSON ELECTRIC CO

MARYLAND HEIGHTS, MO 63043-3215

US

314-569-4109 Cage: 70255

# **Ingredients**

SODIUM OXIDE CAS: 1313-59-3 Fraction By Weight:

ACGIH TLV: N/K

OSHA PELN/K

POTASSIUM OXIDE (MFR CAS# 12136-45-7)

CAS: 12030-89-6 RTECS: TT3790000 Fraction By Weight: OSHA PELN/K

ACGIH TLV: N/K



CAS: 1309-48-4 RTECS: OM3850000 Fraction By Weight:

OSHA PEL10 MG/M3 PARTICULATE ACGIH TLV: 10 MG/M3, FUME

ALUMINUM OXIDE CAS: 1344-28-1 RTECS: BD1200000 Fraction By Weight: OSHA PEL10 MG/M3

ACGIH TLV: 10 MG/M3

SILICA OXIDE

CAS: 112945-52-5 RTECS: VV7310000 Fraction By Weight: OSHA PEL6 MG/M3 ACGIH TLV: 10 MG/M3

### Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE:INGEST: NO EVIDENCE OF ADVERSE EFTS FROM AVAIL INFO. SKIN ABSORB:NO EVIDENCE OF ADVERSE EFTS FROM AVAILABLE INFORMATION. INHAL: MAY CAUSE IRRITATION OF THE NOSE AND THROAT, ACCOMPANIED BY COUGH A ND CHEST DISCOMFORT. SKIN: MAY CAUSE IRRITATION SEEN AS LOCAL REDNESS AND/OR BURNS. (EFTS OF OVEREXP) Explanation of Carcinogenicity: NOT RELEVANT Effects of Overexposure: HLTH HAZ: EYE: MAY CAUSE IRRITATION SEEN AS LOCAL REDNESS OF THE CONJUNCTIVA AND/OR BURNS. CHRONIC:PROLONGED INHALATION MAY CAUSE LUNG DAMAGE. Medical Cond Aggravated by Exposure: BREATHING OF DUST MAY AGGRAVATE ASTHMA AND INFLAMMATORY OR FIBROTIC PULMONARY DISEASE.

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.

#### First Aid

First Aid:INGEST:IF INGESTED LG QTYS, THEN DRINK 2 GLASSES OF WATER. INDUCE VOMITING IF THE PATIENT IS CONSCIOUS. SKIN: WASH THE CONTACTED AREA WITH SOAP AND WATER. INHAL:REMOVE THE PERSON TO FRESH AIR. EYE CONT ACT: IMMEDIATELY FLUSH EYES WITH WATER FOR AT LEAST 15 MINUTES.

#### Fire Fighting

Flash Point: DOES NOT BURN

Extinguishing Media: UNUSED MATERIAL WILL NOT BURN. USE EXTINGUISHING MEDIA SUITABLE FOR SURROUNDING FIRE.

Fire Fighting Procedures: NIOSH/MSHA APPRVD SCBA & FULL PROT EQUIP. DEPENDS ON USE OF MATL. USER OF PROD MUST IDENTIFY HAZ OF RETAINED MATL & INFORM FIRE FIGHTERS OF THESE HAZARDS.

Unusual Fire/Explosion Hazard: IN THEIR FRESH STATE DRIERS ARE NOT FLAMM. HOWEVER, USED HERMETIC DRIERS MAY CONTAIN REFRIGERANT UNDER HIGH PRESS. PREC MUST BE TAKEN TO AVOID PRESS RELEASES.

### **Accidental Release**

Spill Release Procedures: SWEEP THE SPILL AREA. COLLECT AND PLACE THE



SPILLED MATERIAL IN A WASTE DISPOSAL CONTAINER. Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

# Handling

Handling and Storage Precautions: NONE SPECIFIED BY MANUFACTURER. Other Precautions: NONE SPECIFIED BY MANUFACTURER.

### **Exposure Controls**

Respiratory Protection: A NIOSH/MSHA APPROVED RESPIRATOR FOR PROTECTION AGAINST DUST, MIST OR VAPOR IS RECOMMENDED FOR OPERATIONS WHEN THE PERMISSIBLE EXPOSURE LIMIT MIGHT BE EXCEEDED.

Ventilation: LOCAL EXHAUST VENT IS REC FOR OPERATIONS WHERE THE

PERMISSIBLE EXPOSURE LIMIT MIGHT BY EXCEEDED.

Protective Gloves: IMPERVIOUS GLOVES .

Eve Protection: ANSI APPRVD CHEM WORKERS GOGGLES .

Other Protective Equipment: SELECT IN ACCORDANCE WITH OSHA 1910.132 AND 1910.133.

Work Hygienic Practices: NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

HAZ DECOMP PROD: THESE RETAINED MATERIALS OF USE. THE DRIERS THEMSELVES DO NOT READILY DECOMPOSE UNLESS SUBJECTED TO EXTREME TEMPS OR CHEMICAL CONDITIONS. IF SUCH DECOMP DID OCCUR THE PRODUCTS WOULD IN CLUDE THE MIX OF OXIDES LISTED IN ING SECTION.

## **Chemical Properties**

HCC:V7

Appearance and Odor: PRODUCT MAY APPEAR AS BLOCK STYLE OR IN HERMETIC SHELL.

# **Stability**

Stability Indicator/Materials to Avoid:YES SUDDEN CONTACT WITH STRONG ACIDS SUCH AS HYDROCHLORIC ACID AND NITRIC ACID.

Stability Condition to Avoid: USED HERMETIC DRIERS CAN CONTAIN REFRIGERANT UNDER PRESSURE. REMOVE SEALING CAPS SLOWLY ON RESEALED DRIERS

Hazardous Decomposition Products:IT IS POSS THAT OILS CAN BE RETAINED IN DRIER. IT IS REASONABLE TO EXPECT THAT DECOMP PRODS WILL COME FROM (SUPP DATA)

## **Disposal**

Waste Disposal Methods: DISCARD ANY PRODUCT (INCLUDING ANY RETAINED MATERIALS OF USE), DISPOSABLE CONTAINER OR LINER IN AN ENVIRONMENTALLY ACCEPTABLE MANNER, IN FULL COMPLIANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.