

## **"B'LASTER" 404-AIR TOOL OIL & CONDITIONER**

### **MSDS Number**

BWFTZ

### **National Stock Number**

9150-00N056140

### **Product Name**

"B'LASTER" 404-AIR TOOL OIL & CONDITIONER

### **Manufacturer**

WILLIAM K WESTLEY CO

### **Product Identification**

Product ID:"B'LASTER" 404-AIR TOOL OIL & CONDITIONER

MSDS Date:07/17/1992

FSC:9150

NIIN:00N056140

MSDS Number: BWFTZ

### **Responsible Party**

WILLIAM K WESTLEY CO

9545 MIDWEST AVE STE D

GARFIELD HTS , OH 44125

US

Emergency Phone: 800-858-6605

Info Phone: 216-587-0011

Cage: 0BNB4

### **Contractor**

WILLIAM K WESTLEY CO

GARFIELD HTS, OH 44125

US

216-587-0011

Cage: 0BNB4

### **Ingredients**

VM&P NAPHTHA; (PETROLEUM DISTILLATE)

CAS: 64742-48-9

Fraction By Weight:

OSHA PEL300 PPM (MFR)

ACGIH TLV: 300 PPM (MFR)

ISOPROPYL ALCOHOL; (ISO ALCOHOL) (SARA III)

CAS: 67-63-0

RTECS: NT8050000

Fraction By Weight: 15%

OSHA PEL400 PPM

ACGIH TLV: 400 PPM;500 STEL

FLUID-AP; (MIX-POLYALKYLENE GLYCOL)

CAS: 9003-13-8

RTECS: LL3130000

Fraction By Weight:

OSHA PELN/K

ACGIH TLV: N/K

PHOSHORDITHIOIC ACID, ZINC SALT; (ZINC DITHIOPHOSPHATE)

CAS: 19210-06-1

RTECS: TE4800000

Fraction By Weight:

OSHA PEL5 MG/PCM (MFR)

ACGIH TLV: 5 MG/PCM (MFR)

ANILINE; (AMINOBENZENE) (SARA III)

CAS: 62-53-3

RTECS: BW6650000

Fraction By Weight:

OSHA PEL5 PPM, S

ACGIH TLV: 2 PPM, S

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

CRESYLIC BLEND

Fraction By Weight:

OSHA PEL5 PPM (MFR)

ACGIH TLV: 5 PPM (MFR)

43.7%.

RTECS: 9999999VO

## Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ING 1:SKIN:PROLONGED OR REPEATED CONTACT W/THIS PRODUCT TENDS TO REMOVE SKIN OILS POSSIBLY LEADING TO IRRITATION & DERMATITIS. EYE:PRODUCT CONTACTING EYES MAY CAUSE IRRITATION. ING 2:INHAL:PROLONGED O VEREXPOSURE MAY CAUSE COUGHING, SHORTNESS OF BREATH, DIZZINESS & INTOXICATION. EYE CONTACT:MAY CAUSE (EFTS OF OVEREXP)

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:HLTH HAZ:MODERATE IRRITATION, INCLUDING BURNING SENSATION, TEARING, REDNESS OR SWELLING.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

## First Aid

First Aid:INGEST:CALL MD IMMEDIATELY . SKIN:WASH W/SOAP & WATER, EMOLLIENT CREAM IS BENEFICIAL. EYE:FLUSH W/WATER FOR AT LEAST 15

MINUTES. INHAL:PROVIDE W/FRESH AIR & REST. CONSULT MD IF NECESSARY.

## Fire Fighting

Flash Point Method:OC

Flash Point:65.0F,18.3C

Extinguishing Media:MECHANICAL FOAM, DRY CHEMICAL, WATER FOG, CO\*2.

Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT .

Unusual Fire/Explosion Hazard:NONE.

## Accidental Release

Spill Release Procedures:AVOID OPEN FLAME. PROVIDE ADEQUATE VENTILATION. COLLECT & DISPOSE OF ALL SPILLED LIQUID.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

## Handling

Handling and Storage Precautions:STORE AWAY FROM OPEN FLAME & EXTREME HEAT.

Other Precautions:AVOID EYE CONTACT.

## Exposure Controls

Respiratory Protection:IN INADEQUATELY VENTILATED AREAS - USE NIOSH/MHSA APPROVED SELF-CONTAINED BREATHING APPARATUS.

Ventilation:LOCAL EXHAUST: TO A SAFE AREA.

Protective Gloves:IMPERVIOUS GLOVES .

Eye Protection:ANSI APPROVED CHEM WORKERS GOGGS .

Other Protective Equipment:ANSI APPROVED EYE BATH & SAFETY SHOWERS .

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

## Chemical Properties

Boiling Pt:B.P. Text:180F,82C

Melt/Freeze Pt:M.P/F.P Text:28.0F,-2.2C

Vapor Pres:0.03

Vapor Density:2.8

Spec Gravity:0.84 (H\*2O=1)

pH:5.5

Evaporation Rate & Reference:0.1 (BUTYL ACETATE=1)

Solubility in Water:10%

Appearance and Odor:RED, CLEAR COLOR; NON-IRRITATING ODOR.

## Stability

Stability Indicator/Materials to Avoid:YES

NONE SPECIFIED BY MANUFACTURER.

Stability Condition to Avoid:NONE CURRENTLY KNOWN.

Hazardous Decomposition Products:NONE SPECIFIED BY MANUFACTURER.

## Disposal

Waste Disposal Methods:DISPOSAL MUST BE I/A/W FEDERAL, STATE & LOCAL REGULATIONS . COLLECT & DISPOSE OF THE SAME AS FOR OIL OR ALIPHATIC SOLVENTS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.