

"B'LASTER" DIESEL INJECTOR CLEANER

MSDS Number

BWFWL

National Stock Number

6850-00N056258

Product Name

"B'LASTER" DIESEL INJECTOR CLEANER

Manufacturer

WILLIAM K WESTLEY CO

Product Identification

Product ID: "B'LASTER" DIESEL INJECTOR CLEANER

MSDS Date: 07/17/1992

FSC: 6850

NIIN: 00N056258

MSDS Number: BWFWL

Responsible Party

WILLIAM K WESTLEY CO

9545 MIDWEST AVE STE D

GARFIELD HTS , OH 44125

US

Emergency Phone: 216-587-0011

Info Phone: 216-587-0011

Cage: 0BNB4

Contractor

WILLIAM K WESTLEY CO

GARFIELD HTS, OH 44125

US

216-587-0011

Cage: 0BNB4

Ingredients

MINERAL SPIRITS; (PETROLEUM DISTILLATE)

CAS: 64475-85-0

RTECS: PY8240000

Fraction By Weight:

OSHA PEL300 PPM MFR

ACGIH TLV: 300 PPM MFR

ISOPROPYL ALCOHOL (SARA III)

CAS: 67-63-0

RTECS: NT8050000

Fraction By Weight:

OSHA PEL400 PPM

ACGIH TLV: 400 PPM

FLUID-AP; (MIX-POLYALKYLENE GLYCOL)

CAS: 9003-13-8

RTECS: LL3130000

Fraction By Weight:

OSHA PELN/K

ACGIH TLV: N/K

PHOSPHORODITHIOIC ACID, ZINC SALT; (ZINC DITHIOPHOSPHATE)

CAS: 19210-06-1

RTECS: TE4800000

Fraction By Weight:

OSHA PEL5 MG/PCM

ACGIH TLV: 5 MG/PCM (MFR)

ANILINE; (AMINOBENZENE) (SARA III)

CAS: 62-53-3

RTECS: BW6650000

Fraction By Weight:

OSHA PELS, 5 PPM

ACGIH TLV: S, 2 PPM

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

CRESYLIC BLEND

Fraction By Weight:

OSHA PEL5 PPM

ACGIH TLV: 5 PPM

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PETROLEUM DISTILLATE:SKIN:PROLONGED OR REPEATED CONTACT WITH THIS PRODUCT TENDS TO REMOVE SKIN OILS

POSSIBLY LEADING TO IRRITATION AND DERMATITIS. EYE:PRODUCT

CONTACTING THE EYES MAY CAUSE IRRIT. ISOP ROPYL

ALCOHOL:INHAL:PROLONGED OVEREXPOSURE MAY CAUSE COUGHING, SHORTNESS OF BREATH, DIZZINESS & (EFTS OF OVEREXP)

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:HLTH HAZS:INTOXICATION. EYE:MAY CAUSE MODERATE IRRITATION, INCLUDING BURNING SENSATION, TEARING, REDNESS OR SWELLING.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid

First Aid:INGEST:CALL MD IMMEDIATELY . SKIN:WASH WITH SOAP AND WATER, EMOLLIENT CREAM IS BENEFICIAL. EYES:FLUSH WITH WATER FOR AT LEAST 15 MINUTES. INHAL:PROVIDE WITH FRESH AIR AND REST. CONSULT PHYSICIAN IF NECESSARY.

Fire Fighting

Flash Point Method:OC
Flash Point:65.0F,18.3C
Extinguishing Media:MECHANICAL FOAM, DRY CHEMICAL, WATER FOG, CO*2.
Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT .
Unusual Fire/Explosion Hazard:NONE

Accidental Release

Spill Release Procedures:AVOID OPEN FLAME. PROVIDE ADEQUATE VENTILATION. COLLECT AND DISPOSE OF ALL SPILLED LIQUID.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:STORE AWAY FROM OPEN FLAME AND EXTREME HEAT.
Other Precautions:NONE SPECIFIED BY MANUFACTURER.

Exposure Controls

Respiratory Protection:IN INADEQUATELY VENTILATED AREAS - USE NIOSH/MSHA APPROVED SELF-CONTAINED BREATHING APPARATUS.
Ventilation:LOCAL EXHAUST TO A FIRE SAFE AREA.
Protective Gloves:IMPERVIOUS GLOVES .
Eye Protection:ANSI APPRVD CHEM WORKERS GOGGLES .
Other Protective Equipment:EYE BATH AND SAFETY SHOWERS.
Work Hygienic Practices:AVOID EYE CONTACT.
Supplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

Chemical Properties

Boiling Pt:B.P. Text:180F,82C
Melt/Freeze Pt:M.P/F.P Text:28.0F,-2.2C
Vapor Pres:.03
Vapor Density:2.80
Spec Gravity:.84 (H*2O=1)
pH:5.5
Evaporation Rate & Reference:.10 (BUTYL ACETATE=1)
Solubility in Water:10%
Appearance and Odor:RED, CLEAR COLOR, NON-IRRITATING ODOR.

Stability

Stability Indicator/Materials to Avoid:YES
NONE SPECIFIED BY MANUFACTURER.
Stability Condition to Avoid:NONE CURRENTLY KNOWN.
Hazardous Decomposition Products:NONE SPECIFIED BY MANUFACTURER.

Disposal

Waste Disposal Methods:COLLECT AND DISPOSE OF THE SAME AS FOR OIL OR ALIPHATIC SOLVENTS ACCORDING TO ALL FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.