

## **GLASCOAT YELLOW RESIN**

### **MSDS Number**

BWFWT

### **National Stock Number**

5610-00N056281

### **Product Name**

GLASCOAT YELLOW RESIN

### **Manufacturer**

KOCH INDUSTRIES INC

### **Product Identification**

Product ID:GLASCOAT YELLOW RESIN

MSDS Date:01/13/1994

FSC:5610

NIIN:00N056281

MSDS Number: BWFWT

### **Responsible Party**

KOCH INDUSTRIES INC

4901 EXCELSIOR BLVD

MINNEAPOLIS , MN 55416-3011

US

Emergency Phone: 800-424-9300(CHEMTREC)

Info Phone: 612-920-7722

Cage: 8U969

### **Contractor**

KOCH INDUSTRIES

1-800-4249300 CHEMTREC

Cage: 8U969

### **Ingredients**

FIBROUS GLASS; (FIBERGLASS)

RTECS: LK3651000

Fraction By Weight:

OSHA PEL15 MG/M3 (MFR)

ACGIH TLV: 10 MG/M3 (MFR)

### **Hazards**

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:THERE IS NOT CHEMICAL HAZARD FROM THIS

MATERIAL. TOO MUCH GLASS FIBER DUST IN AIR WILL BE IRRITATING TO

RESPIRATORY TRACT & EYES, BUT THIS IS NOT LIKELY TO HAPPEN W/THIS

MATERIAL. GLASS FIBER PARTICLE S ARE IRRITATING TO THE SKIN.

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:INHAL:RESPIRATORY IRRITATION.

SKIN/EYE:IRRITATION. INGEST:STOMACH IRRITATION.

### **First Aid**

First Aid:INHAL:REMOVE TO FRESH AIR. IF BRTHG IS DFCLT, GIVE OXYGEN; IF  
BRTHG HAS STOPPED, GIVE ARTF RESP. GET MED ATTN. SKIN:WASH W/SOAP &

WATER/USE WATERLESS HANDCLEANER. DO NOT USE SOLVS OF THINNERS TO CLEAN SKIN. INGEST:IF VICTIM IS CONSCIOUS, GIVE LIQS. CALL MD. DO NOT INDUCE VOMIT UNLESS DIRECTED TO DO SO BY MD. EYES:FLUSH W/LG AMTS OF WATER FOR AT LST 15 MINS WHILE HOLDING EYELIDS OPEN. GET (SUPDAT)

## Fire Fighting

Flash Point Method:CC

Extinguishing Media:MEDIA SUITABLE FOR SURROUNDING FIRE .

Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT .

Unusual Fire/Explosion Hazard:FIBERGLASS WILL NOT BURN. IN HEAT OF FIRE, ORGANIC BINDERS MAY VAPORIZE & ADD TO THE INTENSITY OF FIRE.

## Accidental Release

Spill Release Procedures:NONE SPECIFIED BY MANUFACTURER.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

## Handling

Handling and Storage Precautions:DO NOT INGEST. CAUTION! GLASS FIBERS MAY BE IRRITATING TO THE SKIN.

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

## Exposure Controls

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN . NOT NORMALLY REQUIRED.

Ventilation:NORMAL VENTILATION IS USUALLY ADEQUATE.

Protective Gloves:NEOPRENE OR VINYL GLOVES.

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:WEAR A PROTECTIVE APRON IF REPEATED CONTACT IS LIKELY.

Work Hygienic Practices:SHOWER & CLEAN WORK CLOTHES DAILY IS RECOMMENDED.

Supplemental Safety and Health

APPEAR/ODOR:WHICH WILL NOT ROT, TEAR OR WEAR. IT IS LIGHTWEIGHT & WILL CONFORM TO IRREGULAR SURFACES. FIRST AID PROC:MEDICAL ATTENTION IF IRRITATION PERSISTS.

## Chemical Properties

Solubility in Water:INSOLUBLE

Appearance and Odor:BONDED GLASS FIBER SHEET. GLASCOAT YELLOW RESIN IS A RESIN COATED FABRIC(SUPDAT

## Stability

Stability Indicator/Materials to Avoid:YES  
NONE.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, ALDEHYDES & OTHER UNIDENTIFIED COMPOUNDS MAY FORM UPON COMBUSTION.

## Disposal

Waste Disposal Methods:WASTES SHOULD BE DISPOSED OF ACCORDING TO FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.