

## **C 30572 CELLU-TONE ALKYD SATIN ENAMEL HIGH HIDING WHITE**

### **MSDS Number**

BWHLF

### **National Stock Number**

8010-00F012759

### **Product Name**

C 30572 CELLU-TONE ALKYD SATIN ENAMEL HIGH HIDING WHITE

### **Manufacturer**

PRATT AND LAMBERT INC

### **Product Identification**

Product ID:C 30572 CELLU-TONE ALKYD SATIN ENAMEL HIGH HIDING WHITE

MSDS Date:07/15/1992

FSC:8010

NIIN:00F012759

MSDS Number: BWHLF

### **Responsible Party**

PRATT AND LAMBERT INC

75 TONAWANDA ST

BUFFALO , NY 14240-5000

US

Emergency Phone: 716-873-6000

Info Phone: 716-873-6000

Cage: 61196

### **Contractor**

PRATT AND LAMBERT INC

CLEVELAND, OH 44101-1027

US

216-566-2902

Cage: 61196

### **Ingredients**

MEDIUM ALIPHATIC NAPHTHA (AROMATIC 100), PARAFFIN-NAPTHANES

CAS: 64742-88-7

Fraction By Weight: 20%

OSHA PEL100 PPM

ACGIH TLV: 100 PPM

KEROSENE (PETROLEUM), HYDROTREATED (C10-C15 SATURATED

CAS: 64742-47-8

RTECS: OA5504000

Fraction By Weight: 5%

TITANIUM DIOXIDE, TIO2 (SUSPECTED ANIMAL CARCINOGEN BY

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: 20%

OSHA PEL10 MG/CUM

ACGIH TLV: 10 MG/CUM (DUST)

SILICON DIOXIDE, CELITE 322

CAS: 7631-86-9

RTECS: VV3100000

Fraction By Weight:

OSHA PEL6 MG/CUM

ACGIH TLV: 0.2 MG/CUM

NAPHTHA PETROLEUM, HEAVY ALKYLATE C9-C12 BOILING PT

CAS: 64741-65-7

Fraction By Weight: 50-65%

LESS WATER-3.48 LBS/GAL;

RTECS: 9999999VO

## Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INGESTION: GI IRRITATION. INHALATION:  
NOSE/THROAT IRRITATION & ACUTE CNS DEPRESSION. EYES/SKIN;  
IRRITATION. ASPIRATION OF MATERIAL INTO LUNGS MAY CAUSE CHEMICAL  
PNEUMONITIS WHICH CAN BE FATAL.  
Explanation of Carcinogenicity:NONE  
Effects of Overexposure:IRRITATION, NAUSEA, VOMITING, HEADACHES,  
DIZZINESS, CONFUSION, DEFATTING.

## First Aid

First Aid:INGESTION: DON'T INDUCE VOMITING. ASPIRATION HAZARD.  
INHALATION: REMOVE TO FRESH AIR. GIVE CPR IF NEEDED. KEEP WARM &  
QUIET. EYES: FLUSH W/LARGE AMOUNTS OF WATER FOR 15 MINS. SKIN: WASH  
AFFECTED AREA W/SOAP & WATER. OBTAIN MEDICAL ATTENTION IN ALL  
CASES. NOTES TO PHYSICIAN: ANY TREATMENT THAT MIGHT BE REQUIRED FOR  
OVEREXPOSURE SHOULD BE DIRECTED AT CONTROL OF SYMPTOMS & CLINICAL  
CONDITIONS.

## Fire Fighting

Flash Point Method:SCC  
Flash Point:115F  
Extinguishing Media:CO2, ALL PURPOSE DRY CHEMICAL, ALCOHOL FOAM. LARGE:  
POLYMER FOAM PREFERRED.  
Fire Fighting Procedures:WEAR SCBA. WATER MAY BE INEFFECTIVE, BUT MAY  
BE USED TO COOL EXPOSED CONTAINERS. IF WATER IS USED, FOG NOZZLES  
ARE PREFERABLE.  
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN  
EXPOSED TO EXTREME HEAT. COMBUSTIBLE LIQUID.

## Accidental Release

Spill Release Procedures:WEAR PERSONAL PROTECTIVE EQUIPMENT. ISOLATE  
AREA. REMOVE ALL IGNITION SOURCES. DIKE/CONTAIN W/INERT MATERIAL.  
TRANSFER TO COVERED METAL CONTAINERS FOR RECOVERY/DISPOSAL/REMOVE  
W/INERT ABSORBENT. USE ONLY NON-SPARKING TOOLS. (SEE SUPP)

---

## Handling

Handling and Storage Precautions:DON'T STORE >115F. TIGHTLY CLOSE CONTAINER AFTER USE. USE IN WELL VENTILATED AREAS. ISOLATE FROM IGNITION SOURCES.

Other Precautions:DON'T TAKE INTERNALLY. CONTAINERS SHOULD BE GROUNDED & BONDED TO RECEIVING CONTAINER. DON'T WASH/REUSE EMPTY CONTAINERS FOR ANY PURPOSE. DON'T WELD/BRAZE/CUT ON EMPTY CONTAINER. NEVER USE PRESSURE TO EMPTY. DRUM ISN'T A PRESSURE VESSEL.

## Exposure Controls

Respiratory Protection:RESTRICTED AREAS-WEAR A NIOSH APPROVED CHEMICAL CARTRIDGE RESPIRATOR. SPARYING-MECHANICAL PREFILTER. CONFINED AREAS- WEAR A NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR.

Ventilation:LOCAL EXHAUST IN SUFFICIENT VOLUME & PATTERN TO MAINTAIN EXPOSURES Protective Gloves:SOLVENT IMPERMEABLE

Eye Protection:SAFETY GLASSES

Other Protective Equipment:EYEWASH FACILITIES, SAFETY SHOWER.

Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

SPILLS CONT'D: PLACE ABSORBENT DIKING MATERIALS IN COVERED METAL CONTAINERS FOR DISPOSAL. PREVENT CONTAMINATION OF SEWERS/STREAMS/GROUNDWATER W/SPILLED MATERIAL/USED ABSORBENT. OTHER PRECAUTIONS CONT' D: INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING & INHALING CONTENTS MAY BE HARMFUL/FATAL.

## Chemical Properties

Boiling Pt:B.P. Text:277-490F

Vapor Density:>1

Spec Gravity:1.2

Evaporation Rate & Reference:SLOWER THAN DIETHYL ETHER

Appearance and Odor:WHITE LIQUID.

Percent Volatiles by Volume:53

## Stability

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS, ALKALINE MATERIALS.

Stability Condition to Avoid:TEMP >115F, EXTREME HEAT, SPARKS, FLAME & OTHER IGNITION SOURCES.

Hazardous Decomposition Products:SMOKE, CO & CO2.

## Disposal

Waste Disposal Methods:INCINERATE ONLY IN EPA PERMITTED FACILITY. DON'T INCINERATE CLOSED CONTAINERS. CONTAMINATED ABSORBENT MAY BE DISPOSED OF IN A HAZADOUS WASTE LANDFILL IAW/FEDERAL, STATE & LOCAL REGULATIONS. HAZARDOUS WASTE #: D001

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.