

2710 DAL SHIELD EXERIOR LATEX SEMI GLOSS

MSDS Number

BWHXW

National Stock Number

8010-00F037378

Product Name

2710 DAL SHIELD EXERIOR LATEX SEMI GLOSS

Manufacturer

DAL WORTH PAINT MFG CO

Product Identification

Product ID:2710 DAL SHIELD EXERIOR LATEX SEMI GLOSS

MSDS Date:11/01/1989

FSC:8010

NIIN:00F037378

MSDS Number: BWHXW

Responsible Party

DAL-WORTH PAINT MFG CO

733 DALWORTH DR

MESQUITE , TX 75149-0173

US

Emergency Phone: 214-285-6346

Info Phone: 214-285-6346

Cage: DALWO

Contractor

DAL-WORTH PAINT MFG CO

173

MESQUITE, TX 75149-0173

US

214-285-6346

Cage: DALWO

Ingredients

NON HAZARDOUS INGREDIENTS

1.72 LBS/GAL

RTECS: 9999999VO

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: IRRITATION OF RESPIRATORY TRACT. SKIN/EYES: PRIMARY IRRITATION. INGESTION: MAY CAUSE SERIOUS INJURY.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:IRRITATION.

First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. EYES: FLUSH THOROUGHLY

W/WATER. SKIN: WASH W/SOAP & WATER. INGESTION: DRINK 1-2 GLASSES OF WATER TO DILUTE. DON'T INDUCE VOMITING. OBTAIN MEDICAL ATTENTION IN ALL CASE S.

Fire Fighting

Flash Point Method:PMCC

Flash Point:>250F

Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER FOG.

Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS. COOL EXPOSED CONTAINERS W/WATER.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY BURST IF EXPOSED TO EXTREME HEAT/FIRE.

Accidental Release

Spill Release Procedures:FLUSH W/WATER. ABSORB W/SAWDUST/RAGS.

Handling

Handling and Storage Precautions:DON'T THROW/DROP CONTAINERS. CLOSE CONTAINER AFTER EACH USE.

Other Precautions:AVOID CONTACT W/EYES, PROLONGED CONTACT W/SKIN & BREATHING OF SPRAY MIST/SANDING DUST. KEEP OUT OF REACH OF CHILDREN. DON'T TAKE INTERNALLY.

Exposure Controls

Respiratory Protection:WEAR NIOSH APPROVED RESPIRATOR FOR PAINT SPRAY MIST & SANDING DUST IN RESTRICTED/CONFINED AREAS.

Ventilation:ADEQUATE TO MAINTAIN WORKING ATMOSPHERE MECHANICAL EXHAUST MAY BE REQUIRED IN CONFINED AREAS.

Protective Gloves:WATERPROOF

Eye Protection:SAFETY GLASSES W/SIDE SHIELDS

Other Protective Equipment:SPLASH GOGGLES, ADEQUATE CLOTHING.

Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. WASH HANDS BEFORE EATING, SMOKING/USING WASHROOM.

Supplemental Safety and Health

Chemical Properties

Vapor Density:>1

Evaporation Rate & Reference:SLOWER THAN ETHER

Appearance and Odor:WHITE, PASTEL BASE, COLORS

Stability

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:EXTREME HEAT, FIRE, ELEVATED TEMPS.

Hazardous Decomposition Products:CO, CO2

Disposal

Waste Disposal Methods:DISPOSE OF IAW/FEDERAL, STATE & LOCAL REGULATIONS. DON'T INCINERATE SEALED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.