

## 1910 PROFESSIONAL FINISHES INTERIOR LATEX FLAT ALL COLORS

## **MSDS Number**

**BWHXY** 

### **National Stock Number**

8010-00F037380

### **Product Name**

1910 PROFESSIONAL FINISHES INTERIOR LATEX FLAT ALL COLORS

#### Manufacturer

DAL WORTH PAINT MFG CO

## **Product Identification**

Product ID:1910 PROFESSIONAL FINISHES INTERIOR LATEX FLAT ALL COLORS

MSDS Date:11/01/1989

FSC:8010

NIIN:00F037380

MSDS Number: BWHXY

## **Responsible Party**

DAL-WORTH PAINT MFG CO

733 DALWORTH DR

MESQUITE, TX 75149-0173

US

Emergency Phone: 214-285-6346

Info Phone: 214-285-6346

Cage: DALWO **Contractor** 

# DAL-WORTH PAINT MFG CO

173 MESQUITE, TX 75149-0173

US

214-285-6346

Cage: DALWO

## **Ingredients**

ETHYLENE GLYCOL, GLYCOL

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight: 0.8%

OSHA PEL50 PPM

ACGIH TLV: 50 PPM

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

0.61 LBS/GAL

RTECS: 9999999VO

**Hazards** 



Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: IRRITATION OF RESPIRATORY TRACT. SKIN/EYES: PRIMARY IRRITATION. INGESTION: MAY CAUSE SERIOUS

INJURY.

Explanation of Carcinogenicity: NONE Effects of Overexposure: IRRITATION.

#### First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. EYES: FLUSH THOROUGHLY W/WATER. SKIN: WASH W/SOAP & WATER. INGESTION: DRINK 1-2 GLASSES OF WATER TO DILUTE. DON'T INDUCE VOMITING. OBTAIN MEDICAL ATTENTION IN ALL CASE S.

## **Fire Fighting**

Flash Point Method: PMCC

Flash Point:>250F

Extinguishing Media: FOAM, CO2, DRY CHEMICAL, WATER FOG.

Fire Fighting Procedures: WEAR SELF CONTAINED BREATHING APPARATUS. COOL

EXPOSED CONTAINERS W/WATER.

Unusual Fire/Explosion Hazard: CLOSED CONTAINERS MAY BURST IF EXPOSED TO

EXTREME HEAT/FIRE.

#### **Accidental Release**

Spill Release Procedures: FLUSH W/WATER. ABSORB W/SAWDUST/RAGS.

## Handling

Handling and Storage Precautions:DON'T THROW/DROP CONTAINERS. CLOSE CONTAINER AFTER EACH USE.
Other Precautions:AVOID CONTACT W/EYES, PROLONGED CONTACT W/SKIN &

BREATHING OF SPRAY MIST/SANDING DUST. KEEP OUT OF REACH OF CHILDREN. DON'T TAKE INTERNALLY.

### **Exposure Controls**

Respiratory Protection: WEAR NIOSH APPROVED RESPSIRATOR FOR PAINT SPRAY

MIST & SANDING DUST IN RESTRICTED/CONFINED AREAS.

Ventilation: ADEQUATE TO MAINTAIN WORKING ATMOSPHERE MECHANICAL EXHAUST MAY BE REQUIRED IN CONFINED AREAS.

Protective Gloves: WATERPROOF

Eye Protection: SAFETY GLASSES W/SIDE SHIELDS

Other Protective Equipment: SPLASH GOGGLES, ADEQUATE CLOTHING.

Work Hygienic Practices: REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE

REUSE. WASH HANDS BEFORE EATING, SMOKING/USING WASHROOM.

Supplemental Safety and Health

### **Chemical Properties**

Vapor Density:>1

Evaporation Rate & Reference: SLOWER THAN ETHER

## **Stability**

Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:EXTREME HEAT, FIRE, ELEVATED TEMPS. Hazardous Decomposition Products:CO, CO2

### **Disposal**

Waste Disposal Methods: DISPOSE OF IAW/FEDERAL, STATE & LOCAL REGULATIONS. DON'T INCINERATE SEALED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.