msds report

https://msdsreport.com/msds/BWJWR

# T L C ALCOHOL FOAM SCRUB

### **MSDS Number**

BWJWR

### **National Stock Number**

7930-00F037791

### **Product Name**

T L C ALCOHOL FOAM SCRUB

### Manufacturer

POLYCHEM CORP

## **Product Identification**

Product ID:T L C ALCOHOL FOAM SCRUB MSDS Date:06/02/1993 FSC:7930 NIIN:00F037791 MSDS Number: BWJWR

### **Responsible Party**

POLYCHEM CORP

12 LYMAN ST

NEW HAVEN , CT 06511-1514

US

Emergency Phone: 203-243-3093/203-777-7363

Info Phone: 203-243-3093/203-777-7363

Cage: 51954

### Contractor

POLYCHEM CORP

NEW HAVEN, CT 06511-1514

US

203-243-3093

Cage: 51954

# Ingredients

ETHANOL (ETHYL ALCOHOL), TECSOL, ALCOHOL CAS: 64-17-5 RTECS: KQ6300000 Fraction By Weight: 60% OSHA PEL1000 PPM

ISOBUTANE, 2-METHYLPROPANE CAS: 75-28-5 RTECS: TZ4300000 Fraction By Weight: 4% OSHA PEL1000 PPM

# Hazards

Routes of Entry: Inhalation:NO Skin:NO Ingestion:YES



Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INGESTION: REPEATED USE COULD CAUSE CNS EFFECTS. EYES: IRRITATION. Explanation of Carcinogenicity:NONE Effects of Overexposure:DROWSINESS, VOMITING &/INTOXICATION.

•

#### **First Aid**

First Aid:INGESTION: INDUCE VOMITING. GIVE A GLASS OF WATER. IF VOMITING DOES OCCUR GIVE A GLASS OF WATER AGAIN. DON'T GIVE FLUIDS TO A UNCONSCIOUS/CONVULSING PERSON. INHALATION: IMMEDIATELY REMOVE TO FRESH AIR . SKIN: IF ALLERGIES DEVELOP DISCONTINUE USE. EYES: IMMEDIATELY FLUSH W/LARGE QUANTITIES OF WATER FOR 15 MINS. DON'T ATTEMPT TO NEUTRALIZE W/CHEMICAL AGENTS. OILS/OINTMENTS SHOULDN'T BE USED. (SUPP)

### **Fire Fighting**

Flash Point Method:COC Flash Point:58F Extinguishing Media:DRY CHEMICAL & CO2. Fire Fighting Procedures:FOAM & WATER FOG ARE EFFECTIVE BUT MAY CAUSE FROTHING. WEAR MSHA/NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS, W/FULL FACE MASK & FULL PROTECTIVE EQUIPMENT Unusual Fire/Explosion Hazard:CONTENTS UNDER PRESSURE. CAN BE A SEVERE EXPLOSION HAZARD. BURNING LIQUID WILL FLOAT ON WATER.

#### **Accidental Release**

Spill Release Procedures:SOAK UP LIQUID W/ABSORBENT MATERIAL. PLACE MATERIAL IN A CHEMICAL WASTE CONTAINER FOR DISPOSAL.

### Handling

Handling and Storage Precautions:STORE IN A COOL DRY PLACE. DON'T STORE >120F/NEAR HEAT SOURCE. Other Precautions:DON'T USE WHILE SMOKING. DON'T PUNCTURE/INCINERATE CAN.

### **Exposure Controls**

Ventilation:GENERAL ROOM VENTILATION IS SUFFICIENT Work Hygienic Practices:ALL FOOD SHOULD BE KEPT IN A SEPARATE AREA, AWAY FROM THE WORKING LOCATION. (SEE SUPP) Supplemental Safety and Health EMERGENCY FIRST AID CONT'D: CONTINUE FLUSHING FOR AN ADDITIONAL 15 MINS IF A PHYSICIAN ISN'T IMMEDIATELY AVAILABLE. OBTAIN MEDICAL ATTENTION IN ALL CASES. WORK HYGIENIC PRACTICES CONT'D: EATING/DRINKI NG & SMOKING SHOULD BE PROHIBITED IN WORK AREA. BEFORE EATING, HANDS & FACE SHOULD BE THOROUGHLY WASHED.

### **Chemical Properties**

Boiling Pt:B.P. Text:173F Vapor Pres:70 Vapor Density:1.59 Solubility in Water:96% Appearance and Odor:WHITE FOAM W/NO ODOR.

#### Stability

Stability Indicator/Materials to Avoid:YES OXIDIZING MATERIALS. Stability Condition to Avoid:EXTREME HEAT, OPEN FLAME, IGNITION SOURCES & HIGH TEMPERATURES. Hazardous Decomposition Products:CO & OTHER HARMFUL SUBSTANCES.

#### Disposal

Waste Disposal Methods:DISPOSE OF IAW/FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,



https://msdsreport.com/msds/BWJWR

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.