

007 POLY SATIN VARNISH - F20

MSDS Number

BWKHC

National Stock Number

8010-00F037971

Product Name

007 POLY SATIN VARNISH - F20

Manufacturer

DAL WORTH PAINT MFG CO

Product Identification

Product ID:007 POLY SATIN VARNISH - F20

MSDS Date:03/12/1986

FSC:8010

NIIN:00F037971

MSDS Number: BWKHC

Responsible Party

DAL-WORTH PAINT MFG CO

733 DALWORTH DR

MESQUITE , TX 75149-0173

US

Emergency Phone: 214-285-6346

Info Phone: 214-285-6346

Cage: DALWO

Contractor

DAL-WORTH PAINT MFG CO

173

MESQUITE, TX 75149-0173

US

214-285-6346

Cage: DALWO

Ingredients

MINERAL SPIRITS-ALIPHATIC HYDROCARBONS

Fraction By Weight: 52%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM

Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: NASAL & RESPIRATORY IRRITATION. ANEMIA, KIDNEY DAMAGE. NOTICE: REPORTS HAVE ASSOCIATED PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE W/REPEATED PROLONGED OVEREXPOSURE TO SOLVENTS. INTENTIONAL MI SUSE BY DELIBERATELY CONCENTRATING & INHALING CONTENTS MAY BE HARMFUL/FATAL.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:IRRITATION, PALE, NAUSEA, DIZZY, WEAK, REDNESS, TEARING, BLURRED VISION, VOMITING, DIARRHEA, SENSITIZATION.

Medical Cond Aggravated by Exposure:RESPIRATORY ALLERGIES & SKIN

SENSITIZATION MAY BECOME WORSE UPON EXPOSURE TO THE PRODUCT/ITS INGREDIENTS.

First Aid

First Aid: INHALATION: REMOVE TO FRESH AIR. GIVE OXYGEN IF NEEDED. EYES: FLUSH W/LARGE AMOUNTS OF WATER. SKIN: THOROUGHLY WASH EXPOSED AREA W/SOAP & WATER. INGESTION: DON'T INDUCE VOMITTING, KEEP WARM & QUIET. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point Method: TCC
Flash Point: 100F
Lower Limits: 1.02
Extinguishing Media: FOAM, CO2, DRY CHEMICAL.
Fire Fighting Procedures: WEAR SCBA.
Unusual Fire/Explosion Hazard: ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS & OPEN FLAMES. CLOSED CONTAINER MAY RUPTURE WHEN EXPOSED TO EXTREME HEAT. AUTOIGNITION TEMP 473F.

Accidental Release

Spill Release Procedures: ABSORB LIQUID ON PAPER, VERMICULITE, FLOOR ABSORBENT. STOP AT SOURCE, DIKE AREA, PUMP LIQUID TO SALVAGE TANK.

Handling

Handling and Storage Precautions: USE ONLY IN WELL VENTILATED AREA. AVOID STORAGE AT HIGH FLASH POINT TEMP 100F NEAR FIRE/OPEN FLAME. Other Precautions: KEEP CLOSURE TIGHT & CONTAINER UPRIGHT TO PREVENT LEAKAGE.

Exposure Controls

Respiratory Protection: APPROVED CHEMICAL/MECHANICAL FILTERS.
Ventilation: LOCAL EXHAUST/MECHANICAL (GENERAL): RECOMMENDED. EXPLOSION PROOF.
Protective Gloves: REQUIRED
Eye Protection: SPLASH GOGGLES
Other Protective Equipment: WEAR CHEMICAL RESISTANT BOOTS.
Work Hygienic Practices: REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. WASH HANDS BEFORE EATING/USING THE WASHROOM.
Supplemental Safety and Health

Chemical Properties

Boiling Pt: B.P. Text: 300F
Vapor Pres: 2
Vapor Density: 4.9
Spec Gravity: 0.9
Solubility in Water: INSOLUBLE
Appearance and Odor: CLEAR LIQUID W/PETROLEUM DISTILLATES

Stability

Stability Indicator/Materials to Avoid: YES
STRONG OXIDIZING AGENTS.
Stability Condition to Avoid: HEAT, SPARKS, OPEN FLAME.
Hazardous Decomposition Products: CO, HYDROCARBONS.

Disposal

Waste Disposal Methods: ALLOW VOLATILE PORTION TO EVAPORATE IN HOOD. DESTROY BY LIQUID INCINERATION IAW/FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.

