

0510 ENCORE LATEX MEDIUM GLOSS EXTERIOR HOUSE & TRIM

MSDS Number

BWKHK

National Stock Number

8010-00F037977

Product Name

0510 ENCORE LATEX MEDIUM GLOSS EXTERIOR HOUSE & TRIM

Manufacturer

DAL WORTH PAINT MFG CO

Product Identification

Product ID:0510 ENCORE LATEX MEDIUM GLOSS EXTERIOR HOUSE & TRIM MSDS Date:11/01/1989

FSC:8010

NIIN:00F037977 MSDS Number: BWKHK

Responsible Party

DAL-WORTH PAINT MFG CO

733 DALWORTH DR

MESQUITE, TX 75149-0173

US

Emergency Phone: 214-285-6346

Info Phone: 214-285-6346

Cage: DALWO

Contractor

DAL-WORTH PAINT MFG CO

173

US

MESQUITE, TX 75149-0173

214-285-6346 Cage: DALWO

Ingredients

1.72 LBS/GAL.

RTECS: 9999999VO

NON HAZARDOUS INGREDIENTS

Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO

Health Hazards Acute and Chronic: INHALTION: IRRITATION OF THE

RESPIRATORY TRACT. SKIN/EYES: PRIMARY IRRITATION. INGESTION: LARGE

AMOUNTS COULD CAUSE SERIOUS INJURY.

Explanation of Carcinogenicity: NONE Effects of Overexposure: IRRITATION.

Medical Cond Aggravated by Exposure: WHEN USED IN ACCORDANCE W/SAFE

HANDLING.

First Aid



First Aid:INHALATION: REMOVE TO FRESH AIR. EYES: FLUSH THOROUGHLY W/WATER. SKIN: WASH W/SOAP & WATER. INGESTION: DRINK 1/2 GLASSES OF WATER TO DILUTE. DON'T INDUCE VOMITING. OBTAIN MEDICAL ATTENTION IN ALL CASE S.

Fire Fighting

Flash Point Method: PMCC

Flash Point:>250F

Extinguishing Media: FOAM, CO2, DRY CHEMICAL, WATER FOG.

Fire Fighting Procedures: COOL EXPOSED CONTAINERS W/WATER. USE SCBA. Unusual Fire/Explosion Hazard: CLOSED CONTAINERS MAY BURST IF EXPOSED TO EXTREME HEAT/FIRE. TOXIC GASES MAY FORM WHEN PRODUCT BURNS.

Accidental Release

Spill Release Procedures: FLUSH W/WATER. ABSORB W/SAWDUST/RAGS.

Handling

Handling and Storage Precautions: DON'T THROW/DROP CONTAINERS. CLOSE CONTAINER AFTER EACH USE.

Other Precautions: AVOID PROLONGED CONTACT W/EYES & SKIN/BREATHING OF SPRAY MIST/SANDING DUST. DON'T TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN.

Exposure Controls

Respiratory Protection: USE NIOSH APPROVED RESPIRATOR SPECIFIED FOR PROTECTION AGAINST PAINT SPRAY MIST & SANDING DUST IN RESTRICTED/CONFINED AREAS.

Ventilation: ADEQUATE/MECHANICAL EXHAUST MAY BE REQUIRED IN CONFINED AREAS.

Protective Gloves: WATERPROOF

Eye Protection: SPLASH GOGGLES

Other Protective Equipment: SAFETY GLASSES W/SIDE SHIELDS. ADEQUATE CLOTHING TO PROTECT SKIN.

Work Hygienic Practices: REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. WASH HANDS BEFORE EATING, SMOKING/USING THE WASHROOM. Supplemental Safety and Health

Chemical Properties

Vapor Density:>1

Evaporation Rate & Reference: SLOWER THAN ETHER

Stability

Stability Indicator/Materials to Avoid:YES

NONE

Stability Condition to Avoid: ELEVATED TEMPS.

Hazardous Decomposition Products: CO2, CO.

Disposal

Waste Disposal Methods: DON'T INCINERATE SEALED CONTAINERS. DISPOSE OF IAW/FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.