

## **MIL-H-46170B TYPE 2, PROD/MSDS#:0425599**

### **MSDS Number**

BWPTL

### **National Stock Number**

9150-01-131-3325

### **Product Name**

MIL-H-46170B TYPE 2, PROD/MSDS#:0425599

### **Manufacturer**

VELSICOL CHEMICAL CORP

### **Product Identification**

Product ID:MIL-H-46170B TYPE 2, PROD/MSDS#:0425599

MSDS Date:02/21/1991

FSC:9150

NIIN:01-131-3325

MSDS Number: BWPTL

### **Responsible Party**

VELSICOL CHEMICAL CORP

10400 W. HIGGINS, SUITE 600

DES PLAINES , IL 60018

US

Emergency Phone: 708-298-9000

Info Phone: 708-635-3471

Preparer: MANAGER, PRODUCT SAFETY

Cage: VELSI

### **Contractor**

VELSICOL CHEMICAL CORPORATION

ROSEMONT, IL 60018

US

847-298-9000

Cage: VELSI

### **Ingredients**

(PETROLEUM SULFONATE) BARIUM DINONYLNAPHTHALENE- SULFONATE

CAS: 25619-56-1

Fraction By Weight: 2%

BARIUM COMPOUNDS

Fraction By Weight: 2-3%

### **Hazards**

LD50 LC50 Mixture:NONE ESTABLISHED

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:LOW ORAL & DERMAL TOXICITY.

MISTS/FUMES FROM EXCESSIVE HEATING MAY CAUSE EYE/SKIN IRRIT,  
NAUSEA, VOMITING, RESPIRATORY TRACT IRRIT. BARIUM COMPOUNDS IS  
MODERATE SKIN IRRITANT & IS CORROSIVE TO EYES.

Effects of Overexposure:EYE/SKIN/RESPIRATORY TRACT IRRIT. NAUSEA, VOMITING.  
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

## First Aid

First Aid:CONTACT:FLUSH EYES W/PLENTY OF WATER FOR 15MINS. WASH SKIN W/SOAP & WATER. CALL PHYSICIAN IF IRRIT PERSISTS. INHAL:REMOVE TO FRESH AIR & GIVE CPR OR OXYGEN IF NEEDED. CALL PHYSICIAN. INGEST:DO NOT INDUCE VOMITING. CALL PHYSICIAN.

## Fire Fighting

Flash Point Method:COC  
Flash Point:430F,221C  
Extinguishing Media:WATER FOG, DRY CHEMICAL, FOAM, OR CARBON DIOXIDE.  
Fire Fighting Procedures:BURNING WILL PRODUCE TOXIC FUMES. WEAR SELF-CONTAINED BREATHING APPARATUS & FULL TURN-OUT GEAR TO FIGHT FIRE. AVOID SPREADING LIQ & FIRE BY WATER FLOODING.  
Unusual Fire/Explosion Hazard:EXPOSURE TO HEAT BUILDS UP PRESSURE IN CLOSED CONTAINERS. COOL WITH WATER SPRAY.

## Accidental Release

Spill Release Procedures:COVER W/AN INERT ABSORBENT MATERIAL & REMOVE TO DISPOSAL CONTAINER. OBEY ALL RELEVANT LOCAL, STATE AND FEDERAL LAWS. DO NOT CONTAMINATE ANY LAKES, STREAMS, PONDS OR UNDERGROUND WATER SUPPLY.

## Handling

Handling and Storage Precautions:CAUTION:DO NOT USE OIL ABOVE MAX RECOMMENDED OPERATING TEMP OF 430F. MAY SOFTEN SOME PLASTIC & PAINT SURFACES. WIPE UP SPILLS IMMEDIATELY.  
Other Precautions:AVOID EYE/SKIN CONTACT.

## Exposure Controls

Respiratory Protection:IF OVERHEATED USE APPROPRIATE NIOSH-APPROVED RESPIRATORY PROTECTIVE EQUIPMENT.  
Ventilation:LOCAL EXHAUST & MECHANICAL VENTILATION RECOMMENDED.  
Protective Gloves:IMPERMEABLE GLOVES  
Eye Protection:CHEMICAL SPLASH GOGGLES OR FACE SHIELDS  
Other Protective Equipment:EYE WASH FOUNTAIN, SAFETY SHOWER. WASH CONTAMINATED CLOTHING BEFORE REUSE.  
Work Hygienic Practices:WASH HANDS AFTER HANDLING.  
Supplemental Safety and Health

## Chemical Properties

HCC:V6  
Spec Gravity:0.842  
Solubility in Water:NEGLIGIBLE  
Appearance and Odor:RED LIQUID.  
Percent Volatiles by Volume:NOT VL

## Stability

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDANTS.  
Hazardous Decomposition Products:BURNING WILL PRODUCE TOXIC FUMES.

## Disposal

Waste Disposal Methods:OBEY RELEVANT LOCAL, STATE AND FEDERAL LAWS. DO NOT CONTAMINATE ANY LAKES, STREAMS, PONDS OR UNDERGROUND WATER SUPPLY.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their

particular situation.