

## **1100 GLOSS BLACK TEMPO ULTRA ENAMELS**

### **MSDS Number**

BWTZT

### **National Stock Number**

8010-00F038455

### **Product Name**

1100 GLOSS BLACK TEMPO ULTRA ENAMELS

### **Manufacturer**

PLASTI KOTE INC (TEMPO PRODUCTS CO)

### **Product Identification**

Product ID:1100 GLOSS BLACK TEMPO ULTRA ENAMELS

MSDS Date:10/10/1986

FSC:8010

NIIN:00F038455

MSDS Number: BWTZT

### **Responsible Party**

PLASTI-KOTE INC (TEMPO PRODUCTS CO)

1000 LAKE RD

MEDINA , OH 44258-5000

US

Emergency Phone: 216-725-4511

Info Phone: 216-725-4511

Cage: EO706

### **Contractor**

TEMPO PRODUCTS CO A PLASTI-KOTE CO INC

MEDINA, OH 44256

US

330-725-4511

Cage: 07708

### **Ingredients**

ACETONE; DIMETHYL KETONE; 2-PROPANONE

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight: 30-40%

OSHA PEL2400 MG/CUM

ACGIH TLV: 750 PPM

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

XYLENE, DIMETHYLBENZENE, XYLOL (IARC - GROUP 3) \*94-4\*

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 5-10%

OSHA PEL100 PPM

ACGIH TLV: 100 PPM, SKIN

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

ETHANOL (ETHYL ALCOHOL), TECSOL, ALCOHOL

CAS: 64-17-5

RTECS: KQ6300000

Fraction By Weight: 5-10%

OSHA PEL1000 PPM

ACGIH TLV: 1000 PPM

DIACETONE ALCOHOL

CAS: 123-42-2

RTECS: SA9100000

Fraction By Weight: 5-6%

OSHA PEL240 MG/CUM

ACGIH TLV: 238 MG/CUM

2-BUTANONE (METHYL ETHYL KETONE) (MEK)

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight: 5%

OSHA PEL200 PPM

ACGIH TLV: 590 MG/CUM

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

ISOBUTANE/PROPANE PROPELLANT \*94-4\*

CAS: 68474-85-7

Fraction By Weight: 23%

## Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: VAPORS CAN CAUSE NASAL & RESPIRATORY IRRITATION/ASPHYXIATION. INGESTION: CAN CAUSE GASTROINTESTINAL IRRITATION. ASPIRATION OF MATERIAL INTO THE LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE, POSSIBLE UNCONSCIOUSNESS, ASPHYXIATION, VOMITING, DIARRHEA

## First Aid

First Aid:INGESTION: ASPIRATION HAZARD. DON'T INDUCE VOMITING, KEEP WARM & QUIET. INHALATION: REMOVE TO FRESH AIR. GIVE OXYGEN/CPR IF NECESSARY. OBTAIN MEDICAL ATTENTION IN ALL CASES.

---

## Fire Fighting

Flash Point:0F  
Lower Limits:1.1  
Extinguishing Media:CO2/DRY CHEMICAL/ALCOHOL FOAM  
Fire Fighting Procedures:WATER SPRAY MAY BE INEFFECTIVE. WATER MAY BE USED TO COOL CLOSED CONTAINERS WHEN EXPOSED TO EXTREME HEAT. IF WATER IS USED, FOG NOZZLES ARE PREFERRED.  
Unusual Fire/Explosion Hazard:EXTREMELY FLAMMABLE. VAPORS ARE >AIR & MAY TRAVEL ALONG THE GROUND/BE MOVED BY VENTILATION & IGNITED BY IGNITION SOURCES AT LOCATIONS DISTANT FROM HANDLING SITE

## Accidental Release

Spill Release Procedures:ABSORB LIQUID ON PAPER, VERMICULITE, FLOOR ABSORBENT/OTHER ABSORBENT MATERIAL & TRANSFER TO A CLOSED CONTAINER. ELIMINATE ALL IGNITION SOURCES.

## Handling

Handling and Storage Precautions:DON'T STORE IN AREAS >120F, IN DIRECT SUNLIGHT, NEAR HEAT/OPEN FLAMES. STORE LARGE QUANTITIES IN BUILDINGS PROTECTED FOR STORAGE NFPA CLASS 1C.

## Exposure Controls

Respiratory Protection:IF TLV IS EXCEEDED, A NIOSH/MSHA JOINTLY APPROVED SCBA W/A FULL FACE PIECE OPERATED IN PRESSURE DEMAND/OTHER POSITIVE PRESSURE MODE IS ADVISED.  
Ventilation:SUFFICIENT MECHANICAL (GENERAL)/LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW TLVS  
Protective Gloves:CHEMICAL RESISTANT  
Eye Protection:CHEMICAL SPLASH GOGGLES  
Supplemental Safety and Health

## Chemical Properties

Boiling Pt:B.P. Text:133-331F  
Vapor Density:>1  
Evaporation Rate & Reference:FASTER THAN ETHER  
Percent Volatiles by Volume:85-90

## Stability

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING AGENTS  
Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAME & OTHER IGNITION SOURCES  
Hazardous Decomposition Products:CO

## Disposal

Waste Disposal Methods:MATERIAL COLLECTED ON ABSORBENT MATERIAL MAY BE DEPOSITED IN A POSTED TOXIC SUBSTANCE LANDFILL IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.