
WATER MASTER WATERBORNE TOP COAT, 15TC, BRUSHABLE, GLOSS

MSDS Number

BWZVL

National Stock Number

8010-01-397-3594

Product Name

WATER MASTER WATERBORNE TOP COAT, 15TC, BRUSHABLE, GLOSS

Manufacturer

ALTERNATIVE MATERIALS TECHNOLOGY INC

Product Identification

Product ID:WATER MASTER WATERBORNE TOP COAT, 15TC, BRUSHABLE, GLOSS

MSDS Date:01/25/1994

FSC:8010

NIIN:01-397-3594

MSDS Number: BWZVL

Responsible Party

ALTERNATIVE MATERIALS TECHNOLOGY, INC

1266 HUMBOLDT AVENUE

CHICO , CA 95928

US

Emergency Phone: 916-894-3585

Info Phone: 916-894-3585

Cage: 0ZXD0

Contractor

ALTERNATIVE MATERIALS TECHNOLOGY, INC

CHICO, CA 95928

US

916-894-3585

Cage: 0ZXD0

Ingredients

ETHYLENE GLYCOL MONOBUTYL ETHER (SARA III)

CAS: 111-76-2

RTECS: KJ8575000

Fraction By Weight: 5.0%

OSHA PEL25 PPM (SKIN)

ACGIH TLV: 25 PPM (SKIN)

246 GRAMS/LITER MINUS

RTECS: 9999999VO

0.87 POUNDS/GALLON. 104

RTECS: 9999999VO

Hazards

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES
Health Hazards Acute and Chronic: EYE: SEVERE IRRITATION (DIRECT CONTACT). SKIN: SLIGHT IRRITATION (REPEATED PROLONGED CONTACT).
INHALATION: EYE & RESPIRATORY TRACT IRRITATION (EXTREMELY HIGH CONCENTRATIONS). SIGNS & SYMPTOMS OF TOXICITY SIMILAR TO SWALLOWING. SWALLOWING: HEADACHE, DIZZINESS, INCOORDINATION, NAUSEA, VOMITING, DIARRHEA, GENERAL *
Effects of Overexposure: * WEAKNESS. INGESTION OF SIGNIFICANT QUANTITIES MAY RESULT IN RED BLOOD CELL HEMOLYSIS.
Medical Condition Aggravated by Exposure: MAY AGGRAVATE AN EXISTING DERMATITIS.

First Aid

First Aid: EYES: IMMEDIATELY FLUSH EYES THOROUGHLY WITH WATER AND CONTINUE WASHING FOR SEVERAL MINUTES. OBTAIN MEDICAL ATTENTION.
SKIN: REMOVE CONTAMINATED CLOTHING. FLUSH SKIN WITH WATER.
INHALATION: REMOVE TO FRESH AIR. SWALLOWING: IF PATIENT IS CONSCIOUS AND HAS A GAG REFLEX, GIVE TWO GLASSES OF WATER. INDUCE VOMITING. OBTAIN MEDICAL ATTENTION IMMEDIATELY.

Fire Fighting

Flash Point Method: CC
Flash Point: NONCOMBUSTIBLE
Extinguishing Media: TYPE A, B, C, OR COMBINATION TYPE

Accidental Release

Spill Release Procedures: DIKE AND CONTAIN SPILLS. ABSORB WITH SUITABLE MATERIAL. COLLECT MATERIAL INTO SUITABLE CONTAINERS AND DISPOSE OF PROPERLY.

Exposure Controls

Respiratory Protection: IF ADEQUATE VENTILATION IS NOT MAINTAINED, RESPIRATOR (OSHA/NIOSH APPROVED) MAY BE NECESSARY. IF EXPOSURE TO SPRAY MISTS EXIST, WEAR NIOSH APPROVED ORGANIC VAPOR/PARTICULATE RESPIRATOR.
Ventilation: LOCAL EXHAUST VENTILATION IS RECOMMENDED.
Protective Gloves: IMPERVIOUS CHEMICAL RESISTANT GLOVES
Supplemental Safety and Health

Chemical Properties

Boiling Point: B.P. Text: 212F, 100C
Vapor Density: Specific Gravity: 1.015 (H₂O=1)
Evaporation Rate & Reference: Solubility in Water: DILUTABLE
Appearance and Odor: WHITE LIQUID, SLIGHT ODOR

Stability

Stability Indicator/Materials to Avoid: YES

Disposal

Waste Disposal Methods: DISPOSE OF PRODUCT IN ACCORDANCE WITH LOCAL, COUNTY, STATE, AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.