

# WATER MASTER WATERBORNE, TOP COAT, 15TC, BRUSHABLE, GLOSS

## **MSDS Number**

**BWZVT** 

### **National Stock Number**

8010-01-397-3601

## **Product Name**

WATER MASTER WATERBORNE, TOP COAT, 15TC, BRUSHABLE, GLOSS

#### Manufacturer

ALTERNATIVE MATERIALS TECHNOLOGY INC

## **Product Identification**

Product ID: WATER MASTER WATERBORNE, TOP COAT, 15TC, BRUSHABLE, GLOSS

MSDS Date:01/25/1994

FSC:8010

NIIN:01-397-3601

MSDS Number: BWZVT

## **Responsible Party**

ALTERNATIVE MATERIALS TECHNOLOGY, INC

1266 HUMBOLDT AVENUE

CHICO, CA 95928

US

Emergency Phone: 916-894-3585

Info Phone: 916-894-3585

Cage: 0ZXD0

## **Contractor**

ALTERNATIVE MATERIALS TECHNOLOGY, INC

CHICO, CA 95928

916-894-3585

US

Cage: 0ZXD0

## **Ingredients**

ETHYLENE GLYCOL MONOBUTYL ETHER (SARA III)

CAS: 111-76-2

RTECS: KJ8575000

Fraction By Weight: 5.0% OSHA PEL25 PPM (SKIN) ACGIH TLV: 25 PPM (SKIN)

246 GRAMS/LITER MINUS

RTECS: 9999999VO

0.87 POUNDS/GALLON. 104

RTECS: 9999999VO



#### Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:EYE: MAY CAUSE SEVERE IRRITATION.
SKIN: MAY CAUSE SLIGHT IRRITATION UPON REPEATED OR PROLONGED
CONTACT. INHALATION: (EXTREMELY HIGH CONCENTRATIONS) IRRITATING TO
EYES & RESPIRATORY TRACT. SIGNS & SYMP TOMS SIMILAR TO SWALLOWING.
SWALLOWING:DIZZINESS, INCOORDINATION, NAUSEA, VOMITING, DIARRHEA,
GENERAL WEAKNESS. \*

Effects of Overexposure:\* INGESTION OF SIGNIFICANT QUANTITIES MAY RESULT IN RED BLOOD CELL HEMOLYSIS.

Medical Cond Aggravated by Exposure: MAY AGGRAVATE AN EXISTING DERMATITIS.

#### **First Aid**

First Aid:EYES: IMMEDIATELY FLUSH EYES THOROUGHLY WITH WATER AND CONTINUE WASHING FOR SEVERAL MINUTES. OBTAIN MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. FLUSH SKIN WITH WATER. INHALATION: REMOVE TO FRESH AIR. SWALLOWING: IF PATIENT IS CONSCIOUS AND HAS A GAG REFLEX, GIVE TWO GLASSES OF WATER. INDUCE VOMITING. OBTAIN MEDICAL ATTENTION.

## Fire Fighting

Flash Point Method:CC
Flash Point:NONCOMBUSTIBLE

Extinguishing Media: TYPE A, B, C, OR COMBINATION TYPE

#### **Accidental Release**

Spill Release Procedures: DIKE AND CONTAIN SPILLS. ABSORB WITH SUITABLE MATERIAL. COLLECT MATERIAL INTO SUITABLE CONTAINERS AND DISPOSE OF PROPERLY.

### Handling

Handling and Storage Precautions: DO NOT ALLOW PRODUCT TO FREEZE.

## **Exposure Controls**

Respiratory Protection:IF ADEQUATE VENTILATION IS NOT MAINTAINED RESPIRATORS (OSHA/NIOSH APPROVED) MAY BE NECESSARY. IF EXPOSURE TO SPRAY MIST EXISTS, WEAR NIOSH APPROVED ORGANIC VAPOR/PARTICULATE RESPIRATOR.

Ventilation:LOCAL EXHAUST VENTILATION IS RECOMMENDED. Protective Gloves:IMPERVIOUS, CHEMICAL RESISTANT GLOVES Supplemental Safety and Health

## **Chemical Properties**

Boiling Pt:B.P. Text:212F,100C

Vapor Density:Spec Gravity:1.015 (H2O=1)

Evaporation Rate & Reference: LESS THAN 1 (BU AC=1)

Solubility in Water: DILUTABLE

Appearance and Odor: WHITE LIQUID, SLIGHT ODOR

### **Stability**

Stability Indicator/Materials to Avoid:YES

## Disposal

Waste Disposal Methods: DISPOSE OF PRODUCT IN ACCORDANCE WITH LOCAL, COUNTY, STATE, AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.