

WATER MASTER WATERBORNE TOP COAT, 15TC, SPRAYABLE, SATIN

MSDS Number

BXBVH

National Stock Number

8010-01-397-3579

Product Name

WATER MASTER WATERBORNE TOP COAT, 15TC, SPRAYABLE, SATIN

Manufacturer

ALTERNATIVE MATERIALS TECHNOLOGY INC

Product Identification

Product ID: WATER MASTER WATERBORNE TOP COAT, 15TC, SPRAYABLE, SATIN

MSDS Date: 11/02/1994

FSC: 8010

NIIN: 01-397-3579

MSDS Number: BXBVH

Responsible Party

ALTERNATIVE MATERIALS TECHNOLOGY, INC

1266 HUMBOLDT AVENUE

CHICO, CA 95928

US

Emergency Phone: 916-894-3585

Info Phone: 916-894-3585

Cage: 0ZXD0

Contractor

ALTERNATIVE MATERIALS TECHNOLOGY, INC

CHICO, CA 95928

US

916-894-3585

Cage: 0ZXD0

Ingredients

DIPROPYLENE GLYCOL MONOMETHYL ETHER (SARA III)

CAS: 34590-94-8

RTECS: JM1575000

Fraction By Weight: 2.25%

OSHA PEL100 PPM (SKIN)

ACGIH TLV: 100 PPM (SKIN)

PROPYLENE GLYCOL MONO-TERT-BUTYL ETHER

CAS: 57018-52-7

Fraction By Weight: 4.5%

PROPYLENE GLYCOL N-BUTYL ETHER

CAS: 5131-66-8

RTECS: UA7700000

Fraction By Weight: 2.25%

222.62 GRAMS/LITER MINUS

RTECS: 9999999VO

0.79 POUNDS/GALLON. 95.01

RTECS: 9999999VO

Hazards

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES
Health Hazards Acute and Chronic: EYE: SEVERE IRRITATION (DIRECT CONTACT). SKIN: SLIGHT IRRITATION (REPEATED OR PROLONGED CONTACT).
INHALATION: (EXTREMELY HIGH CONCENTRATIONS) IRRITATING TO EYES & RESPIRATORY TRACT. SIGNS & SYMPTOMS OF TOXICITY ARE SIMILAR TO THOSE OF SWALLOWING. SWALLOWING: HEADACHE, DIZZINESS, INCOORDINATION, NAUSEA, VOMITING, *
Effects of Overexposure: * DIARRHEA, AND GENERAL WEAKNESS. INGESTION OF SIGNIFICANT QUANTITIES MAY RESULT IN RED BLOOD CELL HEMOLYSIS.
Medical Cond Aggravated by Exposure: MAY AGGRAVATE AN EXISTING DERMATITIS.

First Aid

First Aid: EYES: IMMEDIATELY FLUSH EYES THOROUGHLY WITH WATER AND CONTINUE FOR SEVERAL MINUTES. OBTAIN MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. FLUSH SKIN WITH WATER. INHALATION: REMOVE TO FRESH AIR. SWALLOWING: IF PATIENT IS CONSCIOUS AND HAS A GAG REFLEX, GIVE TWO GLASSES OF WATER. INDUCE VOMITING. OBTAIN MEDICAL ATTENTION.

Fire Fighting

Flash Point Method: CC
Flash Point: NONCOMBUSTIBLE
Extinguishing Media: TYPE A, B, C, OR COMBINATION TYPE

Accidental Release

Spill Release Procedures: DIKE AND CONTAIN SPILLS. ABSORB WITH SUITABLE MATERIAL. COLLECT MATERIAL INTO SUITABLE CONTAINERS AND DISPOSE OF PROPERLY.

Handling

Handling and Storage Precautions: DO NOT ALLOW PRODUCT TO FREEZE! DO NOT STORE BELOW 40F.

Exposure Controls

Respiratory Protection: IF ADEQUATE VENTILATION IS NOT MAINTAINED, RESPIRATORS (OSHA/NIOSH APPROVED) MAY BE NECESSARY. IF EXPOSURE TO SPRAY MIST EXISTS, WEAR NIOSH APPROVED ORGANIC VAPOR/PARTICULATE RESPIRATOR.
Ventilation: LOCAL EXHAUST VENTILATION IS RECOMMENDED.
Protective Gloves: IMPERVIOUS, CHEMICAL RESISTANT GLOVES
Supplemental Safety and Health

Chemical Properties

Boiling Pt: B.P. Text: 304F, 151C
Vapor Density: Spec Gravity: 1.008 (H₂O=1)
Evaporation Rate & Reference: LESS THAN 1 (BU AC=1)
Solubility in Water: DILUTABLE
Appearance and Odor: CLEAR OR COLORED LIQUID, SLIGHT ODOR

Stability

Stability Indicator/Materials to Avoid: YES

Disposal

Waste Disposal Methods: DISPOSE OF PRODUCT IN ACCORDANCE WITH LOCAL, COUNTY, STATE, AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.