

## **SIKAFLEX 15LM CAPITAL TAN, 440**

### **MSDS Number**

BXDHS

### **National Stock Number**

8030-00N058608

### **Product Name**

SIKAFLEX 15LM CAPITAL TAN, 440

### **Manufacturer**

SIKA CORP

### **Product Identification**

Product ID:SIKAFLEX 15LM CAPITAL TAN, 440

MSDS Date:11/06/1989

FSC:8030

NIIN:00N058608

MSDS Number: BXDHS

### **Responsible Party**

SIKA CORP

201 POLITO AVE

LYNDHURST , NJ 07071

US

Emergency Phone: 800-424-9300 (CHEMTREC)

Info Phone: 201-933-8800

Cage: OPMN0

### **Contractor**

SIKA CORPORATION

LYNDHURST, NJ 07071

US

201-933-8800

Cage: OPMN0

### **Ingredients**

CALCIUM CARBONATE; (MARBLE) (LIMESTONE)

CAS: 1317-65-3

RTECS: EV9580000

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST

CALCIUM OXIDE

CAS: 1305-78-8

RTECS: EW3100000

OSHA PEL5 MG/M3

ACGIH TLV: 2 MG/M3

XYLENE; (MIXED ISOMERS) (SARA 313) (CERCLA)

CAS: 1330-20-7

RTECS: ZE2100000

OSHA PEL100 PPM

ACGIH TLV: 100 PPM/150STEL

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

## Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: INHAL: MAY CAUSE REVERSIBLE

INFLAMM EFT ON UPPER RESP SYS. CAUSES ALLERGIC SENSIT IN

SUBSTANCIAL PROPORTION OF HUMANS/ANIMALS IN NORM TISS AFTER RPTD

EXPOS. SKIN: MAY CAUSE REVERSIBLE INFLAMM E FT ON SKIN/TISS AT SITE

OF CONT. CAUSESALLERGIC SENSIT IN SUBSTANCIAL PROPORTION OF

HUMANS/ANIMALS IN (EFTS OF OVEREXP)

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:HLTH HAZ: NORM TISS AFTER RPTD EXPOS. EYES:

CAUSES IRRIT. INGEST: MAY CAUSE EFTS TO GI TRACT, USUALLY RESULTING

FROM INGEST OF MATLS, SUCH AS IRRIT, NAUS, GI DISORDERS,

ULCERATION, DIARR/CONSTIPATION.

Medical Cond Aggravated by Exposure:ASTHMA TYPE CONDITIONS, CHRONIC

BRONCHITIS AND OTHER CHRONIC RESPIRATORY CONDITIONS. RECURRENT SKIN

ECZEMA, PRESENSITIZATION TO PRODUCT.

## First Aid

First Aid:INHAL: REMOVE TO FRESH AIR. IF BREATHING HAS STOPPED,  
INSTITUTE ARTIFICIAL RESPIRATION. CONSULT MD. SKIN: WASH THOROUGHLY  
WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. IF SYMPTOMS  
PERSIST CONSULT MD. EYES: RINSE THOROUGHLY WITH WATER FOR AT LEAST  
15 MINUTES. CONSULT MD. INGEST: DILUTE WITH WATER. CONTACT MD.

## Fire Fighting

Flash Point:105F,41C

Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL.

Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL  
PROTECTIVE EQUIPMENT .

Unusual Fire/Explosion Hazard:DURING A FIRE, IRRITATING AND/OR TOXIC  
GASES AND AEROSOLS FROM THE DECOMPOSITION/COMBUSTION PRODUCTS MAY  
BE PRESENT.

## Accidental Release

Spill Release Procedures:WEAR SUITABLE PROTECTIVE EQUIPMENT. CONTAIN  
SPILL AND COLLECT WITH ABSORBENT MATERIAL AND TRANSFER INTO  
SUITABLE CONTAINERS. AVOID CONTACT.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

## Handling

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS & OPEN  
FLAME. STORE IN TIGHTLY CLOSED CONTR & PROTECT FROM MOISTURE &  
FOREIGN MATL. STOR TEMP 32F MIN, 122F MAX.

Other Precautions:IF CLOSED CONTR OF MATL IS EXPOSED TO HEAT, PRESS CAN  
BUILD UP. IF MOISTURE ENTERS DRUM, PRESS BUILD UP DUE TO RXN. AT  
MAX STOR TEMP NOTED, MATL MAY POLYMERIZE W/OUT HAZ. IDEAL STOR TEMP  
IS 50-81F.

## Exposure Controls

Respiratory Protection:NIOSH/MSHA APPROVED ORGANIC VAPOR RESPIRATOR  
RECOMMENDED.

Ventilation:LOCAL AND MECHANICAL EXHAUSTS HIGHLY RECOMMENDED.

Protective Gloves:CHEM RESIST RUBBER/PLASTIC GLOVES.

Eye Protection:ANSI APPRVD CHEM WORKERS GOGGS .

Other Protective Equipment:WEAR LONG SLEEVE SHIRT AND LONG PANTS TO

AVOID SKIN CONTACT.  
Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.  
Supplemental Safety and Health  
NONE SPECIFIED BY MANUFACTURER.

## Chemical Properties

Vapor Density:HVR/AIR  
Spec Gravity:1.19  
Evaporation Rate & Reference:SLOWER THAN ETHER  
Appearance and Odor:PASTE WITH AROMATIC ODOR  
Percent Volatiles by Volume:

## Stability

Stability Indicator/Materials to Avoid:YES  
WATER, ALCOHOL, AMINES.  
Stability Condition to Avoid:OPEN FLAME, HEAT.  
Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE,  
OXIDES OF NITROGEN.

## Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE &  
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.