
KRYLON GUIDELINE SPRAY PAINT (AEROSOL), 7121 YELLOW

MSDS Number

BXGJX

National Stock Number

8010-00N059006

Product Name

KRYLON GUIDELINE SPRAY PAINT (AEROSOL), 7121 YELLOW

Manufacturer

BORDEN INC

Product Identification

Product ID:KRYLON GUIDELINE SPRAY PAINT (AEROSOL), 7121 YELLOW

MSDS Date:06/30/1986

FSC:8010

NIIN:00N059006

MSDS Number: BXGJX

Responsible Party

BORDEN INC

180 EAST BROAD ST

COLUMBUS , OH 43215

US

Emergency Phone: 614-431-6600

Info Phone: 800-848-9400

Cage: 07982

Contractor

BORDEN INC

208

COLUMBUS, OH 43215-3705

US

614-225-6124

Cage: 07982

Ingredients

METHANOL; (METHYL ALCOHOL) (SARA 313) (CERCLA)

CAS: 67-56-1

RTECS: PC1400000

Fraction By Weight: 3.7-4.2%

OSHA PEL200 PPM, S

ACGIH TLV: 200 PPM;250 STEL, S

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

PROPANE

CAS: 74-98-6

RTECS: TX2275000

Fraction By Weight: 12%
OSHA PEL1000 PPM
ACGIH TLV: ASPHYXIA NT

PROPANE, 2-METHYL-; (ISOBUTANE)
CAS: 75-28-5
RTECS: TZ4300000

Fraction By Weight: 8-12%
OSHA PELN/K
ACGIH TLV: N/K

4.8-12.2.
CAS: 108-88-3
RTECS: XS5250000
Fraction By Weight:
OSHA PEL200 PPM
ACGIH TLV: 50 PPM, S
EPA Report Quantity: 1000 LBS
DOT Report Quantity: 1000 LBS

HEXANE; (N-HEXANE) (CERCLA)
CAS: 110-54-3
RTECS: MN9275000
Fraction By Weight: 0-10.4%
OSHA PEL500 PPM
ACGIH TLV: 50 PPM
EPA Report Quantity: 1 LB
DOT Report Quantity: 1 LB

5.5-17.4.
CAS: 1330-20-7
RTECS: ZE2100000
Fraction By Weight:
OSHA PEL100 PPM
ACGIH TLV: 100 PPM;150 STEL
EPA Report Quantity: 1000 LBS
DOT Report Quantity: 1000 LBS

LIGROINE; (VM&P NAPHTHA)
CAS: 8032-32-4
RTECS: OI6180000
Fraction By Weight: 3.7-5.9%

OSHA PEL300 PPM

ACGIH TLV: 300 PPM

CHRONIC EXPOS HAVE CAUSED PERIPHERAL

RTECS: 9999999ZZ

OVEREXP

RTECS: 9999999ZZ

SYMPS MAY INCL HDCH, DIZZ, NAUS, VOMIT, UNCON & EVEN

RTECS: 9999999ZZ

INCL HDCH, DIZZ, NAUS, VOMIT, UNCON & EVEN ASPHY.

RTECS: 9999999ZZ

HAZS. SEEK CONSULTATION FROM APPROP HLTH

RTECS: 9999999ZZ

INFORMATION .

RTECS: 9999999ZZ

LIDS. CALL MD.

RTECS: 9999999ZZ

BE PROVIDED TO KEEP AIR CONTAM CONC LEVELS BELOW

RTECS: 9999999ZZ

CONTROL TECHNIQUES MAY BE USED TO EFTIVELY MIN

RTECS: 9999999ZZ

ISOLATION & REMOTE CONTROL IN COMBINATION W/APPROP

RTECS: 9999999ZZ

THESE TECHNIQUES MAY NOT NECESSARILY ADDRESS ALL

RTECS: 9999999ZZ

RECS THAT YOU CONSULT W/EXPERTS OF YOUR CHOICE TO

RTECS: 9999999ZZ

Fire Fighting

Extinguishing Media:IN CASE OF FIRE, USE DRY CHEMICAL, FOAM OR CO*2.

Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT . WATER MAY BE INEFFECTIVE, BUT SHOULD BE USED TO KEEP FIRE-EXPOSED CONTAINERS COOL.

Unusual Fire/Explosion Hazard:EXTREMELY FLAMM. CONTENTS UNDER PRESS; EXPOS TO HIGH TEMP MAY CAUSE BURSTING. AVOID RADIATORS, STOVES, DIRECT SUNLIGHT/OTHER HEAT SOURCE. DO NOT (SUPP DATA)

Exposure Controls

Supplemental Safety and Health

Chemical Properties

Vapor Pres:SUPP DATA

Vapor Density:HVR/AIR

Spec Gravity:LTR/WATER

Evaporation Rate & Reference:FASTER THAN BUTYL ACETATE

Solubility in Water:SLIGHT

Percent Volatiles by Volume:76(WT)

Stability

Stability Indicator/Materials to Avoid:YES

NONE SPECIFIED BY MANUFACTURER.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.