

HERITAGE GLOSS LATEX HOUSE PAINT, 5-8302

MSDS Number

BXGMS

National Stock Number

8010-00N059145

Product Name

HERITAGE GLOSS LATEX HOUSE PAINT, 5-8302

Manufacturer

WATTYL PAINT CORP

Product Identification

Product ID:HERITAGE GLOSS LATEX HOUSE PAINT, 5-8302

MSDS Date:09/18/1992

FSC:8010

NIIN:00N059145

MSDS Number: BXGMS

Responsible Party

WATTYL PAINT CORP

5275 PEACHTREE INDUSTRIAL BLVD

ATLANTA , GA 30341

US

Emergency Phone: 404-455-7000

Info Phone: 404-455-7000

Cage: WATTL

Contractor

WATTYL PAINT CORP

ATLANTA, GA 30341

US

404-455-7000

Cage: WATTL

Ingredients

NON-HAZARDOUS INGREDIENTS

OSHA PELN/K

ACGIH TLV: N/K

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE:INHALATION:W/POOR VENTILATION, VAPOR OR MIST MAY IRRITATE RESPIRATORY MUCOUS MEMBRANES, CAUSING HEADACHE & NAUSEA. EYE CONTACT:PRIMARY IRRITANT. CHRONIC:NONE RECOGNIZED.

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid

First Aid:INHAL:REMOVE TO FRESH AIR. EYE:FLUSH IMMEDIATELY W/LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. TAKE TO MD FOR MEDICAL

TREATMENT. SKIN:REMOVE W/SOAP & WATER. IF DRENCHED, REMOVE CONTAMINATED. INGES T:IF VICTIM IS CONSCIOUS, GIVE 2 GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMITING. CONSULT MD OR POISON CONTROL CENTER.

Fire Fighting

Flash Point:NONE
Lower Limits:NONE
Extinguishing Media:WATER FOG (APPLICABLE ONLY FOR COOLING CLOSED CONTAINERS).
Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT .
Unusual Fire/Explosion Hazard:CLOSED CONTAINER MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures:VENTILATE AS DESCRIBED IN SPECIAL PROTECTION INFO SECTION. AVOID UNNECESSARY SKIN CONTACT. COLLECT BY ABSORPTION, SHOVEL &/OR WET MOPPING.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:DO NOT STORE >120F. CLOSE CONTAINER AFTER EACH USE. DO NOT TAKE INTERNALLY.
Other Precautions:PIGMENTED PAINT & COATINGS (THOSE WHICH ARE OPAQUE, COLORED/WHICH HAVE REDUCED GLOSS WHEN DRY) MAY CONTAIN MATLS SUCH AS SILICA, TALC, CALCIUM CARBONATE, TITANIUM DIOXIDE, ETC, WHICH ARE HAZ TO INHALE IN DRY POWDER FORM. THESE HAZS (SUPDAT)

Exposure Controls

Respiratory Protection:DURING SPRAY APPLICATION USE NIOSH/MSHA APPROVED MECHANICAL FILTER RESPIRATOR TO REMOVE SOLID AIRBORNE PARTICLES OF OVERSPRAY.
Ventilation:PROVIDE SUFFICIENT VENT, IN VOL & PATTERN, TO INSURE VAP CONCS WELL BELOW ANY TLV & LEL LISTED.
Protective Gloves:IMPERVIOUS GLOVES .
Eye Protection:ANSI APPROVED CHEM WORKERS GOGGS .
Other Protective Equipment:EYE WASH FOUNTAIN & DELUGE SHOWER WHICH MEET ANSI DESIGN CRITERIA .
Work Hygienic Practices:OBSERVE GOOD SANITARY PRACTICES.
Supplemental Safety and Health
OTHER PREC:ARE NOT BELIEVED TO BE PRESENT WHEN POWDERS ARE DISPERSED IN LIQ COATINGS. HOWEVER, PRECS SHOULD BE CAREFULLY OBSERVED & NIOSH/MSHA APPRVD RESPS SHOULD ALSO BE USED IF DRIED COATING IS SAND ED/ABRADED IN SUCH A WAY AS TO PRDCE DUST.

Chemical Properties

Boiling Pt:B.P. Text:212F,100C
Vapor Density:LTR/AIR
Spec Gravity:1.1-1.26
Evaporation Rate & Reference:SLOWER THAN ETHER
Appearance and Odor:NONE SPECIFIED BY MANUFACTURER.
Percent Volatiles by Volume:63-69

Stability

Stability Indicator/Materials to Avoid:YES
NONE KNOWN.
Stability Condition to Avoid:HIGH TEMPERATURES.
Hazardous Decomposition Products:WHEN HEATED TO DECOMPOSITION, AS IN A FIRE OR IN WELDING, MAY PRODUCE TOXIC FUMES SUCH AS CARBON MONOXIDE.

Disposal

Waste Disposal Methods:DISPOSE I/A/W LOCAL, STATE & FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.