

## **RISOGRAPH RC INK, GREEN (S-978)**

### **MSDS Number**

BXGXF

### **National Stock Number**

7510-00N059466

### **Product Name**

RISOGRAPH RC INK, GREEN (S-978)

### **Manufacturer**

RISO INC

### **Product Identification**

Product ID:RISOGRAPH RC INK, GREEN (S-978)

MSDS Date:07/18/1994

FSC:7510

NIIN:00N059466

MSDS Number: BXGXF

### **Responsible Party**

RISO INC

300 ROSEWOOD DR, SUITE 210

DANVERS , MA 01923

US

Emergency Phone: 508-777-7377

Info Phone: 508-777-7377

Cage: 0LJK9

### **Contractor**

RISO INC

DANVERS, MA 01923

US

508-777-7377

Cage: 0LJK9

### **Ingredients**

MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED (MILDLY)

CAS: 64742-55-8

RTECS: PY8036500

Fraction By Weight: 0-15%

OSHA PEL5 MG/M3 (OIL MIST)

ACGIH TLV: 5 MG/M3 (OIL MIST)

MINERAL OIL,PETROLEUM DISTILLATES,ACID-TREATED HEAVY

CAS: 64742-18-3

RTECS: PY8032000

Fraction By Weight: 0-15%

OSHA PEL5 MG/M3 (OIL MIST)

ACGIH TLV: 5 MG/M3 (OIL MIST)

#### GLYCEROL

CAS: 56-81-5

RTECS: MA8050000

OSHA PEL15 MG/M3 (MIST)

ACGIH TLV: 10 MG/M3 (MIST)

#### CARBON BLACK

CAS: 1333-86-4

RTECS: FF5800000

OSHA PEL3.5 MG/M3

ACGIH TLV: 3.5 MG/M3; 9495

#### KEROSENE (PETROLEUM), HYDROTREATED; (ALIPHATIC HYDROCARBON)

CAS: 64742-47-8

RTECS: OA5504000

OSHA PELN/K

ACGIH TLV: N/K

#### WATER

CAS: 7732-18-5

RTECS: ZC0110000

Fraction By Weight: 0-60%

OSHA PELN/K

ACGIH TLV: N/K

#### OTHERS

Fraction By Weight: 0-60%

OSHA PELN/K

ACGIH TLV: N/K

### Fire Fighting

Flash Point Method:PMCC

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM OR WATER SPRAY.

Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT . RISOGRAH RC INK IS NOT COMBUSTIBLE.

Unusual Fire/Explosion Hazard:NO UNUSUAL FIRE AND EXPLOSION HAZARDS.

### Exposure Controls

Supplemental Safety and Health

### Chemical Properties

Boiling Pt:B.P. Text:212F,100C

Melt/Freeze Pt:M.P/F.P Text:Spec Gravity:(SUP DAT)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:EXTREMELY VISCOUS COLORED LIQUID WITH SLIGHT ODOR

### Stability

Stability Indicator/Materials to Avoid: YES  
STRONG OXIDIZING AGENTS.  
Stability Condition to Avoid: NOT APPLICABLE.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.