
ODORLESS, SEMI-GLOSS, INTERIOR, ALKYD, ENAMEL, 23717, IVORY

MSDS Number

BXGXX

National Stock Number

8010-00-225-7961

Product Name

ODORLESS, SEMI-GLOSS, INTERIOR, ALKYD, ENAMEL, 23717, IVORY

Manufacturer

FARWEST PAINT MFG CO

Product Identification

Product ID: ODORLESS, SEMI-GLOSS, INTERIOR, ALKYD, ENAMEL, 23717, IVORY

MSDS Date: 04/01/1993

FSC: 8010

NIIN: 00-225-7961

MSDS Number: BXGXX

Responsible Party

FARWEST PAINT MFG CO

4522 S 133 ST

TUKWILA, WA 98168

US

Emergency Phone: 206-941-1619

Info Phone: 206-244-8844

Preparer: NORMA HABEEB

Cage: 6F266

Contractor

FARWEST PAINT MANUFACTURING CO

TUKWILA, WA 98168

US

206-244-8844

Cage: 6F266

Ingredients

ODORLESS PETROLEUM NAPHTHA

CAS: 64742-48-9

Fraction By Weight: 19.81%

OSHA PEL100 PPM

ACGIH TLV: 100 PPM

ODORLESS MINERAL SPIRITS

CAS: 64741-65-7

Fraction By Weight: 8.45%

OSHA PEL100 PPM

ACGIH TLV: 100 PPM

365 G/L; 3.05 LB/GL

RTECS: 9999999VO

Fire Fighting

Flash Point Method:TCC

Flash Point:120F,49C

Lower Limits:1.2%

Upper Limits:6.0%

Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER FOG, ANY CLASS B EXTINGUISHING AGENT. USE WATER TO KEEP ADJACENT CONTAINERS COOL.

Fire Fighting Procedures:FIREFIGHTERS & OTHERS EXPOSED TO VAPORS OR COMBUSTION PRODUCTS SHOULD WEAR SCBA. EVACUATE AREA OF UNPROTECTED PERSONNEL. WEAR PROTECTIVE CLOTHING.

Unusual Fire/Explosion Hazard:VAPORS MAY FORM AN EXPLOSIVE MIXTURE IN AIR & MAY BE IGNITED BY SPARKS, PILOT LIGHTS. CLOSED CONTAINERS MAY RUPTURE WHEN EXPOSED TO EXTREME HEAT.

Exposure Controls

Supplemental Safety and Health

Chemical Properties

HCC:F4

Boiling Pt:B.P. Text:346 TO 406F

Vapor Pres:1.0 @ 20C

Vapor Density:>AIR

Viscosity:75-100 KU

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:NIL

Appearance and Odor:WHITE OR TINTED LIQUID WITH SLIGHT ODOR

Percent Volatiles by Volume:49

Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDANTS, ACIDS, BASES AND EPOXY HARDENERS UNDER CONTROLLED CONDITIONS.

Stability Condition to Avoid:HEAT, SPARKS AND OPEN FLAMES. IF PRODUCT CONTAINS ALUMINUM, MOISTURE IN CLOSED CONTAINERS WILL GENERATE HYDROGEN GAS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.