

LA TTE-508C, FS22-601

MSDS Number

BXGYN

National Stock Number

8010-00-584-3087

Product Name

LA TTE-508C, FS22-601

Manufacturer

LASTING PAINTS INC

Product Identification

Product ID:LA TTE-508C, FS22-601

MSDS Date:11/18/1993

FSC:8010

NIIN:00-584-3087

MSDS Number: BXGYN

Responsible Party

LASTING PAINTS, INC

200 SOUTH FRANKLINTOWN ROAD

BALTIMORE , MD 21223

US

Emergency Phone: 410-947-6306

Info Phone: 410-947-6300

Cage: GO423

Contractor

LASTING PAINTS, INC.

BALTIMORE, MD 21223

US

410-947-6300/800-368-2205

Cage: GO423

Ingredients

ALIPHATIC DISTILLATE (STODDARD) (VAPOR PRESSURE 10.0 MM HG)

CAS: 8052-41-3

RTECS: WJ8925000

Fraction By Weight: 25.5%

ACGIH TLV: 100 PPM

ORGANOCLAY (CONTAINS LESS THAN 1% CRYSTALLINE SILICA)

Fraction By Weight: 1.0%

Hazards

Health Hazards Acute and Chronic:INHALATION: IRRITATION OF RESPIRATORY TRACT OR ACUTE NERVOUS SYSTEM DEPRESSION CHARACTERIZED BY: HEADACHE, DIZZINESS, STAGGERING, CONFUSION, COMA. SKIN OR EYES: PRIMARY IRRITATION OR SENSITIZER.

Effects of Overexposure:REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND

NERVOUS SYSTEM DAMAGE.

Medical Cond Aggravated by Exposure:INHALATION BY PERSONS WITH RESPIRATORY PROBLEMS COULD HAVE THE CONDITION ADDITIONALLY AGGRAVATED.

First Aid

First Aid:INHAL: REMOVE TO FRESH AIR. RESTORE BREATHING. TREAT SYMPTOMATICALLY. CONSULT PHYSICIAN. EYE (SPLASH): FLUSH IMMEDIATELY WITH LARGE AMOUNT WATER FOR 15 MIN. CONSULT PHYSICIAN. SKIN (SPLASH): WASH WITH SOAP & WATER. REMOVE CONTAMINATED CLOTHING. CONSULT PHYSICIAN IF IRRITATION PERSISTS. INGEST: DRINK 1-2 GLASSES WATER TO DILUTE. DO NOT INDUCE VOMIT. CONSULT PHYSICIAN/POISON CONTROL IMMEDIATELY. TREAT SYMPTOMATICALLY.

Fire Fighting

Flash Point:110F,43C

Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER FOG. USE ANY CLASS B APPROVED FIRE EXTINGUISHER.

Fire Fighting Procedures:KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRIC EQUIPMENT, SPARKS, FLAME. CLOSED CONTAINERS MAY EXPLODE WITH HEAT. APPLICATION TO HOT SURFACES REQUIRE SPECIAL PRECAUTION.

Unusual Fire/Explosion Hazard:WATER SPRAY MAY BE INEFFECTIVE. USE TO COOL CONTAINERS. IF USED, FOG NOZZLES ARE PREFERRED. USE FULL PROTECTIVE EQUIPMENT INCLUDING SBCA.

Accidental Release

Spill Release Procedures:REMOVE SOURCES OF IGNITION AND PROVIDE VENTILATION. USE SCOOP ON LARGE SPILLS AND ABSORBENT MATERIAL ON SMALL SPILLS. AVOID BREATHING VAPOR AND USE RESPIRATORY PROTECTION. FLUSH AREA WITH WATER. HOLD CLEAN-UP MATERIALS FOR PROPER DISPOSAL.

Handling

Handling and Storage Precautions:STORE AWAY FROM HEAT, SPARKS, OPEN FLAME IN WELL VENTED AREA. DON'T STORE ABOVE 100F. KEEP CLOSURE TIGHT & CONTAINER UPRIGHT. DON'T PUNCTURE, DRAG, SLIDE.

Other Precautions:DO NOT GET IN EYES. AVOID SKIN CONTACT. PREVENT PROLONGED OR REPEATED BREATHING OF VAPOR OR SPRAY MIST. DRUMS SHOULD BE GROUNDED WHEN POURING. RESTRICT FREE FALL OF LIQUID TO A FEW INCHES TO AVOID GENERATION OF STATIC CHARGE.

Exposure Controls

Respiratory Protection:UNRESTRICTED VENTILATION: MECHANICAL FILTER TO REMOVE SOLID PARTICLES. RESTRICTED VENTILATION: USE CHEMICAL/MECHANICAL FILTER TO REMOVE BOTH VAPOR AND SOLIDS. NO VENTILATION: USE AIR LINE TYPE RESPIRATOR.

Ventilation:DESIGNED AND MAINTAINED TO PROVIDE VOLUME AND PATTERN TO PREVENT CONCENTRATIONS IN EXCESS OF TLV.

Protective Gloves:USE NEOPRENE OR OTHER IMPERVIOUS TYPE.

Eye Protection:GOGGLES OR SIDE-SHIELD SPECTACLES.

Other Protective Equipment:HAVE EYE WASH STATION AND SAFETY SHOWERS AVAILABLE.

Work Hygienic Practices:WASH HANDS BEFORE EATING OR USING WASHROOM. SMOKE IN DESIGNATED AREAS ONLY.

Supplemental Safety and Health

REMOVE DECOMPOSITION PRODUCTS DURING WELDING OR BURNING.

Chemical Properties

Boiling Pt:B.P. Text:323 TO 390F

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:45.6

Stability

Stability Indicator/Materials to Avoid:YES

OXIDIZING AGENTS

Stability Condition to Avoid:HEAT AND OPEN FLAME

Hazardous Decomposition Products: CARBON MONOXIDE AND OTHER ORGANIC MATERIALS MAY BE FORMED DURING COMBUSTION.

Disposal

Waste Disposal Methods: DISPOSAL SHOULD BE DONE IN ACCORDANCE WITH ALL FEDERAL, STATE & LOCAL REGULATIONS. BEFORE ATTEMPTING CLEAN UP, REFER TO HAZARD CAUTION INFORMATION IN OTHER SECTIONS OF THE SHEET.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.