

1-COAT, TT-P-2756, 26231, 03GY407

MSDS Number

BXHDX

National Stock Number

8010-01-354-0972

Product Name

1-COAT, TT-P-2756, 26231, 03GY407

Manufacturer

DEFT INC

Product Identification

Product ID:1-COAT, TT-P-2756, 26231, 03GY407

MSDS Date:12/01/1993

FSC:8010

NIIN:01-354-0972

Kit Part:Y

MSDS Number: BXHDX

Responsible Party

DEFT, INC

17451 VON KARMAN AVE

IRVINE , CA 92714

US

Emergency Phone: 800-424-9300 CHEMTREC

Info Phone: 714-474-0400

Preparer: NORM GAUL

Cage: 5M511

Contractor

DEFT, INC

IRVINE, CA 92714-6205

US

714-474-0400

Cage: 5M511

Ingredients

PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE (VAPOR PRESSURE

CAS: 108-65-6

RTECS: AI8925000

Fraction By Weight:

N-BUTYL ACETATE (VAPOR PRESSURE 13 MM HG @ 68F)

CAS: 123-86-4

RTECS: AF7350000

Fraction By Weight: 5%

OSHA PEL150 PPM;STEL 200 PPM

ACGIH TLV: 150 PPM;STEL 200 PPM

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

XYLENE (SARA 313) (CERCLA) (VAPOR PRESSURE 21 MM HG @ 100F)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 0.07%

OSHA PEL100 PPM;STEL 150 PPM

ACGIH TLV: 100 PPM;STEL 150 PPM

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

METHYL ETHYL KETONE (SARA 313) (CERCLA) (VAPOR PRESSURE 70

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight: 9.47%

OSHA PEL200 PPM;STEL 300 PPM

ACGIH TLV: 200 PPM;STEL 300 PPM

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

2-4 PENTANEDIONE (VAPOR PRESSURE 6.9 MM HG @ 68F)

CAS: 123-54-6

RTECS: SA1925000

Fraction By Weight:

TOLUENE (SARA III) (CERCLA) (VAPOR PRESSURE 22 MM HG @ 68F)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 0.13%

OSHA PEL100 PPM;STEL 150 PPM

ACGIH TLV: 100 PPM;STEL 150 PPM

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

FLOW AGENT (VAPOR PRESSURE 0 MM HG)

CAS: 26376-86-3

Fraction By Weight:

ANTI MAR AGENT (VAPOR PRESSURE 0 MM HG)

Fraction By Weight:

ETHYL BENZENE (SARA 313) (VAPOR PRESSURE 7.1 MM HG @ 68F)

CAS: 100-41-4

RTECS: DA0700000

Fraction By Weight: 0.03%

OSHA PEL100 PPM;STEL 125 PPM
ACGIH TLV: 100 PPM;STEL 125 PPM
EPA Report Quantity: 1000 LBS
DOT Report Quantity: 1000 LBS

ETHYL 3-ETHOXYPROPIONATE (VAPOR PRESSURE 0.7 MM HG @ 68F)

CAS: 763-69-9

RTECS: UF3325000

Fraction By Weight:

DIBUTYL TIN DILAURATE (VAPOR PRESSURE 0.2 MM HG @ 320F)

CAS: 77-58-7

RTECS: WH7000000

Fraction By Weight:

OSHA PEL.1 MG/M3;STEL .1MG/M

271 G/L

RTECS: 9999999VO

Fire Fighting

Flash Point Method:TCC

Flash Point:23.0F,-5.0C

Lower Limits:1.00%

Upper Limits:13.10%

Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG, WATER SPRAY

Fire Fighting Procedures:FULL FIRE FIGHTING EQUIPMENT WITH SCBA, FULL PROTECTIVE CLOTHING. USE WATER TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP, AUTO IGNITION OR EXPLOSION.

Unusual Fire/Explosion Hazard:KEEP CONTAINER CLOSED. KEEP FROM HEAT, SPARKS, ELECT EQUIP, FLAME. CLOSED CONTAINER MAY EXPLODE W/HEAT. APPLICATION TO HOT SURFACE REQUIRES SPECIAL PRECAUTION**

Exposure Controls

Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:175 TO 401F

Vapor Density:>AIR

Spec Gravity:1.35534

Viscosity:*

Evaporation Rate & Reference:2.68 X N-BUTYL ACETATE

Solubility in Water:INSOLUBLE

Appearance and Odor:GRAY LIQUID WITH SOLVENT ODOR

Percent Volatiles by Volume:31.6

Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:HIGH TEMPERATURES, SPARKS OR OPEN FLAMES

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their

particular situation.