

SOLID COLOR LATEX STAIN, B22

MSDS Number

BXHJN

National Stock Number

8010-01-397-3865

Product Name

SOLID COLOR LATEX STAIN, B22

Manufacturer

THE SHERWIN WILLIAMS CO

Product Identification

Product ID: SOLID COLOR LATEX STAIN, B22

MSDS Date: 03/01/1991

FSC: 8010

NIIN: 01-397-3865

MSDS Number: BXHJN

Responsible Party

THE SHERWIN-WILLIAMS CO

101 PROSPECT AVE N W

CLEVELAND , OH 44115

US

Emergency Phone: 216-566-2917

Info Phone: 216-566-2902

Cage: DO693

Contractor

THE SHERWIN-WILLIAMS CO

CLEVELAND, OH 44115

US

216-566-2902

Cage: DO693

Ingredients

ETHYLENE GLYCOL (SARA III)(VAPOR PRESSURE 0.1 MM HG PPM)

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight: 0-2%

OSHA PELC 50 PPM

ACGIH TLV: C 50 PPM

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

QUARTZ

CAS: 14808-60-7

RTECS: VV7330000

Fraction By Weight: 0-24%

OSHA PEL0.1 MG/M3 RDUST

ACGIH TLV: 0.1 MG/M3 RDUST

CRISTOBALLTE

CAS: 14464-46-1

RTECS: VV7325000

Fraction By Weight: 0-2%

OSHA PEL0.05 MG/ME RDUST

ACGIH TLV: 0.05 MG/M3 RDUST

MICA

CAS: 12001-26-2

RTECS: VV8760000

Fraction By Weight: 0-2%

OSHA PEL3 MG/M3 RDUST

ACGIH TLV: 3 MG/M3 RDUST

TITANIUM DIOXIDE

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: 0-17%

OSHA PEL10(5) MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST

ZINC OXIDE

CAS: 1314-13-2

RTECS: ZH4810000

Fraction By Weight: 0-2%

OSHA PEL10 (5) MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST

Fire Fighting

Flash Point Method:PMCC

Flash Point:>199F,>93C

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, ALCOHOL FOAM

Fire Fighting Procedures:FULL PROTECTIVE EQUIP INCLUDING SCBA SHOULD BE USED. WTR SPRAY MAY BE INEFFECTIVE.IF WTR USED, FOG NOZZLES PREFERRED. WTR MAY BE USED TO COOL CLOSED CONTAINERS*

Unusual Fire/Explosion Hazard:*TOPREVENT PRESSURE BUILD-UP/POSSIBLE AUTOIGN OR EXPLOS WHEN EXPOSED TO EXTREME HEAT. CLSD CNTNR MAY EXPLODE DUE TO BUILD-UP PRESS WHEN EXPOSED TO EXTREME HEAT.

Exposure Controls

Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:212 TO 448F

Vapor Density:>AIR

Spec Gravity:1.1-1.4

pH:9.3

Evaporation Rate & Reference:Percent Volatiles by Volume:52-75%

Stability

Stability Indicator/Materials to Avoid:YES

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.