

## **SOLID COLOR LATEX STAIN, B22**

### **MSDS Number**

BXHJX

### **National Stock Number**

8010-01-397-3873

### **Product Name**

SOLID COLOR LATEX STAIN, B22

### **Manufacturer**

SHERWIN WILLIAMS CO

### **Product Identification**

Product ID: SOLID COLOR LATEX STAIN, B22

MSDS Date: 03/01/1991

FSC: 8010

NIIN: 01-397-3873

MSDS Number: BXHJX

### **Responsible Party**

SHERWIN-WILLIAMS CO

101 PROSPECT AVE N W

CLEVELAND , OH 44115-1042

US

Emergency Phone: 216-566-2917

Info Phone: 216-566-2902

Cage: 54636

### **Contractor**

SHERWIN-WILLIAMS CO THE

CLEVELAND, OH 44115-1042

US

800-251-2486/216-566-2242

Cage: 54636

### **Ingredients**

ETHYLENE GLYCOL (SARA III)

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight: 0-2%

OSHA PELC 50 PPM

ACGIH TLV: C 50 PPM

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

QUARTZ

CAS: 14808-60-7

RTECS: VV7330000

Fraction By Weight: 0-24%

OSHA PEL0.1 MG/M3 RDUST  
ACGIH TLV: 0.1 MG/M3 RDUST

CRISTOBALLTE  
CAS: 14464-46-1

RTECS: VV7325000  
Fraction By Weight: 0-2%  
OSHA PEL0.05 MG/M3 RDUST  
ACGIH TLV: 0.05 MG/M3 RDUST

MICA  
CAS: 12001-26-2  
RTECS: VV8760000  
Fraction By Weight: 0-2%  
OSHA PEL3 MG/M3 RDUST  
ACGIH TLV: 3 MG/M3 RDUST

TITANIUM DIOXIDE  
CAS: 13463-67-7  
RTECS: XR2275000  
Fraction By Weight: 0-17%  
OSHA PEL10(5) MG/M3 RDUST  
ACGIH TLV: 10 MG/M3 RDUST

ZINC OXIDE  
CAS: 1314-13-2  
RTECS: ZH4810000  
Fraction By Weight: 0-2%  
OSHA PEL10(5) MG/M3 RDUST  
ACGIH TLV: 10 MG/M3 RDUST

## Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:UNKNOWN IARC:UNKNOWN OSHA:NO  
Health Hazards Acute and Chronic:IRRIT OF EYES,SKIN & RESPIRATORY  
SYSTEM. MAY CAUSE NERVOUS SYSTEM DEPRESSION. EXTREME OVEREXPOSURE  
MAY RESULT IN UNCONSCIOUSNESS, POSSIBLY DEATH. HEADACHE, DIZZY,  
NAUSEA, LOSS OF COORDINATION ARE INDICATION OF EXCESSIVE  
OVEREXPOSURE TO VAPORS OR SPRAY MISTS. REDNESS, ITCHING, BURNING  
MAY INDICATE EXCESSIVE EXPOSURE.  
Explanation of Carcinogenicity:CRYSTALLINE SILICA IS LISTED BY IARC.  
LONG TERM EXPOSURE TO DUST MAY CAUSE LUNG DAMAGE, POSSIBLE CANCER.  
Effects of Overexposure:REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED  
OVEREXPOSURE TO SOLVENTS WITH BRAIN AND NERVOUS SYSTEM DAMAGE.  
PROLONGED OVEREXPOSURE TO SOLVENT INGREDIENTS IN SECTION II MAY  
CAUSE ADVERSE EFFECTS TO THE LIVER, AND URINARY SYSTEMS.

## First Aid

First Aid:INHALATION: IF AFFECTED, REMOVE FROM EXPOSURE. RESTORE

BREATHING. KEEP WARM & QUIET. SKIN: WASH AFFECTED AREA THOROUGHLY WITH SOAP & WATER. REMOVE CONTAMINATED CLOTHING & WASH BEFORE REUSE. EYE: FLUSH WITH LARGE AMOUNT OF WATER FOR 15 MINUTES. GET MEDICAL ATTENTION. SWALLOWING: GET MEDICAL ATTENTION.

## Fire Fighting

Flash Point Method: PMCC  
Flash Point: >199F, >93C  
Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, ALCOHOL FOAM  
Fire Fighting Procedures: USE FULL PROTECT EQUIP W/SCBA. WATER MAY BE INEFFECTIVE. IF USED FOG NOZZLES PREFERRED. USE TO COOL CLOSED CNTNR/PREVENT PRESSURE, AUTOIGNITION, OR EXPLOSION.  
Unusual Fire/Explosion Hazard: CLOSED CNTNR MAY EXPLODE (DUE TO BUILD UP PRESSURE) WHEN EXPOSED TO EXTREME HEAT.

## Accidental Release

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. VENTILATE AND REMOVE WITH INERT ABSORBENT.

## Handling

Handling and Storage Precautions: CONTENTS ARE COMBUSTIBLE. KEEP FROM HEAT/FLAME. CONSULT NFPA CODE. USE APPROVED BONDING, GROUNDING PROCEDURES. KEEP CLOSED WHEN NOT IN USE.\*\*  
Other Precautions: \*\*TRANSFER ONLY TO APPROVED CONTAINERS WITH COMPLETE & APPROPRIATE LABELS. DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN.

## Exposure Controls

Respiratory Protection: IF EXPOSURE CANNOT BE CONTROLLED VENTILATION, WEAR NIOSH/MSHA APPROVED ORGANIC VAPOR/PARTICULATE RESPIRATOR. WHEN SANDING/ABRADING DRIED FILM, WEAR NIOSH/MSHA APPROVED DUST/MIST RESP GENERATOR FROM PRODUCT, PAINT, OR ABRASIVE.  
Ventilation: LOCAL EXHAUST PREFERRED. GEN EXHAUST ACCEPTABLE IF EXPOSURE MAINTAINED  
Protective Gloves: RECOMMENDED BY GLOVE SUPPLIER  
Eye Protection: SAFETY GLASSES/UNPERFORATED SIDESHIELDS  
Work Hygienic Practices: WASH HANDS AFTER USING  
Supplemental Safety and Health  
USE ONLY WITH ADEQUATE VENTILATION. AVOID BREATHING VAPOR AND SPRAY MIST. AVOID CONTACT WITH EYES & SKIN.

## Chemical Properties

Boiling Pt: B.P. Text: 212 TO 448F  
Vapor Density: >AIR  
Spec Gravity: 1.1-1.4  
pH: 9.3  
Evaporation Rate & Reference: SLOWER THAN ETHER  
Percent Volatiles by Volume: 52-75%

## Stability

Stability Indicator/Materials to Avoid: YES  
Hazardous Decomposition Products: BY FIRE: CARBON DIOXIDE, CARBON MONOXIDE

## Disposal

Waste Disposal Methods: WASTE MAY BE HAZARDOUS AS DEFINED UNDER (RCRA) 40 CFR 261. TEST FOR EXTRACTABILITY TO DETERMINE THE APPLICABLE EPA HAZ. INCINERATE IN APPROVED FACILITY. WASTE FROM OTHER LATEX FINISHES NOT HAZ. DO NOT INCINERATE CLSD CNTNR. DISPOSE OF IN ACCORD W/REG

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their

particular situation.